

SIMPLY SMARTER COLLABORATION

The $\it 4K\ TRUTOUCH\ X\ series$ features InGlass $^{\rm m}$ technology for superior writing experience and combines advanced technology with elegance.



COLLABOARTION INTERACTIVE PRESENTATION

TRUTOUCH Xseries debuts with evolutionary innovation leading the way to a brand new user experience like you never expected.

COMMUNICATE BETTER, COLLABORATE EASIER

Featuring Montage UC sofeware for easy collaboration anytime, anywhere.






SUPERIOR WRITING EXPERIENCE

Advanced InGlass™ technology for responsive touch Digital Whiteboard with seamless writing experience.

CLEAR AND ROBUST IMAGE

X9 makes use of the latest optical bonding technology which reduces reflections resulting in improved contrast and reduced parallax. With 4K UHD resolution, the X9 delivers clear and robust images that give you the best video conferencing experience.



POWERED BY



Communication connect anything



Quick access annotation & intuitive interface



Wireless Collaboration

Connect with any Device



Video / Voice

All New Interface Communication



Multi-OS





Hand-Writing Recognition

FEATURES

Optical Bonding makes the touch panel more sturdy and protects the display from dust and moisture. **All-in-one** system requires no additional equipment such as camera microphone nor speakers. **With OPS slot**, users can install any of favorite Windows applications without limit.



USER INTERFACE

Efficient meetings on the go with easily accessible



Scheduling function for meeting room schedules.



Enhance communication with discussion board/annotation.













Become an expert with an intuitive interface.



One click share by Email or USB flash.



Model	X6	X8	Х9
		Display	
Backlight		LED	
Display Area	1431 × 806 mm	1662 × 942 mm	1897 × 1068 mm
Active Screen Size	65"	75"	86"
Display Ratio		16:9	
Resolution	3840 × 2160 Pixels		
Display Colors	8-bit	8-bit	10-bit
Brightness		≥320nit	
Contrast	4000:1	4000:1	1200:1
Response Time	8ms		
Viewing Angle		178°	
Life Time		≥30,000 hours	
		Speaker	
Speaker Position	Forward		
Rated Impedance	Ω8		
Freq. Response	80 - 18K Hz		
Output S.P.L.	88 ± 3dB		
Max. Power Output		15W × 2	
	Microphone		
Sensitivity		-38dB ± 3dB	
Freq. Response	62 - 12.5K Hz		
Polar Patterns	Omnidirectional		
THD +N (1K Hz @ +4dBu)	0.25% at 104dB SPL		
Quantity		4	
		Camera	
Position	Top \times 1 & Bottom \times 1 (Only one can use in the same time)		
Sensor	2M Pixels		
Lens	72°		
Video Resolution	1920 × 1080 @30fps (Max)		
		Electrical	
D	Maximum ≤250W	Maximum ≤400W	Maximum ≤450W
Power Consumption	Standby Mode ≤0.5W	Standby Mode ≦0.5W	Standby Mode ≤0.5W
Working Voltage		AC 100-240V, 50/60Hz	
		Touch	
Touch Surface	Optical Bonding Anti-Glare & Anti-Fingerprint Glass		
Transparency	80% - 90%		
Haze	≤5%		
Surface Hardness	7H		
Touch Technology	InGlass		
HID Support	HID		
Touch Points	20 Points in Windows/ 10 Points in Android		
Writing Tools	Nano Pen/ Finger/ Palm		
Touch Resolution	22855 × 12856	26394 × 14847	30320 × 17055
Scan Speed		150HZ	
Positioning Accuracy		±1.0mm	
Communication Interface	USB-A		
	Transportation/Storage		
Storage Temperature/ Humidity		-15℃ - 55℃/ 20 - 90%RH	
Working Temperature/ Humidity	0°C - 40°C/ 20 - 80%RH		
Mounting (Optional)	Wall-Mounted/ Floor Stand		
Outline Dimension	1569 × 1045 × 89mm	1792 × 1169 × 103mm	2039 × 1315 × 103mm
Packing Dimension	1725 × 275 × 1170mm	1918 × 275 × 1295mm	2155 × 310 × 1400mm
	US 45kg	US 58kg	US 71kg
Net Weight	EU 45kg	EU 58kg	EU 71kg
l I	·	US 72±2kg	US 93±2kg
Gross Weight	US 57.5±2kg		EU 93±2kg
Gross Weight	US 57.5±2kg EU 57.5±2kg	EU 72±2kg	EO 9012Ng
Gross Weight		EU 72±2kg Ports	EU 90±2Kg
Gross Weight Front Interface Inputs	EU 57.5±2kg		
-	EU 57.5±2kg H	Ports	×1
Front Interface Inputs	EU 57.5±2kg H	Ports DMI 1.4 × 1, USB(Touch) × 1, USB(Dynamic) × 2, MIC	×1
Front Interface Inputs AV Inputs	EU 57.5±2kg H	Ports DMI 1.4 × 1, USB(Touch) × 1, USB(Dynamic) × 2, MIC HDMI 2.0 × 2, HDMI 1.4 × 1, DP1.2 × 1, USB(Touch) × MI Out (Support 4K@60Hz) × 1, Line Out × 1, SPDIF C	×1 4 Jut ×1
Front Interface Inputs AV Inputs AV Outputs	EU 57.5±2kg H	Ports IDMI 1.4 × 1, USB(Touch) × 1, USB(Dynamic) × 2, MIC HDMI 2.0 × 2, HDMI 1.4 × 1, DP1.2 × 1, USB(Touch) × MI Out (Support 4K@60Hz) × 1, Line Out × 1, SPDIF C ed × 1, RS232 × 1, RJ45 × 2, USB3.0(Dynamic) × 1, OI	×1 4 Jut ×1
Front Interface Inputs AV Inputs AV Outputs	EU 57.5±2kg H	Ports DMI 1.4 × 1, USB(Touch) × 1, USB(Dynamic) × 2, MIC HDMI 2.0 × 2, HDMI 1.4 × 1, DP1.2 × 1, USB(Touch) × MI Out (Support 4K@60Hz) × 1, Line Out × 1, SPDIF C	×1 4 Jut ×1

newline

Newline Interactive Inc. 101 East Park Blvd. Suite 807 Plano, TX 75074, USA TEL: +1 888 233 0868

Want to buy: info@newline-interactive.com Become our partner: partner@newline-interactive.com Europe office Ronda de Poniente, N'2, 1ª planta, Oficina 1B, 28760, Tres Cantos, Madrid, Spain TEL: +34 911169178 Want to buy: info_eu@newline-interactive.com Become our partner:

partner_eu@newline-interactive.com

Asia Pacific Office
4F-3, No.76 Sec.2, Jiafeng S. Rd,
Zhubei City, Hsinchu Country,
30272, Taiwan
TEL: +886 35504768
Want to buy:
info_ap@newline-interactive.com
Become our partner:
partner_ap@newline-interactive.com

India office
Room No. 203, No. 37, TTK Road,
Alwarpet, Chennai,
Tamil Nadu, India, 600018
TEL: +91 4446945513
Want to buy:
info.in@newline-interactive.com
Become our partner:
partner.in@newline-interactive.com