PRODUCT **SPECIFICATIONS**

Model	TT-6518VN	TT-7518VN	TT-8618VN	
		Display		
Backlight		LED		
Display Area	1430 × 805 mm	1651 × 929 mm	1897 × 1066 mm	
Active Screen Size	65"	75"	86"	
Display Ratio		16:9		
Resolution		3840 × 2160 Pixels		
Display Color Depth	8-bit	8-bit	10-bit	
Brightness		370 nit		
Contrast Ratio	4000:1	4000:1	1200:1	
Response Time		8 ms		
Viewing Angle		178°		
Life Time	≥ 30,000 hours			
		Speaker		
Speaker Position		Front		
	80			
Rated Impedance				
Frequency Response		180 - 20K Hz		
Output SPL		82 ± 3 dB		
Max. Power Output		15 W × 2		
	Maximum ≤ 250 W	Power Maximum ≤ 400 W	Maximum ≤ 450 W	
Power Consumption	Standby Mode ≤ 0.5 W	Standby Mode ≤ 0.5 W	Standby Mode ≤ 0.5 W	
Working Voltage		AC 100-240 V, 50/60 Hz		
		Touch		
Touch Surface	Optical Bonding Anti-Glare & Anti-Fingerprint Glass			
Transparency		88%		
Surface Hardness	7Н			
Touch Technology	Infrared Touch			
HID Support	HID			
Touch Points	20 Points in Windows/ 10 Points in Android			
Writing Tools	Passive Pen/ Finger/ Palm			
Scan Speed	130 Hz	120 Hz	100 Hz	
Communication Interface	100112	USB-A	100 112	
communication interface		Environmental/ Physical Specifications		
Storage Temperature/ Humidity	-15°C - 55°C/ 20 - 90% RH			
		-15 C - 35 C / 20 - 90% RH		
Working Temperature/ Humidity				
Mounting (Optional)	1517 044 00	Wall Mount/ Floor Stand	0010 1011 104	
Outline Dimensions	1547 × 944 × 90 mm	1771 × 1071 × 108 mm	2018 × 1211 × 104 mm	
Packing Dimensions	1725 × 1085 × 280 mm	1918 × 1195 × 280 mm	2180 × 1330 × 340 mm	
Net Weight	US 39 kg EU 39 kg	US 50.5 kg E U 50.5 kg	US 62.5 kg EU 62.5 kg	
Gross Weight	US 52 ± 2 kg	US 68 ± 2 kg	US 81.5 ± 2 kg	
closs neight	EU 53 ± 2 kg	EU 68 ± 2 kg	EU 81.5 ± 2 kg	
Front late (1 to 1			2	
Front Interface Inputs		HDMI 1.4 × 1, USB(Touch) × 1, USB(Dynamic) × 2		
AV Inputs		HDMI 2.0 × 2, HDMI 1.4 × 1, DP 1.2 × 1, USB(Touch) × 4		
AV Outputs		HDMI Out (Support 4K@60Hz) × 1, Line Out(Earphone) × 1, SPDIF Out × 1		
Other	USB 2.0(Android) × 1, USB 2.0(Dynamic) × 1, RS232 × 1, RJ45 × 2, USB 3.0(Dynamic) × 1, OPS Slot(4K@60Hz) × 1, DC 5V-2A Out ×			
		Other Features		
Intelligent Thermo-Protector	Yes			
Built-In Wi-Fi		2.4G/ 5G		
Front	Interface Inputs	terface Inputs Rear Bottom Ports		
JTOUCH has various I/O				
s that provide connectivity	─ USB 2.0 ── USB Touch HDMI IN	Power HDMI Touch	RS232 LAN In L	

TR por to PC, camera, DVD players, and more.

newline

NEWLINE INTERACTIVE INC. 101 East Park Blvd. Suite 807 Plano, TX 75074, USA TEL: +1 888 233 0868

Want to buy: info@newline-interactive.com Become our partner: partner@newline-interactive.com EUROPE OFFICE Ronda de Poniente, N'2, 1st floor, Oficina 1B, 28760, Tres Cantos, Madrid, Spain TEL: +34 911169178

Touch HDMI Touch HDMI Touch

DP

Want to buy: info_eu@newline-interactive.com Become our partner: partner_eu@newline-interactive.com ASIA PACIFIC OFFICE 17F. No. 653. Bannan Rd Zhonghe Dist, New Taipei City

235, Taiwan

TEL: +886 2 8228 2089 Want to buy: info_ap@newline-interactive.com Become our partner:

partner_ap@newline-interactive.com

USB 3.0 USB 2.0

INDIA OFFICE Room No. 203, No. 37, TTK Road, Alwarpet, Chennai, Tamil Nadu, India, 600018 TEL: 1 800 419 0309

Line Out HDMI Out SPDIF

(-)

Want to buy: info.in@newline-interactive.com Become our partner: partner.in@newline-interactive.com

TRUTOUCH VN series



" CREATIVITY THROUGH SIMPLICITY "

Newline's new generation VN series features upgraded IR touch technology that is more responsive and offers the most intuitive and smoothest writing experience. The multi-function display is a perfect solution for higher education classrooms, seminar rooms, and corporate meeting rooms.







4K UHD

Annotation

1 to Many Presentation

newline











Content x Simplicity = CREATIVITY



Superior Touch Experience

With the state-of-the-art touch technology, users can annotate with a writing stylus or fingers which is as natural as writing on papers. VN series also supports object recognition under the built-in annotation tool.

Optical Bonding



What's simpler?

Less clutter. Lower installation & setup time. Less weight & slim frame design. Less system limitations. Personalized User Interface

Land Carlos Carl

What's better?

Brand new UI design. 4K UHD that redefines clarity. 20-Point Touch Support Size selections from 65", 75" to 86".

Maximized Viewing Angle

VN series adapt optical bonding technology that eliminates the gap between surface glass and display, and resulting in a 178° viewing angle. No matter where you sit in the meeting room, the image is just as clear.



UHD

Collaborate on Content Better, Together

TRUTOUCH VN series is designed for a intuitive user experience. It allows a seamless writing and co-working experience simultaneously. A powerful TRUTOUCH BYOD ready display enables the screen to be turned into a discussion board with a single touch. Productivity made easy!

Clear and Robust Images

Capture your audience's attention when showing videos, image and presentations. TRUTOUCH VN series' 4K UHD resolution delivers clear and robust images, even when multiple users simultaneously project their screens in quadrant view.

Tools that evoke INSPIRATION Welcome to the New Visual Era!

TRUTOUCH VN series debuts with revolutionary innovation leading the way to a brand new user experience like you never expected.