

THE UNMATCHED ALL-IN-ONE UNIFIED COLLABORATION SOLUTION





Built-in Cameras

以》

Noise Cancellation



Access to



Seamless Wireless Casting



Optical Bonding Technology



Object Recognition



OPS Computer Included



Compatible with

Collaborate with anyone, anywhere in the world, with the X Series Unified Collaboration system. With built-in cameras and microphone array, use the Unified Collaboration (UC) software of your choice on an all-in-one interactive display to enhance any meeting or huddle space.

The X Series brings all the tools you need, right at your fingertips. With two 1080p wide-angle cameras, a microphone array with echo reduction and noise cancellation, speakers, and a built-in OPS computer powered by Intel processors all seamlessly integrated into the interactive display, just walk in and get your meeting started. No hassle, just productivity.

As natural as writing on paper, the X Series provides a smooth and intuitive writing and viewing experience. Optical bonding gives you an ultra-wide 178° viewing angle. No matter where you sit in the room, the image is vivid and clear. Wirelessly cast to the display or access documents saved in Cloud storage, all with a seamless and easy to navigate user interface.

X Series allows you to meet, conference, and collaborate without limitations.

XSeries



Model	X5	Х6	Х8	Х9
Display				
creen Size	55"	65"	75"	86"
isplay Area	47.62 x 26.79 in	56.23 x 31.63 in	64.97 x 36.55 in	74.69 x 42.05 in
acklight	LED	LED	LED	LED
esolution	1920 x 1080 pixels	3840 x 2160 pixels	3840 x 2160 pixels	3840 x 2160 pixels
	16:9	16:9	16:9	16:9
isplay Ratio			370nit	
rightness	370nit	370nit	178°	370nit 178°
iewing Angle	178°	178°		
fetime Hours	50,000 hours	50,000 hours	50,000 hours	50,000 hours
eakers, Cameras, Microphones				
peaker Position	Forward	Forward	Forward	Forward
beaker Frequency Response	65Hz - 12.5KHz	6.5Hz - 12.5KHz	6.5Hz - 12.5KHz	6.5Hz - 12.5KHz
ax Power Output	(2) 15W	(2) 15W	(2) 15W	(2) 15W
icrophone Sensitivity	-38dBV±3dB	-38dBV±3dB	-38dBV±3dB	-38dBV±3dB
ic Frequency Response	65Hz - 12.5KHz	65Hz - 12.5KHz	65Hz - 12.5KHz	65Hz - 12.5KHz
ic Polar Patterns	Omni-directional	Omni-directional	Omni-directional	Omni-directional
ic Pickup Range	26.25 ft	26.25 ft	26.25 ft	26.25 ft
ic Quantity	4-element array	4-element array	4-element array	4-element array
amera Position	1 Top, 1 Bottom	1 Top, 1 Bottom	1 Top, 1 Bottom	1 Top, 1 Bottom
amera Sensor	2M Pixels	2M Pixels	2M Pixels	2M Pixels
amera Lens	86°	86°	86°	86°
deo Resolution	1920x1080@30fps (Max)	1920x1080@30fps (Max)	1920x1080@30fps (Max)	1920x1080@30fps (Max)
ame Rate	30fps/60fps	30fps/60fps	30fps/60fps	30fps/60fps
ower				
lax Power Consumption	≤180W (Standby ≤0.5W)	≤220W (Standby ≤0.5W)	≤300W (Standby ≤0.5W)	≤450W (Standby ≤0.5W)
Jorking Voltage	AC 100-240V, 50/60Hz	AC 100-240V, 50/60Hz	AC 100-240V, 50/60Hz	AC 100-240V, 50/60Hz
	· /	· '	, ,	//
ouch				
ouch Surface	Anti-glare tempered glass	Optically bonded anti-glare glass	Optically bonded anti-glare glass	Optically bonded anti-glare glass
ouch Technology	InGlass™	InGlass™	InGlass™	InGlass™
ouch Points	Up to 20 Points	Up to 20 Points	Up to 20 Points	Up to 20 Points
riting Tools	Stylus or Finger	Stylus or Finger	Stylus or Finger	Stylus or Finger
ommunication Interface	USB-A	USB-A	USB-A	USB-A
ansportation/Storage				
orage Temperature/Humidity	14°F - 122°F / 10% - 90% D51	14°F - 122°F / 10% - 90% D51	14°F - 122°F / 10% - 90% D51	14°F - 122°F / 10% - 90% D51
orking Temperature/Humidity	32°F - 104°F / 10% - 90%	32°F - 104°F / 10% - 90%	32°F - 104°F / 10% - 90%	32°F - 104°F / 10% - 90%
ounting Options	Wall-mount or Mobile Stand	Wall-mount or Mobile Stand	Wall-mount or Mobile Stand	Wall-mount or Mobile Stand
utline Dimension	52 x 34.9 x 3.4 in	61.7 x 41.1 x 3.5 in	70.6 x 46.1 x 4 in	80.3 x 51.8 x 4 in
eight	79.4 lbs	99.2 lbs	121.3 lbs	174.10 lbs
orts				
ont Interface Ports	HDI	MI 1.4 (4K@30Hz) x 1, USB(Touch) x 1	IISB(Dynamic) v 2 Microphone In (3	5mm) v 1
puts	HDI	MI (4K@60Hz) x 2, HDMI (4K@30Hz) x		Jouenny A 4
utputs	1100/2 0		ne Out (3.5mm) x 1, SPDIF Out x 1	5 EV 2A) Out v 1
ther	O2R(3:0) x	x 1, USB(2.0) x 2, RS232 x 1, RJ45 x 2,	UPS SIDES (4K@BUHZ) X 1, POWEF (DC	_ 3v-2A) Out X 1
ther Major Features				
nbedded Operating System	Android	Android	Android	Android
PS Included	Yes	Yes	Yes	Yes
ireless Screen Casting	Yes	Yes	Yes	Yes
bject Recognition	Yes	Yes	Yes	Yes
ewline Workspace	Free 1-year license included	Free 1-year license included	Free 1-year license included	Free 1-year license included



vd, Suite 807 Toll-Free: 888-233-0868 Docal: 972-468-9728