

# newline

Connect. Create. Collaborate.

## THE ENHANCED INTERACTIVE DISPLAY FOR COLLABORATION



Superior  
Image Quality



Seamless  
Wireless Casting



Access to  
the Cloud



Superior  
Touch



Impressive  
Embedded OS



Object  
Recognition



Collaboration  
Hub



Compatible with  
all Devices

Increase productivity and collaboration across the board with the RS+. Turn the display into a digital whiteboard, share, and use your favorite software all with a single touch. Take notes and annotations right on the screen, that you can save and share instantly after the meeting. Never forget an important to-do item again.

With a lightweight slim frame design, built-in OS support, embedded tools, and a customizable user interface, the RS+ Series is the perfect solution to redefine communication in the office.

Object recognition technology lets the RS Series recognize when you are using a stylus or your finger, and switches between annotation modes based on how you are interacting with the display. Wirelessly cast to the display or access documents saved in Cloud storage, all with a seamless and easy to navigate user interface.

Collaborate without limits on a screen that lets you work how you want and brings your team together.

# RS+ Series

# RS+ Series

Model	RS65	RS75	RS86
<b>Display</b>			
Screen Size	65"	75"	86"
Display Area	56.4 x 31.8 in	65 x 36.6 in	74.5 x 42.1 in
Backlight	LED	LED	LED
Resolution	3840 x 2160 pixels	3840 x 2160 pixels	3840 x 2160 pixels
Display Ratio	16:9	16:9	16:9
Brightness	370nit	370nit	370nit
Display Colors	8 bit	8 bit	10 bit
Contrast Ratio	4000:1	4000:1	4000:1
Response Time	8 ms	8 ms	8 ms
Viewing Angle	178°	178°	178°
Lifetime Hours	50,000 hours	50,000 hours	50,000 hours
<b>Speakers</b>			
Position	Forward	Forward	Forward
Max Power Output	(2) 15W	(2) 15W	(2) 15W
Transmission Range	16.4 ft	16.4 ft	16.4 ft
<b>Power</b>			
Max Power Consumption	≤250W (Standby ≤0.5W)	≤400W (Standby ≤0.5W)	≤450W (Standby ≤0.5W)
Working Voltage	AC 100-240V, 50/60Hz	AC 100-240V, 50/60Hz	AC 100-240V, 50/60Hz
<b>Touch</b>			
Touch Surface	Anti-glare tempered glass	Anti-glare tempered glass	Anti-glare tempered glass
Touch Points	Up to 20 Points	Up to 20 Points	Up to 20 Points
Surface Hardness	>7H	>7H	>7H
Touch Sensor	Infrared Touch	Infrared Touch	Infrared Touch
Writing Tools	Stylus or Finger	Stylus or Finger	Stylus or Finger
Communication Interface	USB-A	USB-A	USB-A
<b>Transportation/Storage</b>			
Storage Temp/Humidity	14°F - 122°F / 20% - 90%	14°F - 122°F / 20% - 90%	14°F - 122°F / 20% - 90%
Working Temp/Humidity	32°F - 104°F / 20% - 90%	32°F - 104°F / 20% - 90%	32°F - 104°F / 20% - 90%
Mounting Options	Wall-mount or Mobile Stand	Wall-mount or Mobile Stand	Wall-mount or Mobile Stand
Outline Dimension	60.9 x 37.2 x 3.8 in	69.7 x 42.2 x 4.3 in	79.5 x 47.7 x 4.3 in
Weight	97 lbs	123.5 lbs	158.7 lbs
<b>Embedded Operating System</b>			
CPU	ARMv8 A73 x 2 + A53 x 2 (A53 : 1.05-1.3GHz; A73 : 1.15-1.5GHz)	ARMv8 A73 x 2 + A53 x 2 (A53 : 1.05-1.3GHz; A73 : 1.15-1.5GHz)	ARMv8 A73 x 2 + A53 x 2 (A53 : 1.05-1.3GHz; A73 : 1.15-1.5GHz)
GPU	Mali-G51MP2 650 MHz	Mali-G51MP2 650 MHz	Mali-G51MP2 650 MHz
RAM	3GB	3GB	3GB
ROM	16GB	16GB	16GB
Android Version	8.0.0	8.0.0	8.0.0
External Memory	32GB TF card (Built in)	32GB TF card (Built in)	32GB TF card (Built in)
Multimedia Files Supported	Image (JPEG, BMP, PNG); Video (MPEG1, MPEG2, MPEG4, H.264, H.265, MOV, FLV); Audio (MP3, M4A, AAC)		
<b>Ports</b>			
Front Interface Inputs	HDMI 1.4 (4K@30Hz) x 1, USB (Touch) x 1, USB (Public) x 2, Microphone x 1		
Rear AV Inputs	HDMI 2.0 (4K@60Hz) x 2, DisplayPort x 1, USB (Touch) x 4, VGA x 1, PC Audio x 1		
AV Outputs	HDMI out (Supports up to 4K@60Hz) x 1, Line Out x 1, SPDIF out x 1		
Other	USB (3.0) x 1, USB (2.0) x 1, USB (Embedded) x 1, RS232 x 1, RJ45 x 2, OPS Slots (4K@60Hz) x 1, DC 5V-2A out x 1		