

newline

CERTIFIED

**OPTICAL
BONDING**



Enterprise Level
Security



Superior
Touch



Crystalclear
Image Quality



Maximum
Viewing Angle



Object
Recognition



Bonded
PCAP



Ultra
Lightweight



Easy
Installation

UNMATCHED POWERFUL PCAP WITH ENTERPRISE LEVEL SECURITY

NAOS IP is Newline's premium solution for the corporate workspace. Based on the combination of optical bonding technology and capacitive touch technology this product line features a superior touch experience, crystal clear images and a true maximum viewing angle. This product line comes in a wide variety of sizes and can be easily combined with the Newline 4K wide angle camera with microphone. This versatile premium solution is optimized for Windows and suits any workspace, from huddle room to large meeting room.

NAOS IP can ensure enterprise level security. This solution has no functional Android which makes it safer. You can still benefit from the Newline interactive ecosystem. Simply complete your NAOS IP with a Newline OPS including the Windows bundle of interactive ecosystem tools for a full Newline experience!

Newline NAOS IP is compatible with optional Newline OPS with Newline interactive ecosystem tools for Windows:

CAST

BROADCAST

LAUNCH CONTROL

NAOS IP

MODEL	TT-6519IP	TT-7519IP	TT-8619IP
Display			
Active Screen Size	65"	75"	86"
Backlight type	LED (WCG + Anti blue light Filter)		
Aspect ratio	16:9		
Resolution	3840 x 2160 (4K UHD)		
Display color	1,07 billion		
Brightness	≥400 cd/m ²		
Contrast Ratio (Dynamic)	4000:1		
Viewing angle	178°		
Life Time	≥50.000 hours		
Electrical			
Power Consumption (Normal)	≤250 W	≤300 W	≤400 W
Power Consumption (Standby mode)	<0,5 W		
Working Voltage	AC 100-240 V; 50/60 Hz; Max 3,0 A		
Touch			
Surface treatment	Optical Bonding / Anti-glare tempered glass + Anti-fingerprint		
Touch type	Projective Capacitive Touch (P-cap)		
Writing pen	Fine passive pen		
Touch points	Windows 20 points		
Speaker			
Speaker Position	Downward		
Speaker Rated Impedance	8 Ω		
Speaker Max.Power Output	2 x 15 W		
Transportation/Storage			
Outline Dimension	1509 x 886 x 86 mm	1731 x 1010 x 86 mm	1977 x 1150 x 86 mm
Package size	1640 x 1036 x 221 mm	1859 x 1136 x 247 mm	2119 x 1281 x 275 mm
Net weight	36 Kg	49 Kg	60 Kg
Gross weight	46,5 Kg	62 Kg	76 Kg
VESA Mount	600 x 400 mm	800 x 400 mm	800 x 400 mm
IO Ports			
Rear input ports	HDMI 2.0 (4K@60 Hz) x 2; VGA (2K@60 Hz) x 1; USB-B 2.0 (Touch) x 1; VGA audio in (Jack 3,5 mm) x 1; USB-A 2.0 x 1; YPbPr x 1; RS232 (Serial) x 1		
Rear output ports	Line Out (Earphone Jack 3,5 mm) x 1; AV out x 1		
OPS port	Yes, 4K@60 Hz		
Others			
OPS PC	Available		
Firmware update	OTA		

newline

HEAD OFFICE EMEA

Ronda de Poniente, 16,
Bajo E-28760, Tres Cantos,
Madrid, Spain
TEL: +34 911169178

BRANCH OFFICE POLAND

Aleje Jerozolimskie 200,
pokój 322, 02-486,
Warszawa, Poland
TEL: +48 533379973

BRANCH OFFICE GERMANY

Am Münster 36,
37154 Northeim
Germany
TEL: +49 55515889580

SHOWROOM/OFFICE ITALY

Via Giuseppe Giusti 10
20068 Peschiera Borromeo - MI
Italy
TEL: +39 3351295904