

newline *ip*



Linux-based OS



Capacitive
Touch



Security



24/7 Rated



Device
Compatibility



Superior
Image Quality



PTZ Camera

AN OUTSTANDING INTERACTIVE DISPLAY DESIGNED FOR ENTERPRISE SECURITY

The IP Series is a Linux-based interactive display for secure and intuitive collaboration. Immerse yourself in the outstanding interactivity of an optically bonded 4K display with P-cap touch technology and intelligent Object Recognition. With stronger network security, connect your team to the world without comprising sensitive information.

Newline IP Series features the following optional interactive ecosystem tools:

CAST

LAUNCHCONTROL

WORKSPACE

Model	TT-6519IP	TT7519IP	TT-8619IP
Display			
Backlight	LED		
Display Area	1428 × 804 mm	1650 × 928 mm	1895 × 1066 mm
Active Screen Size	65"	75"	86"
Display Ratio	16:9		
Resolution	3840 × 2160 Pixels		
Display Color Depth	8-bit + 2-bit FRC (1.07 billion)		10-bit (1.07 billion)
Brightness	≥ 370 nit		
Contrast Ratio	4000:1	4000:1	1200:1
Viewing Angle	178°		
Life Time	≥ 50,000 hours		
Speaker			
Speaker Position	Downward		
Max. Power Output	15 W × 2		
Electrical			
Power Consumption	Maximum ≤ 300 W Standby Mode ≤ 0.5 W	Maximum ≤ 400 W Standby Mode ≤ 0.5 W	Maximum ≤ 450 W Standby Mode ≤ 0.5 W
Working Voltage	AC 100-240 V, 50/60 Hz		
Touch			
Touch Surface	Optical Bonding Tempered Anti-Glare Glass		
Transparency	88% ± 3		
Surface Hardness	7H		
Touch Technology	P-Capacitive Touch		
Touch Points	20 Points		
Touch Resolution	32767 × 32767		
Transportation/ Storage			
Storage Temperature/ Humidity	-20°C - 60°C/ 20 - 93% RH		
Working Temperature/ Humidity	0°C - 45°C/ 20 - 93% RH		
Mounting (Optional)	Wall Mount/ Floor Stand		
Outline Dimensions	1509 × 865 × 86 mm	1731 × 1010 × 86 mm	1977 × 1150 × 86 mm
Packing Dimensions	1640 × 221 × 1036 mm	1859 × 247 × 1136 mm	2119 × 275 × 1281 mm
Net Weight	36 kg	49 kg	60 kg
Gross Weight	46.5 kg	62 kg	76 kg
Other			
Inputs	USB 2.0 × 1, USB(Touch) × 1, HDMI 2.0 × 2, VGA In × 1, RCA × 1, Audio In × 1, YPbPr × 1, MIC In × 1, RS232 × 1, OPS Slot × 1		
Outputs	Earphone Out × 1		
OPS Slot	4K@60Hz/30Hz		
Operating System	N/A		