

# newline i

## REVOLUTIONIZING THE EDUCATION SECTOR

The most cost efficiency I Series has been designed to transfer the traditional classroom setup to a digital classroom. 4K screen in many sizes brings digital content alive to engage student attention.



Superior Touch




No Calibration



Plug & Play



Software



No Glare



Affordable

# newline *i*

Model	TT-6519I	TT-7519I	TT-8519IS
<b>Display</b>			
Display Backlight	LED		
Display Area	1428 x 804 mm	1650 x 928 mm	1872 x 1053 mm
Active Screen Size ("inch)	65"	75"	85"
Display Ratio	16 : 9		
Resolution	3840 x 2160 Pixels		
Display Colors	8 bit + FRC (1.07 billion)		10 bit + FRC (1.07 billion)
LCD Brightness(After Glass)	≥ 370 nit		≥ 400 nit
Contrast Ratio (Dynamic)	4000:1		
Viewing Angle	178°		
Life time (working hours/day)	50,000 hours		
Response Time	8ms		
<b>Speaker</b>			
Speaker Position	Downward		
Transmission Range	5M		
Speaker Max.Power Output	15 W x 2		
<b>Power</b>			
Power Consumption	Maximum ≤ 250 W Standby Mode ≤ 0.5 W	Maximum ≤ 400 W Standby Mode ≤ 0.5 W	Maximum ≤ 450 W Standby Mode ≤ 0.5 W
Working Voltage	AC100-240V Max 3.0A	AC100-240V Max 4.0A	AC100-240V Max 4.5A
<b>Touch</b>			
Touch Surface Technology	Anti-Glare glass tempered glass		
Touch Surface Hardness	>7H		
Touch Sensor	Infrared Touch		
Touch Points	20 Points		
Touch Screen Writing Tools	Stylus, Finger		
Communication Interface	USB-A		
<b>Transportation/ Storage</b>			
Storage Temperature/ Humidity	-10°C ~ 45°C / 20 ~ 90% RH (non-condensing)		
Working Temperature/ Humidity	0°C ~ 40°C / 20 ~ 80% RH (non-condensing)		
Mounting Options	Wall-mount or Mobile Stand		
Outline Dimensions	1546 x 944 x 96 mm	1770 x 1071 x 101 mm	1982.6 x 1180.5 x 87.1 mm
Packing Dimensions	1670 x 1056 x 221 mm	1895 x 1193 x 247 mm	2170 x 1345 x 275 mm
Net Weight	44 kg	57 kg	69 kg
Gross Weight	58 ± 2 kg	73 ± 2 kg	86 ± 2 kg
Vesa Mount Installation Position	600 x 400 mm	800 x 400 mm	
<b>Ports</b>			
Front Interface Inputs	USB 3.0 for OPS x 2, HDMI In x 1, Touch USB(Type B) x 1, MIC In x 1		USB 3.0 for OPS x 1, HDMI In x 1, USB 2.0 for media player x 1, Touch USB(Type B) x 1, MIC In x 1
Rear AV Inputs	HDMI 2.0 in x 2, VGA IN x 1, VGA Audio in x 1, Touch USB(Type B) x 1, YPbPr in x 1, CVBS in x 1, AV (L&R) in x 1		
AV Outputs	AV out x 1, Ear Phone x 1		
Other	USB2.0 x 1, RS232 x 1, OPS Slot x 1(4K@60Hz)		
<b>Embedded Operating System</b>			
CPU	MIPS Advanced Multi-core CPU		
GPU	MStarACE6 Video Processor		
RAM	2Gbit DDR3 MCP		
ROM	64M bit norflash		
External Memory	None		
Android Version	None		
<b>Other</b>			
OPS PC	Optional		
Wi-Fi Dongle	NA		
Newline Software Content	Teach Infinity II (Free download from website. Support Windows, Mac, Linux)		

## newline

### HEADQUARTERS (TX, USA)

101 East Park Blvd.  
Suite 807 Plano,  
TX 75074, USA  
TEL: +1 888 233 0868  
info@newline-interactive.com

### ASIA PACIFIC OFFICE (Taipei, Taiwan)

17F, No. 653, Bannan Rd,  
Zhonghe Dist, New Taipei City  
235, Taiwan  
TEL: +886 2 8228 2089  
info\_ap@newline-interactive.com

### EUROPE OFFICE (Madrid, Spain)

Ronda de Poniente, N'2, 1st floor,  
Oficina 1B, 28760,  
Tres Cantos, Madrid, Spain  
TEL: +34 911 169178  
info\_eu@newline-interactive.com

### INDIA OFFICE (Chennai)

Room No. 203, No. 37, TTK Road,  
Alwarpet, Chennai,  
Tamil Nadu, India, 600018  
TEL: 1 800 419 0309  
info.in@newline-interactive.com

### KOREA OFFICE (Seoul, South Korea)

A816, 8F, 401 Yangcheon-ro,  
Gangseo-gu, Seoul,  
07528 Korea  
TEL: +82 2 2638 5140  
koreainfo@newline-interactive.com

newline-interactive.com