



newline VN



Superior
Touch



Optical
Bonding



Max. Viewing
Angle



Annotation



Go Wireless



Collaboration
Hub



Intuitive User
Interface



Win/Android/iOS
Compatibility

THE SUPERIOR INTERACTIVE DISPLAY FOR AN INTUITIVE TOUCH EXPERIENCE

VN series delivers the best visual experience ever and significantly reduces reflection and parallax due to the optical bonding technology used. It is highly responsive and provides lag-free multi-touch for the most intuitive and smoothest writing experience.

This multifunctional display is the perfect solution for conference rooms or higher education classrooms looking to communicate better and collaborate easier.

newline VN series features the following interactive ecosystem tools:

CAST

BROADCAST

DISPLAY MANAGEMENT

newline VN

Model	TT-6518VN	TT-7518VN	TT-8618VN
	Display		
Display Backlight	LED		
Display Area	1429.5 x 804.5 mm	1651 x 929 mm	1897 x 1066 mm
Active Screen Size (″inch)	65″	75″	86″
Display Ratio	16 : 9		
Resolution	3840 × 2160 Pixels		
Display Colors	8 bit + FRC (1.07 billion) colors		10-bit(D), 1.07 Billion colors
LCD Brightness(After Glass)	370 nit		
Contrast Ratio (Dynamic)	4000:1		
Viewing Angle	178°		
Life time (working hours/day)	≥ 50,000 hours		
Response Time	8ms		
	Speaker		
Speaker Position	Forward		
Transmission Range	5m		
Speaker Max.Power Output	15 W × 2		
	Power		
Power Consumption	Maximum ≤250 W Standby Mode ≤ 0.5 W	Maximum ≤ 400 W Standby Mode ≤ 0.5 W	Maximum ≤ 450 W Standby Mode ≤ 0.5 W
Working Voltage	AC100-240V ; 50/60 Hz		
	Touch		
Touch Surface Technology	Anti-Glare, tempered glass with Optical bonding		
Touch Surface Hardness	> 7H		
Touch Sensor	Infrared touch		
Touch Points	Up to 20 Points		
Touch Screen Writing Tools	Stylus, Finger		
Communication Interface	USB		
	Transportation/ Storage		
Storage Temperature/ Humidity	15°C ~ 55°C / 20 ~ 90% RH (Non coagulation)		
Working Temperature/ Humidity	0°C ~ 40°C / 20 ~ 80% RH (Non coagulation)		
Mounting Options	Wall-mount or Mobile Stand		
Outline Dimensions	1547 × 944 × 89 mm	1771 × 1071 × 108 mm	2018 × 1211 × 104 mm
Packing Dimensions	1670 × 1056 × 221 mm	1894 × 1193 × 247 mm	2170 × 1345 × 275 mm
Net Weight	39 kg	50.5 kg	62.5 kg
Gross Weight	53 ± 2 kg	68 ± 2 kg	81.5 ± 2 kg
VESA Mount installation position	600 x 400 mm	800 x 400 mm	
	Ports		
Front Interface Inputs	HDMI 1.4 (4K@30Hz) x 1, USB (Touch) x 1, USB 2.0 (Public) x 2		
AV Inputs	HDMI out (Support 4k@60Hz, 1920x1080@60Hz, 720x480@60Hz) x 1, Line Out x 1, SPDIF out x 1		
AV Outputs	HDMI out (Support 3840x2160@60Hz, 1920x1080@60Hz, 720x480@60Hz)*1, Line Out(earphone) *1, SPDIF out*1		
Other	USB 2.0 (Public) x 1, USB 3.0 (Public) x 1, USB 2.0 (Embedded) x 1, RS232 x 1, RJ45 x 2 (in/Out), OPS Slots (4K@60Hz) x 1, DC 5V-2A out x 1		
	Embedded Operating System		
CPU	ARM Cortex A53 4 x core 1.4GHz		
GPU	ARM Mali450 MP4 6-cores 600MHz		
RAM	2GB		
ROM	8GB		
Android Version	5.0.1		
	Other		
OPS PC	Optional		
WIFI dongle	YES, 802.11 a/b/g/n/ac (2.4G/5G Dual-band)		
Intelligent thermo protector	YES		
Built-in microphone	NA		
Newline Software Content	Newline Display management (SupportAndroid) Newline Cast (Support Windows and Android) & Broadcast (Support Android),		

newline

HEADQUARTERS (TX, USA)

101 East Park Blvd.
Suite 807 Plano,
TX 75074, USA
TEL: +1 888 233 0868
info@newline-interactive.com

ASIA PACIFIC OFFICE (Taipei, Taiwan)

17F, No. 653, Bannan Rd,
Zhonghe Dist, New Taipei City
235, Taiwan
TEL: +886 2 8228 2089
info_ap@newline-interactive.com

EUROPE OFFICE (Madrid, Spain)

Ronda de Poniente, N'2, 1st floor,
Oficina 1B, 28760,
Tres Cantos, Madrid, Spain
TEL: +34 911 169178
info_eu@newline-interactive.com

INDIA OFFICE (Chennai)

Room No. 203, No. 37, TTK Road,
Alwarpet, Chennai,
Tamil Nadu, India, 600018
TEL: 1 800 419 0309
info.in@newline-interactive.com

KOREA OFFICE (Seoul, South Korea)

A816, 8F, 401 Yangcheon-ro,
Gangseo-gu, Seoul,
07528 Korea
TEL: +82 2 2638 5140
koreainfo@newline-interactive.com

newline-interactive.com

2019 Newline Interactive Inc. Specification may vary by region, please contact our local offices for details. Actual product features and specifications are subject to change without notice. This material may include corporate names and trademarks of third parties which are the properties of the third parties respectively.