

newline VN



THE SMOOTHEST, MOST INTUITIVE TOUCH EXPERIENCE

Communication and collaboration made easy for all teams







65"



86"

FEATURES



Superior Touch



Annotation



Intuitive User Interface



Go Wireless





Optical Bonding



Max. Viewing Angle



Win/Android/iOS Compatibility



Collaboration



UNPARALLELED WRITING EXPERIENCE

Object Recognition and advanced IR touch technology give you the smoothest, most intuitive and responsive writing experience available. Write with a thin pen, erase with your palm, and set memory functions. Collaborate easily and comfortably without limitations.



Ultra-wide 178° viewing angle for clear, robust images no matter where you sit in the room.

Optical bonding brings an improved visual experience with accurate touch and a sturdier display. The benefits are endless.





TRULY ENGAGING COLLABORATION

A stunning, multi-functional display to make your meetings and presentations more engaging than ever. The VN Series enables BYOD so you can share and broadcast personal device screens wirelessly and hassle-free. Enhance productivity and maximize efficiency with the VN Series.



Present wirelessly from any network with a single click. Share video, links, and files from any device.



Broadcast content or present wirelessly from a personal device, and invite up to 200 participants to connect from their own.

DISPLAY MANAGEMENT

Centrally manage and deploy apps, configure settings, use digital signage and broadcast messages to all your Newline displays.

Built-In Apps

Everything you need to schedule meetings, manage e-mails, save and open files with the cloud and work on documents, all with Newline's built-in apps. Collaborate locally and remotely, easily.







Office Viewer

Business Calen

54.54



F-Mail

File Commander

APPLICATIONS

MEETING ROOM



HIGHER EDUCATION



HUDDLE SPACE



TRAINING



SPECIFICATIONS

Model	TT-6518VN	TT-7518VN	TT-8618VN		
		Display			
Display Backlight		LED			
Display Area	1429.5 x 804.5 mm	1651 x 929 mm	1897 x 1066 mm		
Active Screen Size ("inch)	65"	75"	86"		
Display Ratio		16:9			
Resolution		3840 × 2160 Pixels			
Display Colors	8 bit + FRC (1.07 billion) colors 10-bit(D), 1.07 Billion color				
LCD Brightness(After Glass)	370 nit				
	4000:1				
Contrast Ratio (Dynamic)	178°				
Viewing Angle					
Life time (working hours/day)		≧ 50,000 hours			
Response Time	8ms				
	Speaker				
Speaker Position	Front facing				
Transmission Range	5m				
Speaker Max.Power Output		15 W × 2			
		Power			
Power Consumption	Maximum ≦250 W	Maximum ≤ 400 W	Maximum ≤ 450 W		
·	Standby Mode ≤ 0.5 W	Standby Mode ≤ 0.5 W	Standby Mode ≤ 0.5 W		
Working Voltage		AC100-240V ; 50/60 Hz			
	Touch				
Touch Surface Technology	Anti-Glare, tempered glass with Optical bonding				
Touch Surface Hardness	>7H				
Touch Sensor	Infrared touch				
Touch Points	Up to 20 Points				
Touch Screen Writing Tools	Stylus, Finger				
Communication Interface		USB			
	Transportation/ Storage				
Storage Temperature/ Humidity	15°C ~ 55°C / 20 ~ 90% RH (Non coagulation)				
Working Temperature/ Humidity	0° C $\sim 40^{\circ}$ C $/$ 20 $\sim 80\%$ RH (Non coagulation)				
Mounting Options		Wall-mount or Mobile Stand			
Outline Dimensions	1547 × 944 × 89 mm	1771 × 1071 × 108 mm	2018 × 1211 × 104 mm		
Packing Dimensions	1670 × 1056 × 221 mm	1894 × 1193 × 247 mm	2170 × 1345 × 275 mm		
Net Weight	39 kg	50.5 kg	62.5 kg		
Gross Weight	53 ± 2 kg	68 ± 2 kg	81.5 ± 2 kg		
VESA Mount installation position	600 x 400 mm	-	400 mm		
	Ports				
Front Interface Inputs	HDMI 1.4 (4K@30Hz) x 1, USB (Touch) x 1, USB 2.0 (Public) x 2				
Front Interface Inputs AV Inputs	HDMI out (Support 4k@60Hz, 1920x1080@60Hz, 720x480@60Hz) x 1, Line Out x 1, SPDIF out x 1				
AV Inputs AV Outputs	HDMI out (Support 3840x2160@60Hz, 1920x1080@60Hz, 720x480@60Hz) x1, Line Out x1, SPDIF out x1 HDMI out (Support 3840x2160@60Hz, 1920x1080@60Hz, 720x480@60Hz) x1, Line Out(earphone) x1, SPDIF out x1				
Αν Ομίραιδ	, ,,	USB 2.0 (Public) x 1, USB 3.0 (Public) x 1, USB 2.0 (Embedded) x 1, RS232 x 1,			
Other		x 1, USB 3.0 (Public) x 1, USB 2.0 (Embedde (in/Out), OPS Slots (4K@60Hz) x 1, DC 5V-2			
	Embedded Operating System				
CPU	ARM Cortex A53 4 x core 1.4GHz				
GPU	ARM Mali450 MP4 6-cores 600MHz				
RAM	2GB				
ROM	8GB				
Android Version	50.1				
Aliurolu version					
		Other			
00000	Optional				
OPS PC		(EQ 000 11 - (b /- /- /- /0 10 /EQ D			
WIFI dongle	Υ	'ES, 802.11 a/b/g/n/ac (2.4G/5G Dual-band)		
WIFI dongle Intelligent thermo protector	Y	YES)		
WIFI dongle	Υ)		
WIFI dongle Intelligent thermo protector	Ne	YES	id)		

newline

HEADQUARTERS (TX, USA)

101 East Park Blvd.

Suite 807 Plano,

TX 75074, USA

TEL: +1 888 233 0868

info@newline-interactive.com

ASIA PACIFIC OFFICE (Taipei, Taiwan)
17F, No. 653, Bannan Rd,
Zhonghe Dist, New Taipei City
235, Taiwan
TEL: +886 2 8228 2089
info_ap@newline-interactive.com

EUROPE OFFICE (Madrid, Spain)
Ronda de Poniente, N'2, 1st floor,
Oficina 1B, 28760,
Tres Cantos, Madrid, Spain
TEL: +34 911169178
info eu@newline-interactive.com

INDIA OFFICE (Chennai)
Room No. 203, No. 37, TTK Road,
Alwarpet, Chennai,
Tamil Nadu, India, 600018
TEL: 1 800 419 0309
info.in@newline-interactive.com

KOREA OFFICE (Seoul, South Korea) A816, 8F, 401 Yangcheon-ro, Gangseo-gu, Seoul,

Gangseo-gu, Seoul, 07528 Korea TEL: +82 2 2638 5140 koreainfo@newline-interactive.com

newline-interactive.com