newline





Superior Image Quality



Seamless Wireless Casting



Access to the Cloud



Non-Touch Display



Impressive Embedded OS



Remote Management



Control by Remote



Compatible with all Devices

STREAMLINE YOUR SUCCESS

The NT Series is a non-touch display that brings your lessons to life in vivid Ultra-High Definition (4K) resolution. Focus on just the tools you need to get your students engaged in class without paying more for features you won't use.

Wirelessly cast to the screen from any mobile device, tablet, desktop, or laptop. Whether you use Windows, Mac, or Chrome, the NT Series lets you share your screen through a wireless connection or through the multiple I/O ports built into the panel. Access your files on your preferred Cloud storage system right on the display. The built-in file viewer lets you easily navigate through local files, Cloud storage, and files from connected USB thumb drives.

Rediscover the simplicity of real innovation with the new NT Series.

Newline NT Series includes the following software solutions



BROADCAST

DISPLAY MANAGEMENT PLUS

NT Series

AAAA		111 9 9 1 1 9 9	
Model	NT85	NT98	
Display			
Screen Size	85"	98"	
Display Area	73.7 x 41.5 in	85 x 47.8 in	
Backlight	LED	LED	
Resolution	3840 x 2160 pixels	3840 x 2160 pixels	
Display Ratio	16:9	16:9	
Brightness	≥400 cd/m²	≥400 cd/m²	
Display Colors	8 bit	10 bit	
Dynamic Contrast	4000:1	4000:1	
Static Contrast	3200:1	900:1	
Haze	2%~5%	25%~28%	
Viewing Angle	178°	178°	
Lifetime Hours	50,000 hours	50,000 hours	
Continuous Run Time	24/7	24/7	
Speakers			
Position	Downward	Downward	
Rated Impedence	6Ω	6Ω	
Frequency Response	90 Hz (±20%) - 18 kHz	90 Hz (±20%) - 18 kHz	
Output S.P.L.	84 ± 3 db	84 ± 3 db	
Max Power Output	(2) 20W	(2) 20W	
Microphone	(2) 2011	(2) 2011	
Internal Microphone	Yes	Yes	
Echo Cancellation	Yes	Yes	
Beamforming	Yes	Yes	
Noise Reduction	Yes	Yes	
Reverb Removal	Yes	Yes	
Power			
Max Power Consumption	≤450W (Standby ≤0.5W)	≤700W (Standby ≤0.5W)	
Working Voltage	AC100-240V Max 4.5A	AC100-240V Max 7.0A	
Transportation/Storage	710100 Z 10V Max 1.07	7.0 100 2 10V Max 7.0 N	
Storage Temp/Humidity	14°F~113°F / 20% - 90%	14°F~113°F / 20% - 90%	
Working Temp/Humidity	32°F - 104°F / 20% - 80%	32°F - 104°F / 20% - 80%	
Mounting Options	Wall-mount or Mobile Stand	Wall-mount or Mobile Stand	
VESA Mount	800x400 mm	800x600 mm	
Weight	143 lbs	258 lbs	
Embedded Operating System	143 IUS	230 IUS	
	A70+0, A50+0	A7040.AF040	
CPU	A73*2+A53*2	A73*2+A53*2	
GPU	G51*4	G51*4	
RAM	3 GB DDR4	3 GB DDR4	
ROM	16GB	16GB	
Android Version	8.0.0	8.0.0	
External Memory	None	None	
Multimedia Files Supported	Image: JPEG, BMP, PNG; Video: MPE	Image: JPEG, BMP, PNG; Video: MPEG2, MPEG4, H264, HEVC (H.265); Audio: WMA, MP3, M4A, (AAC)	
Ports			
Input Ports		(4) HDMI 2.0; (4) USB 3.0; (1) USB (For touch passthrough); (1) LAN in; (1) RS232	
Output Ports	(1) LAN out; (1) SPDIF out; (1) Head	(1) LAN out; (1) SPDIF out; (1) Headphones out	
OPS Slot	YES 4K@60HZ	YES 4K@60HZ	

