



newline *nt*



Remote Control



16/7 Operation



OPS Slot



Go Wireless



Win/iOS/Android



Embedded Microphone



Superior Image Quality



Direct Cloud Access

Commercial Displays

LARGE-SCALE COLLABORATION FOR EFFECTIVE AND STREAMLINED MEETINGS

The NT series is an innovative line of non-touch displays designed for large-scale collaboration. Created with your team's needs in mind, the NT series brings you all the collaborative tools a TV screen lacks. Streamline your meeting and presentations by focusing on just the tools you need to succeed.

NT series is a commercial display designed for 16/7 operation.

Newline NT series features the following interactive ecosystem tools :

CAST

BROADCAST

newline *nt*

Model	TT-8519NT	TT-9819NT
	Display	
Display Backlight	LED	
Display Area	1872 x 1053 mm	2159 x 1214 mm
Active Screen Size ("inch)	85"	98"
Display Ratio	16 : 9	
Resolution	3840 x 2160 Pixels	
Display Colors	8 bit + FRC (1.07 billion)	10bit(D), 1.07Billion colors
LCD Brightness(After Glass)	≥ 400 nit	
Contrast Ratio (Dynamic)	4000:1	
Viewing Angle	178°	
Life time (working hours/day)	50,000 hours	
Response Time	8ms	
	Speaker	
Speaker Position	Downward	
Transmission Range	≤ 10m	
Speaker Max.Power Output	20 W x 2	
	Power	
Power Consumption	Maximum ≤ 450 W Standby Mode ≤ 0.5 W	Maximum ≤ 700 W Standby Mode ≤ 0.5 W
Working Voltage	AC 100-240 V, 50/60 Hz	
	Touch	
Touch Surface Technology	N/A	
Touch Surface Hardness	N/A	
Touch Sensor	N/A	
Touch Points	N/A	
Touch Screen Writing Tools	N/A	
Communication Interface	N/A	
	Transportation/ Storage	
Storage Temperature/ Humidity	0°C ~ 50°C / 10 ~ 90% RH (No condensation)	
Working Temperature/ Humidity	20°C ~ +70°C / 5 ~ 95% RH (No condensation)	
Mounting Options	Wall mount (standard), Moving Stand (Option)	
Outline Dimensions	1967 x 1152 x 87 mm	2212 x 1292 x 93 mm
Packing Dimensions	2101 x 275 x 1272 mm	2380 x 372 x 1443 mm
Net Weight	46.5 kg	80 kg
Gross Weight	64.5 ± 2 kg	113 ± 2 kg
Vesa Mount Installation Position	800 x 400 mm	800 x 600 mm
	Ports	
Front Interface Inputs	N/A	
Rear AV Inputs	HDMI x 4, USB 3.0 Type B (for touch, passthrough) x 1, LAN IN x 1	
AV Outputs	LAN OUT x 1, SPDIF OUT x 1, Earphone x 1	
Other	USB 3.0 x 4, RS232 x 1, OPS Slot (4K@60Hz) x 1	
	Embedded Operating System	
CPU	Quad-core V810 (A73*2 + A53*2)	
GPU	G51 x 4	
RAM	DDR4 3GB	
ROM	16GB	
External Memory	N/A	
Android Version	8.0	
	Other	
OPS PC	Optional	
Wi-Fi Dongle	Plugable WiFi & BT module 7668U	
Built-in microphone	6-element array, 8 meters pick up	
Microphone Features	Echo cancellation, Beamforming, Noise reduction, Reverb removal	
Bluetooth Capable	YES	
Newline Software Content	Newline Cast & Broadcast (Support Windows and Android)	

newline

HEADQUARTERS (TX, USA)

101 East Park Blvd.
Suite 807 Plano,
TX 75074, USA
TEL: +1 888 233 0868
info@newline-interactive.com

ASIA PACIFIC OFFICE (Taipei, Taiwan)

17F, No. 653, Bannan Rd,
Zhonghe Dist, New Taipei City
235, Taiwan
TEL: +886 2 8228 2089
info_ap@newline-interactive.com

EUROPE OFFICE (Madrid, Spain)

Ronda de Poniente, N'2, 1st floor,
Oficina 1B, 28760,
Tres Cantos, Madrid, Spain
TEL: +34 911169178
info_eu@newline-interactive.com

INDIA OFFICE (Chennai)

Room No. 203, No. 37, TTK Road,
Alwarpet, Chennai,
Tamil Nadu, India, 600018
TEL: 1 800 419 0309
info.in@newline-interactive.com

KOREA OFFICE (Seoul, South Korea)

A816, 8F, 401 Yangcheon-ro,
Gangseo-gu, Seoul,
07528 Korea
TEL: +82 2 2638 5140
koreainfo@newline-interactive.com

newline-interactive.com

2019 Newline Interactive Inc. Specification may vary by region, please contact our local offices for details. Actual product features and specifications are subject to change without notice. This material may include corporate names and trademarks of third parties which are the properties of the third parties respectively.