

newline



Superior
Image Quality



Seamless
Wireless Casting



Access to
the Cloud



Non-Touch
Display



Impressive
Embedded OS



Remote
Management



Control by
Remote



Compatible
with all Devices

STREAMLINE YOUR SUCCESS

The NT Series is a non-touch display that brings your lectures to life in vivid Ultra-High Definition (4K) resolution. Focus on just the tools you need to get your students engaged in class without paying more for features you won't use.

Wirelessly cast to the screen from any mobile device, tablet, desktop, or laptop. Whether you use Windows, Mac, or Chrome, the NT Series lets you share your screen through a wireless connection or through the multiple I/O ports built into the panel. Access your files on your preferred Cloud storage system right on the display. The built-in file viewer lets you easily navigate through local files, Cloud storage, and files from connected USB thumb drives.

Rediscover the simplicity of real innovation with the new NT Series.

Newline NT Series includes the following software solutions

CAST

BROADCAST

NT Series

| Model | NT65 | NT85 | NT98 |
|----------------------------------|---|----------------------------|----------------------------|
| Display | | | |
| Screen Size | 65" | 85" | 98" |
| Display Area | 56.2 x 31.6 in | 73.7 x 41.5 in | 85 x 47.8 in |
| Backlight | LED | LED | LED |
| Resolution | 3840 x 2160 pixels | 3840 x 2160 pixels | 3840 x 2160 pixels |
| Display Ratio | 16:9 | 16:9 | 16:9 |
| Brightness | ≥400 cd/m ² | ≥400 cd/m ² | ≥400 cd/m ² |
| Display Colors | 8 bit | 8 bit | 10 bit |
| Dynamic Contrast | 4000:1 | 4000:1 | 4000:1 |
| Haze | 2%~5% | 2%~5% | 25%~28% |
| Viewing Angle | 178° | 178° | 178° |
| Lifetime Hours | 50,000 hours | 50,000 hours | 50,000 hours |
| Continuous Run Time | 24/7 | 24/7 | 24/7 |
| Speakers | | | |
| Position | Downward | Downward | Downward |
| Rated Impedence | 6Ω | 6Ω | 6Ω |
| Frequency Response | Fb-20KHz/-10dB | Fb-20KHz/-10dB | Fb-20KHz/-10dB |
| Output S.P.L. | 0dB~ -10dB | 0dB~ -10dB | 0dB~ -10dB |
| Max Power Output | (2) 20W | (2) 20W | (2) 20W |
| Microphone | | | |
| Internal Microphone | 6-mic array | 6-mic array | 6-mic array |
| Pickup Range | 19.7 - 26.2 ft | 19.7 - 26.2 ft | 19.7 - 26.2 ft |
| Echo Cancellation | Yes | Yes | Yes |
| Noise Reduction | Yes | Yes | Yes |
| Reverb Removal | Yes | Yes | Yes |
| Power | | | |
| Max Power Consumption | ≤200W (Standby ≤0.5W) | ≤450W (Standby ≤0.5W) | ≤700W (Standby ≤0.5W) |
| Working Voltage | AC100-240V Max 4.5A | AC100-240V Max 4.5A | AC100-240V Max 7.0A |
| Transportation/Storage | | | |
| Storage Temp/Humidity | 14°F~113°F / 20% - 90% | 14°F~113°F / 20% - 90% | 14°F~113°F / 20% - 90% |
| Working Temp/Humidity | 32°F - 104°F / 20% - 80% | 32°F - 104°F / 20% - 80% | 32°F - 104°F / 20% - 80% |
| Mounting Options | Wall-mount or Mobile Stand | Wall-mount or Mobile Stand | Wall-mount or Mobile Stand |
| VESA Mount | 600x400mm | 800x400 mm | 800x600 mm |
| Outline Dimensions | 59 x 34.9 x 3.3 in | 77.4 x 43.4 x 3.4 in | 87.1 x 50.9 x 3.7 in |
| Net Weight | 62 lbs | 113 lbs | 190 lbs |
| Embedded Operating System | | | |
| CPU | A73*2+A53*2 | A73*2+A53*2 | A73*2+A53*2 |
| GPU | G51*4 | G51*4 | G51*4 |
| RAM | 3 GB DDR4 | 3 GB DDR4 | 3 GB DDR4 |
| ROM | 16GB | 16GB | 16GB |
| Android Version | 8.0.0 | 8.0.0 | 8.0.0 |
| Multimedia Files Supported | Image: JPEG, BMP, PNG; Video: MPEG2, MPEG4, H264, HEVC (H.265); Audio: WMA, MP3, M4A, (AAC) | | |
| Ports | | | |
| Input Ports | (4) HDMI 2.0; (4)USB 3.0; (1) USB (For touch passthrough) ; (1) LAN in; (1) RS232 | | |
| Output Ports | (1) LAN out; (1) SPDIF out; (1) Headphones out | | |
| OPS Slot | YES 4K@60HZ | | |