



Built-in Cameras



Microphone Аггау



Superior Touch





Go Wireless



Collaboration





Win/Android/iOS Compatibility

THE UNMATCHED ALL-IN-ONE UNIFIED **COLLABORATION SOLUTION**

The X series features an all-in-one solution for collaboration that is immersive, unified and effective. X series is designed to make your meetings more efficient. The two built-in 1080p wide-angle cameras let you be seen from anywhere in the room. The microphone array reduces noise and cancels echo. Your voice can be heard clearly. Advanced InGlass touch enables responsive touch for a smooth and intuitive writing experience as natural as writing on paper. Optical bonding gives you an ultra-wide 178° viewing angle. No matter where you sit in the room, the image is robust and clear.

X series allows you to meet, conference and collaborate without limitations. Share voice, video, data and annotations. Work on documents simultaneously with people on a conference call as if you were in the same room. With the instant digital discussion board and on-screen annotation tool, you'll never let another idea slip aways.

newline X series features the following interactive ecosystem tools:

CAST

BROADCAST

DISPLAY MANAGEMENT LAUNCH CONTROL



| N | /lodel | X6 | X8 | Х9 | | | | | |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------|--------------------------|--------------|-------------------|-------------------------|-------|--|
| | | | Display | | | | | | |
| Displa | ay Backlight | | LED | | | | | | |
| | play Area | 1431.30 x 806.30 mm | 1662.24 x 941.96 mm | 1897.10 x 1067.70 mm | | | | | |
| | reen Size ("inch) | 65" | 75" | 86" | | | | | |
| | | 00 | 16:9 | 00 | | | | | |
| | play Ratio | | | | | | | | |
| Resolution Display Colors | | 3840 × 2160 Pixels 8 bit + FRC (1.07 billion) colors 10-bit(D), 1.07 Billion colors | | | | | | | |
| | | | | | LCD Brightr | ness(After Glass) | 370 nit | | |
| Contrast F | Ratio (Dynamic) | 4000:1 | | | | | | | |
| View | ving Angle | | 178° | | | | | | |
| | orking hours/day) | ≥ 50,000 hours | | | | | | | |
| | onse Time | | 8ms | | | | | | |
| ПСОР | onse mine | | | | | | | | |
| | | | Speaker | | | | | | |
| Speak | ker Position | | Front facing | | | | | | |
| | nission Range | 5m | | | | | | | |
| Speaker Max.Power Output | | 15 W × 2 | | | | | | | |
| Speaker Wil | ax.i owei output | | | | | | | | |
| | | | Camera | | | | | | |
| Р | Position | Top x | 1 & Bottom x 1 (Only one can use in the sam | ne time) | | | | | |
| Ş | Sensor | 2M Pixels | | | | | | | |
| | Lens | | 86° | | | | | | |
| | Resolution | | 1920 x 1080 @ 30fps (Max) | | | | | | |
| | | 30fps @ 1080P | | | | | | | |
| Fra | ame Rate | | | | | | | | |
| | | | Power | | | | | | |
| | | Maximum ≦250 W | Maximum ≤ 400 W | Maximum ≤ 450 W | | | | | |
| Power (| Consumption | Standby Mode ≤ 0.5 W | Standby Mode ≤ 0.5 W | Standby Mode ≤ 0.5 W | | | | | |
| \A/ | : | Startaby Wode = 0.5 W | | Standby Wode = 0.5 W | | | | | |
| Worki | ing Voltage | AC100-240V ; 50/60 Hz | | | | | | | |
| | | Touch | | | | | | | |
| Touch Surf | face Technology | | Anti-Glare, tempered glass | | | | | | |
| | rface Hardness | >7H | | | | | | | |
| | | | | | | | | | |
| Touch Sensor Touch Points Touch Screen Writing Tools | | InGlass Up to 20 Points Pencil or Finger or Eraser | | | | | | | |
| | | | | | Communic | ication Interface | | USB-A | |
| | | | | | Storage Tomp | | Transportation/ Storage | | |
| and the second of the second o | -15°C ~ 55°C / 20 ~ 90% RH (Non coagulation) | | | | | | | | |
| | perature/ Humidity | 0° C ~ 40° C / 20 ~ 80% RH (Non coagulation) | | | | | | | |
| | perature/ Humidity | | | | | | | | |
| Mount | ting Options | | Wall-mount or Mobile Stand | | | | | | |
| Outline | Dimensions | 1569 × 1045 × 89 mm | 1792 × 1169 × 103 mm | 2039 × 1315.1 × 102.8 mm | | | | | |
| Packing | g Dimensions | 1720 × 1170 × 275 mm | 1918 × 1295 × 275 mm | 2170 × 1440 × 310 mm | | | | | |
| | et Weight | 45 kg | 58 kg | 71 kg | | | | | |
| | ss Weight | 57.5 ± 2 kg | 72 ± 2 kg | 93 ± 2 kg | | | | | |
| | installation position | 600 x 400 mm | - | 400 mm | | | | | |
| V LOA IVIOUTILI | matanation position | 000 X 400 IIIII | | TOO HILL | | | | | |
| AV Ir | | Ports | | | | | | | |
| | terface Inputs | HDMI 1.4 (4k@30 Hz) x 1; USB-A 2.0 (Touch) x 1; USB-A 2.0 (Public) x 2; MIC In (Jack 3,5 mm) x 1 | | | | | | | |
| | V Inputs | HDMI 2.0 (4k@60 Hz) x 2; HDMI 1.4 (4k@30 Hz) x 1; DP 1.2 (4k@60 Hz) x 1; USB-A 2.0 (Touch) x 4 HDMI out (Support 4k@60Hz, 1920x1080@60Hz, 720x480@60Hz) x 1; Line Out (Earphone Jack 3,5 mm) x 1; SPDIF Out x 1 USB-A 2.0 (Public) x 1; USB-A 2.0 (Embedded) x 1; USB-A 3.0 (Public) x 1; LAN Out (RJ45) x 1; | | | | | | | |
| | Outputs | | | | | | | | |
| AV | pa.to | | | | | | | | |
| | Other | | | | | | | | |
| | | Lan In (RJ45) x 1; RS232 (Serial) x 1; DC 5 V-2 A out; OPS Slots(4K@60/30Hz) x1 | | | | | | | |
| | | Embedded Operating System | | | | | | | |
| | CPU | ARM Cortex A53 4 x core 1.4GHz | | | | | | | |
| | GPU | ARM Mali450 MP4 6-cores 600MHz | | | | | | | |
| | | | | | | | | | |
| | RAM | 2GB | | | | | | | |
| | ROM | 8GB | | | | | | | |
| Andro | oid Version | 5.0.1 | | | | | | | |
| | | Other | | | | | | | |
| | DDC DC | | | | | | | | |
| | OPS PC | Optional | | | | | | | |
| Build in WIFI 802.11 a/b/g/n/ac embedded (2.4G/5G Dual-band) | | | | and) | | | | | |
| Intelligent tl | hermo protector | YES | | | | | | | |
| Built-in | microphone | 4-element array, Omnidirectional; Pickup distance 8 m; Echo cancellation; Beamforming; Noise reduction | | | | | | | |
| | | Newline Display Management (Support Android) | | | | | | | |
| Newline So | oftware Content | Newline Display Management (Support Android) Newline Cast (Support Windows and Android) & Broadcast (Support Android), Launcher Control (License key, Support Windows) | | | | | | | |
| | | L | aunoner Control (License key, Support Windo | wsj | | | | | |
| | | | | | | | | | |

newline

HEADQUARTERS (TX, USA) 101 East Park Blvd. Suite 807 Plano,

TX 75074, USA
TEL: +1 888 233 0868
info@newline-interactive.com

APAC OFFICE (Hsinchu, Taiwan) 4F-3, No. 76, Sec. 2, Jiafeng S. Rd., Zhubei City, Hsinchu County,

302, Taiwan TEL: +886 3 550 4768 info_ap@newline-interactive.com **EUROPE OFFICE (Madrid, Spain)** Ronda de Poniente, N'2, 1st floor,

Ronda de Poniente, N'2, 1st floor, Oficina 1B, 28760, Tres Cantos, Madrid, Spain TEL: +34 911169178 info_eu@newline-interactive.com INDIA OFFICE (Chennai)

Room No. 203, No. 37, TTK Road, Alwarpet, Chennai, Tamil Nadu, India, 600018 TEL: 1 800 419 0309 info.in@newline-interactive.com KOREA OFFICE (Seoul, South Korea)

A816, 8F, 401 Yangcheon-ro, Gangseo-gu, Seoul, 07528 Korea TEL: +82 2 2638 5140 koreainfo@newline-interactive.com

newline-interactive.com