

newline

HUDDLE CAM



4K Resolution



120° Field of View



Built-in
Microphone



Echo
Cancellation

PLUG-AND-PLAY SOLUTION FOR HUDDLE SPACES

The Newline Huddle Cam is a plug-and-play video conferencing solution designed for huddle rooms and small meeting rooms. It works with all leading video and audio conferencing applications and is specifically certified by Zoom. With 4K UHD camera supporting face tracking, and an expansive 120° field of view, Newline Huddle Cam allows you to present and communicate comfortably anywhere in the meeting room without having to huddle around the microphone and camera. The echo-and-noise-cancelling microphone array further ensures a smooth flow of meeting with high quality audio performance. Newline Huddle Cam upgrades your huddle spaces, enhancing your remote collaboration quickly and easily anytime, anywhere.

HUDDLE CAM

Model	TC-4V19Z
Camera	
Sensor	1/2,5" CMOS, 8,51M pixel
Resolution	4K (4K@30 fps, 1080p@60 fps/30 fps, 720p@60 fps/30 fps)
Field of View	120°
Effective Focus Length	f = 2,8 mm
Aperture	f 1 : 1,8
Minimal Illumination	0,5 Lux
Shutter Speed	1/30 s~1/10000 s
White Balance (WB)	Yes
Scanning Mode	Progressive
Backlight Compensation	Yes
Brightness setting	Yes
Contrast Ratio Adjustment	Yes
Color Saturation setting	Yes
Edge Enhancement	Yes
Flicker	Yes 50 Hz/60 Hz/ Off
Mirror image	Yes
Digital Noise Reduction	2D, 3D
Microphone	
Microphone Type	4 MEMS Microphone Array
Pick-up Distance	3,5 m
Frequency	16 Hz~20 KHz
Polar Patterns	Omni-directional
Noise Cancellation	Yes
Echo Cancellation	Yes
Automatic Gain Control	Yes
USB Specification	
Hardware Requirement	2,4 GHz Intel® Core 2 Duo processor or higher 2 GB RAM or more USB-A 2.0 (USB-A 3.0 required for 4K)
Color System / Compression	H.264 / MJPEG / YUY2
UVC Protocol	UVC 1.1
Input/Output Interface	
USB Interface	USB-B 3.0 x 1
SPDIF In	1
General	
Input Voltage	5 V (USB Power)
Current Consumption	0,9~1,4 A (Max)
Power Consumption	4,5~7 W
Working Temperature	-10°C~40°C
Storage Temperature	-40°C~60°C
Dimensions	240,5 x 56 x 52,3 mm
Net Weight	0,56 Kg
Current Consumption	0,9 - 1,4 A (Max.)

newline

HEAD OFFICE EMEA

Ronda de Poniente, 16,
Bajo E, 28760, Tres Cantos,
Madrid, Spain
TEL: +34 91 052 8834

BRANCH OFFICE POLAND

Aleje Jerozolimskie 200,
pokój 322, 02-486,
Warszawa, Poland
TEL: +48 533379973

BRANCH OFFICE GERMANY

Am Münster 36,
37154 Northeim
Germany
TEL: +49 55515889580

SHOWROOM/OFFICE ITALY

Via Giuseppe Giusti 10,
20068 Peschiera Borromeo - MI
Italy
TEL: +39 3351295904

newline-interactive.com/eu/ / info_eu@newline-interactive.com

Contact Support: support_eu@newline-interactive.com / Technical Support Hotline: +34 91 804 31 79

2021 Newline Interactive Inc. Specification may vary by region, please contact our local offices for details. Actual product features and specifications are subject to change without notice. This material may include corporate names and trademarks of third parties which are the properties of the third parties respectively.