

THE SMART **ALL-ROUND** MEETING ROOM SOLUTION

MIRA has it all! Being Newline's most versatile display, this solution will fulfill nearly every need in the corporate workspace. Suitable for meeting rooms, huddle spaces, lecture halls and offices MIRA is the proven successful solution. The combination of optical bonding and advanced IR touch results in exceptional touch accuracy and a smooth writing experience with recognition of pen, finger and palm. But there is more! Other optical bonding benefits are clear images, vibrant colors and a true 178° viewing angle.

The built-in camera and microphone facilitate easy collaboration and video calls. Unique fast keys make navigation between your favorite apps, interactive whiteboard, computer and any other source super easy. The integrated interactive ecosystem tools enable secure wireless presentation and collaboration. The flexibility of MIRA makes this interactive display the ultimate solution for your workplace!

Newline MIRA includes the following interactive ecosystem tools for Android:



BROADCAST

DISPLAY **MANAGEMENT**

MODEL	TT-6520H0	TT-7520H0	TT-8620H0
Display			
Active Screen Size	65"	75"	86"
Backlight type	03	LED (WCG + anti blue light)	80
Aspect ratio		16:9	
Resolution	3840 x 2160		
	1.07 billion		
Display color	≥400 cd/m²		
Brightness		4000:1	
Contrast Ratio (Dynamic)	178°		
/iewing angle	>50.000 hours		
ife Time		250.000 nours	
Electrical	050W	00011	40004
ower Consumption (Normal)	≤250W	≤300W	≤400W
ower Consumption (Standby mode)		<0,5W	
/orking Voltage	AC100-240V, 50/60Hz, Max 3.0A		
ouch			
urface treatment	Optical Bonding / Anti-glare tempered glass + Anti-fingerprint		
ouch type	IR		
Vriting pen	Fine pen		
ouch points	Windows 20 points, Android 10 points		
peaker			
peaker Position	Downward		
peaker Rated Impedance	8Ω		
peaker Max.Power Output		2 x 15 W	
ransportation/Storage			
Outline Dimension	1509 x 883 x 80 mm	1730 x 1007 x 81 mm	1976 x 1147 x 81 mm
ackage size	1640 x 1036 x 221 mm	1859 x 1160 x 247 mm	2119 x 1281 x 275 mm
let weight	34,7 Kg	46 Kg	57,5 Kg
roop weight	45,5 Kg	61,3 Kg	75,8 Kg
noss weight	45,5 Kg		
· · · · · · · · · · · · · · · · · · ·	600 x 400 mm	800 x 400 mm	800 x 400 mm
/ESA mount	. •	800 x 400 mm	800 x 400 mm
Gross weight /ESA mount O Ports Rear input ports	600 x 400 mm USB-A 2.0 (Android) x 1, USB-A 3.0 (Dy	800 x 400 mm ynamic) x 2, HDMI 2.0 (4K@60Hz) x 2, V0 1, RS232 x 1, Microphone In x 1, USB-C	GA (2K@60Hz) x 1, Audio In x 1, USB- <i>A</i>
/ESA mount D Ports Rear input ports	600 x 400 mm USB-A 2.0 (Android) x 1, USB-A 3.0 (Dy 3.0 (Touch) x 1, RJ45 ln x	ynamic) x 2, HDMI 2.0 (4K@60Hz) x 2, V0	GA (2K@60Hz) x 1, Audio In x 1, USB-, (Sound Bar) x 1, USB-C x 1
PESA mount D Ports Dear input ports Dear output ports	600 x 400 mm USB-A 2.0 (Android) x 1, USB-A 3.0 (Dy 3.0 (Touch) x 1, RJ45 ln x	ynamic) x 2, HDMI 2.0 (4K@60Hz) x 2, V0 1, RS232 x 1, Microphone In x 1, USB-C	GA (2K@60Hz) x 1, Audio In x 1, USB-, (Sound Bar) x 1, USB-C x 1
PESA mount D Ports Dear input ports Dear output ports Dear output ports Dear output ports	600 x 400 mm USB-A 2.0 (Android) x 1, USB-A 3.0 (Dy 3.0 (Touch) x 1, RJ45 ln x	ynamic) x 2, HDMI 2.0 (4K@60Hz) x 2, V0 1, RS232 x 1, Microphone In x 1, USB-C 2.0 out (4k@60 Hz) x 1, Earphone x 1, SI	GA (2K@60Hz) x 1, Audio In x 1, USB-, (Sound Bar) x 1, USB-C x 1
PESA mount D Ports Dear input ports Dear output ports DPS port Smart System	600 x 400 mm USB-A 2.0 (Android) x 1, USB-A 3.0 (Dy 3.0 (Touch) x 1, RJ45 ln x	ynamic) x 2, HDMI 2.0 (4K@60Hz) x 2, V(1, RS232 x 1, Microphone In x 1, USB-C 2.0 out (4k@60 Hz) x 1, Earphone x 1, SI Yes, 4K@60 Hz/30 Hz	GA (2K@60Hz) x 1, Audio In x 1, USB- (Sound Bar) x 1, USB-C x 1 PDIF x 1
PESA mount D Ports Rear input ports Rear output ports PPS port Cmart System PPU	600 x 400 mm USB-A 2.0 (Android) x 1, USB-A 3.0 (Dy 3.0 (Touch) x 1, RJ45 ln x	ynamic) x 2, HDMI 2.0 (4K@60Hz) x 2, V0 1, RS232 x 1, Microphone In x 1, USB-C 2.0 out (4k@60 Hz) x 1, Earphone x 1, SI	GA (2K@60Hz) x 1, Audio In x 1, USB- (Sound Bar) x 1, USB-C x 1 PDIF x 1
PESA mount D Ports Rear input ports Rear output ports DPS port Cmart System CPU	600 x 400 mm USB-A 2.0 (Android) x 1, USB-A 3.0 (Dy 3.0 (Touch) x 1, RJ45 ln x	ynamic) x 2, HDMI 2.0 (4K@60Hz) x 2, V0 1, RS232 x 1, Microphone In x 1, USB-C 2.0 out (4k@60 Hz) x 1, Earphone x 1, SI Yes, 4K@60 Hz/30 Hz + A53 x 2 (A53 : 1.05-1.3GHz; A73 : 1.15	GA (2K@60Hz) x 1, Audio In x 1, USB- (Sound Bar) x 1, USB-C x 1 PDIF x 1
PESA mount D Ports Dear input ports Dear output ports DPS port DPS port DPU DPU DPU DAM	600 x 400 mm USB-A 2.0 (Android) x 1, USB-A 3.0 (Dy 3.0 (Touch) x 1, RJ45 ln x	ynamic) x 2, HDMI 2.0 (4K@60Hz) x 2, V0 1, RS232 x 1, Microphone In x 1, USB-C 2.0 out (4k@60 Hz) x 1, Earphone x 1, SI Yes, 4K@60 Hz/30 Hz + A53 x 2 (A53 : 1.05-1.3GHz; A73 : 1.15 MaliG51 x 4 4 GB	GA (2K@60Hz) x 1, Audio In x 1, USB-/ (Sound Bar) x 1, USB-C x 1 PDIF x 1
PESA mount D Ports Rear input ports Rear output ports PPS port Rear System PPU RAM ROM	600 x 400 mm USB-A 2.0 (Android) x 1, USB-A 3.0 (Dy 3.0 (Touch) x 1, RJ45 ln x	ynamic) x 2, HDMI 2.0 (4K@60Hz) x 2, V0 1, RS232 x 1, Microphone In x 1, USB-C 2.0 out (4k@60 Hz) x 1, Earphone x 1, SI Yes, 4K@60 Hz/30 Hz + A53 x 2 (A53 : 1.05-1.3GHz; A73 : 1.15 MaliG51 x 4 4 GB 64 GB	GA (2K@60Hz) x 1, Audio In x 1, USB-/ (Sound Bar) x 1, USB-C x 1 PDIF x 1
ZESA mount O Ports Rear input ports Rear output ports DPS port Gmart System CPU GPU RAM ROM Android version	600 x 400 mm USB-A 2.0 (Android) x 1, USB-A 3.0 (Dy 3.0 (Touch) x 1, RJ45 ln x HDMI	ynamic) x 2, HDMI 2.0 (4K@60Hz) x 2, V0 1, RS232 x 1, Microphone In x 1, USB-C 2.0 out (4k@60 Hz) x 1, Earphone x 1, SI	GA (2K@60Hz) x 1, Audio In x 1, USB-/ (Sound Bar) x 1, USB-C x 1 PDIF x 1 G-1.5GHz)
Pear input ports Rear output ports Rear output ports Rear System RPU RAM ROM Android version Vi-Fi module	600 x 400 mm USB-A 2.0 (Android) x 1, USB-A 3.0 (Dy 3.0 (Touch) x 1, RJ45 ln x HDMI	ynamic) x 2, HDMI 2.0 (4K@60Hz) x 2, V0 1, RS232 x 1, Microphone In x 1, USB-C 2.0 out (4k@60 Hz) x 1, Earphone x 1, SI Yes, 4K@60 Hz/30 Hz + A53 x 2 (A53 : 1.05-1.3GHz; A73 : 1.15 MaliG51 x 4 4 GB 64 GB 8.0	GA (2K@60Hz) x 1, Audio In x 1, USB-/ (Sound Bar) x 1, USB-C x 1 PDIF x 1 G-1.5GHz)
VESA mount O Ports Rear input ports Rear output ports OPS port CPU CPU CAM ROM Android version VI-Fi module Built in Camera & Microphones	600 x 400 mm USB-A 2.0 (Android) x 1, USB-A 3.0 (Dy 3.0 (Touch) x 1, RJ45 ln x HDMI	ynamic) x 2, HDMI 2.0 (4K@60Hz) x 2, V0 1, RS232 x 1, Microphone In x 1, USB-C 2.0 out (4k@60 Hz) x 1, Earphone x 1, SI	GA (2K@60Hz) x 1, Audio In x 1, USB- (Sound Bar) x 1, USB-C x 1 PDIF x 1 G-1.5GHz)
Pess mount Description Descrip	600 x 400 mm USB-A 2.0 (Android) x 1, USB-A 3.0 (Dy 3.0 (Touch) x 1, RJ45 ln x HDMI	ynamic) x 2, HDMI 2.0 (4K@60Hz) x 2, V0 1, RS232 x 1, Microphone In x 1, USB-C 2.0 out (4k@60 Hz) x 1, Earphone x 1, SI	GA (2K@60Hz) x 1, Audio In x 1, USB- (Sound Bar) x 1, USB-C x 1 PDIF x 1 G-1.5GHz)
Personal Ports Rear input ports Rear output ports Rear output ports Rear System RPU RAM ROM Randroid version Wi-Fi module Resolution Max. Resolution Max. Rewing angle	600 x 400 mm USB-A 2.0 (Android) x 1, USB-A 3.0 (Dy 3.0 (Touch) x 1, RJ45 ln x HDMI A73 x 2	ynamic) x 2, HDMI 2.0 (4K@60Hz) x 2, V0 1, RS232 x 1, Microphone In x 1, USB-C 2.0 out (4k@60 Hz) x 1, Earphone x 1, SI	GA (2K@60Hz) x 1, Audio In x 1, USB- (Sound Bar) x 1, USB-C x 1 PDIF x 1 5-1.5GHz) the same time
ESA mount D Ports Pear input ports Pear output ports PPS port PPU AM OM Indroid version Vi-Fi module Puilt in Camera & Microphones Pesolution Max. Tiewing angle uilt-in Microphone	600 x 400 mm USB-A 2.0 (Android) x 1, USB-A 3.0 (Dy 3.0 (Touch) x 1, RJ45 ln x HDMI A73 x 2	ynamic) x 2, HDMI 2.0 (4K@60Hz) x 2, V0 1, RS232 x 1, Microphone In x 1, USB-C 2.0 out (4k@60 Hz) x 1, Earphone x 1, SI	GA (2K@60Hz) x 1, Audio In x 1, USB- (Sound Bar) x 1, USB-C x 1 PDIF x 1 5-1.5GHz) the same time
Personal Ports Rear input ports Rear output ports Rear output ports Rear System RPU RAM ROM RICHARD R	600 x 400 mm USB-A 2.0 (Android) x 1, USB-A 3.0 (Dy 3.0 (Touch) x 1, RJ45 ln x HDMI A73 x 2	ynamic) x 2, HDMI 2.0 (4K@60Hz) x 2, V0 1, RS232 x 1, Microphone In x 1, USB-C 2.0 out (4k@60 Hz) x 1, Earphone x 1, SI	GA (2K@60Hz) x 1, Audio In x 1, USB- (Sound Bar) x 1, USB-C x 1 PDIF x 1 5-1.5GHz) the same time
/ESA mount O Ports	600 x 400 mm USB-A 2.0 (Android) x 1, USB-A 3.0 (Dy 3.0 (Touch) x 1, RJ45 ln x HDMI A73 x 2	ynamic) x 2, HDMI 2.0 (4K@60Hz) x 2, V0 1, RS232 x 1, Microphone In x 1, USB-C 2.0 out (4k@60 Hz) x 1, Earphone x 1, SI	GA (2K@60Hz) x 1, Audio In x 1, USB-A (Sound Bar) x 1, USB-C x 1 PDIF x 1 5-1.5GHz) the same time

newline

ASIA PACIFIC OFFICE

4F-3, No. 76, Sec. 2, Jiafeng S. Rd., Zhubei City, Hsinchu County, 302, Taiwan

TEL: +886 3 550 4768

EUROPE OFFICE

Ronda de Poniente 16, Bajo E-28760, Tres Cantos, Madrid, Spain

TEL: +34 911169178

INDIA OFFICE

Room No. 203, No.37, TTK Road, 101 East Park Blvd. Alwarpet, Chennai, Tamil Nadu, India, 600018

TEL: +91 44 46945513

NEWLINE INTERACTIVE INC.

Suite 807 Plano, TX 75074, USA

TEL: +1 888 233 0868