

newline *nt*



LARGE-SCALE COLLABORATION FOR EFFECTIVE AND STREAMLINED MEETINGS

The NT Series is an innovative line of non-touch displays designed for large-scale collaboration. Created with your team's needs in mind, the NT Series brings you all the collaborative tools a TV screen lacks. Streamline your meetings and presentations by focusing on just the tools you need to succeed.



85", 98"



4K Ultra HD



Non-touch

newline *nt*



4K

Superior Image Quality with 4K UHD resolution



Remote control from provided device or app

WCG

Vivid and brighter images with Wide Color Gamut



Blue Light Filter for a safe viewing experience



Built-in mic array for conferences and voice control



CAST

Built-in wireless casting with Newline Cast. Present and share content seamlessly from any device and OS with a single click.



BROADCAST

Share the NT Series display screen in real-time with Newline Broadcast. Invite up to 200 participants to connect from anywhere in the world.



DISPLAY MANAGEMENT

Configure display settings, use digital signage features or broadcast emergency messages to all Newline displays from your desk with Newline Display Management.



Office Viewer

FILE MANAGEMENT

Embedded file viewer to open and manage all your files right on the NT Series. Compatible with Word, Excel, PowerPoint and PDF documents.



Cloud

DIRECT CLOUD ACCESS

Access your files from the cloud directly on the display. Pull them up on the large screen, even if you forgot to bring your personal device or flash drive with you.

Model	TT-8519NT	TT-9819NT
Display		
Backlight	LED	
Display Area	1872 × 1053 mm	2159 × 1214 mm
Display Ratio	16:9	
Resolution	3840 × 2160 Pixels	
Display Color Depth	8-bit	10-bit
Brightness	≥ 400 nit	
Contrast Ratio	4000:1	1200:1
Viewing Angle	178°	
Life Time	≥ 50,000 hours	
Speaker		
Max. Power Output	20 W × 2	
Rated Impedance	6 Ω	
Electrical		
Power Consumption	≤ 450 W	≤ 700 W
Standby Power Consumption	< 0.5 W	
Working Voltage	AC 100-240 V	
Transportation/ Storage		
Storage Temperature/ Humidity	15 - 55 / 20 - 90 %RH	
Working Temperature/ Humidity	0 - 40 / 20 - 80 %RH	
Mounting (Optional)	Wall Mount/ Floor Stand	
Outline Dimensions	1967 × 1152 × 87	