


newline



Built-In
Cameras



Microphone Array



Superior Touch



Annotation



Go Wireless



Win/iOS/Android
Compatibility



Collaboration
Hub



Security

THE NEXT GENERATION OF IMMERSIVE AND UNIFIED COLLABORATION

The X5/X7 offer an all-in-one solution for productive and effective collaboration in the workplace. With superb high-quality audio and two built-in 1080p wide-angle cameras, meeting participants from multiple locations can see and interact with one another naturally, as if they were in the same room. Writing on the X5/X7 feels as smooth as writing on paper, providing meeting members inspirational confidence to have better, more creative meetings.

The X5/X7 allow you to hold video conferences and collaborate easily, with no limitations. Bring your own device and share voice, video, data and annotations. Work with your OS and device of choice, the way you like it.

X Series

X Series

Model	X5	X7	Model	X5	X7
Display			Touch		
Backlight	LED		Touch Surface	Chemically Strengthened Soda Lime Glass	Tempered Glass
Display Area	1210 × 680 mm	1539 × 866 mm	Transparency	> 89%	> 90%
Active Screen Size	55"	70"	Surface Hardness	8H	7H
Display Ratio	16:9		Touch Technology	InGlass	P-Capacitive Touch
Resolution	1920 × 1080 Pixels		HID Support	HID	HID
Display Color Depth	8-bit	10-bit	Touch Points	10 Points in Windows/ 5 Points in Android (3 points to write, 5 points to erase)	10 Points in Windows/ 5 Points in Android
Brightness	370 nit	350 nit	Writing Tools	Passive Pen/ Finger/ Palm	Passive Pen/ Finger/ Palm
Contrast Ratio	4000:1		Scan Speed	100 Hz	180 Hz
Response Time	8 ms		Positioning Accuracy	±1.0 mm	
Life Time	≥ 30,000 hours		Communication Interface	USB-A	
Speaker			Microphone		
Speaker Position	Front		Sensitivity	-28 ± 3 dB	
Rated Impedance	8 Ω(±15%)	8 Ω	Frequency Response	100 - 7.75K Hz	
Frequency Response	90(±20%) - 18K Hz		Polar Patterns	Omnidirectional	
Output SPL	84 ± 3 dB		THD +N (1K Hz @ +4dBu)	< 1% at 6 dB SPL	
Max. Power Output	10 W × 2	15 W × 2	Quantity	4	
Camera			Connectivity		
Position	Top × 1, Bottom × 1 (Only one can be used at a time)		Front Interface Inputs	MIC(3.5mm) × 1, HDMI × 1, USB(Touch) × 1, USB(Internal PC) × 1, USB(Embedded System) × 1	MIC(3.5mm) × 1, HDMI × 1, USB(Touch) × 1, USB(OPS) × 1, USB(Android) × 1
Sensor	2M Pixels		AV Inputs	HDMI × 1, VGA × 1, USB(Touch) × 2, Audio(3.5 mm) × 1	
Lens	86°		AV Outputs	Line Out(3.5 mm) × 1, HDMI × 1(Only Video)	
Video Resolution	1920 × 1080 @30fps (Max)		Other	USB 2.0 × 2, RS232 × 1, RJ45 × 1, USB 3.0 × 1, SD Reader, OPS Slot	
Environmental/ Physical Specifications			Power		
Storage Temperature/ Humidity	-10 - 50 / 10 - 90% RH		Power Consumption	Maximum < 180 W (X5+I5 OPS) Maximum < 160 W (Only X5) Standby Mode ≤ 0.5 W	Maximum < 250 W Standby Mode ≤ 0.5 W
Working Temperature/ Humidity	0 - 40 / 10 - 90% RH		Working Voltage	AC 100-240 V, 50/60 Hz	
Mounting (Optional)	Wall Mount/ Floor Stand		Other Features		
Outline Dimensions	1320 × 886 × 87 mm	1589 × 1049 × 78 mm	Intelligent Thermo-Protector	Yes	
Packing Dimensions	1470 × 995 × 265 mm	1720 × 1180 × 270 mm	Built-In Wi-Fi	Yes	
Net Weight	36 kg	65 kg			
Gross Weight	45 kg	80 kg			

newline

NEWLINE INTERACTIVE INC.

950 W Bethany Drive
Suite 330
Allen, TX 75013
TEL: +1 888 233 0868

ASIA PACIFIC OFFICE

4F-3, No. 76, Sec. 2, Jiafeng S. Rd.,
Zhubei City, Hsinchu County,
302, Taiwan
TEL: +886 3 550 4768

EUROPE OFFICE

Ronda de Poniente, N'2, 1st floor,
Oficina 1B, 28760,
Tres Cantos, Madrid, Spain
TEL: +34 911169178

INDIA OFFICE

Room No. 203, No. 37, TTK Road,
Alwarpet, Chennai,
Tamil Nadu, India, 600018
TEL: 1 800 419 0309

newline-interactive.com

2019 Newline Interactive Inc. Specification may vary by region, please contact our local offices for details. Actual product features and specifications are subject to change without notice. This material may include corporate names and trademarks of third parties which are the properties of the third parties respectively.