







Optical Bonding



Built-In Cameras



Annotation



Microphone Array



Collaboration



Security Hub



Win/Android/iOS Compatibility

THE UNMATCHED ALL-IN-ONEUNIFIED COLLABORATION SOLUTION

The PTC Series is an all-in-one UHD solution for collaboration that is immersive, unified and effective. P-Cap touch technology enables a more accurate, responsive touch for a smooth and intuitive writing experience as natural as writing on a paper. The unique Optical Bonding technology reduces light reflection and parallax effect to provide the best visual experience possible.

PTC Series is the pioneer of workspace innovation, maximizing the efficiency of meetings and discussions. Share files, ideas and notes remotely and seamlessly with the tools you prefer and the devices you have, and never let another idea slip away. Join the workstyle revolution with Newline PTC Series and embrace new ways of engagement and collaboration.

Ideal for corporate environments that require video conference capabilities.

PTC Series

Model	TT-6519PTC	TT-7519PTC	TT-8619PTC
	Displa	ay	
Display Backlight		LED (Blue light filter)	
Display Area	1428.48 x 803.52 mm	1650.24 x 928.26 mm	1895.04 x 1065.96 mm
Active Screen Size ("inch)	65"	75"	86"
Display Ratio		16:9	
Resolution		3840 × 2160 Pixels	
Display Colors	8 bit + FRC		10 bit 1.07Billion
LCD Brightness(After Glass)		≧ 370 nit	
Contrast Ratio (Dynamic)		4000:1	
Viewing Angle		178°	
Life time (working hours/day)		≥ 50,000 hours	
Response Time		8ms	
Response Time	Charle		
On a class Desition	Speak		
Speaker Position		Soundbar mounted on top	
Speaker Max.Power Output		TS Soundbar : 20W x 2 (8Ω)	
Transmission Range	-2	> 12m	
	Powe		
Power Consumption	Maximum ≦ 300 W Standby Mode ≦ 0.5 W	Maximum \leq 400 W Standby Mode \leq 0.5 W	Maximum ≤ 450 W Standby Mode ≤ 0.5 W
Working Voltage	,	AAC 100-240V, 50/60Hz	,
	Touc		
Touch Surface Technology		Anti-Glare, tempered glass with Optical bondin	ng
Touch Surface Hardness		7H	
Touch Type		P-CAP	
Touch Points		Up to 20 Points	
Touch Screen Writing Tools		Stylus, Finger	
Communication Interface		USB-A	
	Transportation	ı / Storage	
Storage Temperature/ Humidity		-10°C ~ 45°C / 20 ~ 90% RH	
Working Temperature/ Humidity	0°C ~ 40°C / 20 ~ 80% RH (Non Condensing)		
Mounting Options		Wall-mount or Mobile Stand	
Outline Dimensions	1509 × 865 × 86 mm	1731 × 1010 × 86 mm	1997 × 1150 × 86 mm
Packing Dimensions	1640 × 1036 × 221 mm	1859 × 1160 × 247 mm	2119 × 1281 × 275 mm
Net Weight	Approx.40kg	Approx.50kg	Approx.61kg
Gross Weight	49kg	69kg	83kg
GIOSS WEIGHT		Uaky	ooky
VESA Mount installation position	The state of the s	800 v	400 mm
VESA Mount installation position	600 x 400 mm		400 mm
	The state of the s	s	400 mm
VESA Mount installation position Front Interface Inputs Rear AV Inputs	600 x 400 mm Ports		
Front Interface Inputs Rear AV Inputs	600 x 400 mm Ports	s NA	
Front Interface Inputs	600 x 400 mm Ports HDMI In x 2	NA NA 2, VGA In × 1, Audio In × 1, Microphone In × 1	, Type C x 1
Front Interface Inputs Rear AV Inputs AV Outputs	600 x 400 mm Ports HDMI In x 2 USB 2.0 (Android) x 1, USB 3.0 (Public) x	NA NA 2, VGA In x 1, Audio In x 1, Microphone In x 1 HDMI out x 1, Earphone x 1, SPDIF x 1 (2, USB 3.0 Touch x 1, RJ45 x 1, RS232 x 1, (, Type C x 1
Front Interface Inputs Rear AV Inputs AV Outputs	600 x 400 mm Ports HDMI In x 2	NA NA 2, VGA In x 1, Audio In x 1, Microphone In x 1 HDMI out x 1, Earphone x 1, SPDIF x 1 (2, USB 3.0 Touch x 1, RJ45 x 1, RS232 x 1, (, Type C x 1
Front Interface Inputs Rear AV Inputs AV Outputs Other	600 x 400 mm Ports HDMI In x 2 USB 2.0 (Android) x 1, USB 3.0 (Public) x	NA 2, VGA In x 1, Audio In x 1, Microphone In x 1 HDMI out x 1, Earphone x 1, SPDIF x 1 x 2, USB 3.0 Touch x 1, RJ45 x 1, RS232 x 1, 0 ating System	, Type C x 1
Front Interface Inputs Rear AV Inputs AV Outputs Other	600 x 400 mm Ports HDMI In x 2 USB 2.0 (Android) x 1, USB 3.0 (Public) x	NA 2, VGA In x 1, Audio In x 1, Microphone In x 1 HDMI out x 1, Earphone x 1, SPDIF x 1 x 2, USB 3.0 Touch x 1, RJ45 x 1, RS232 x 1, Cating System Hisilicon 811 (A73 x 2 + A53 x 2)	, Type C x 1
Front Interface Inputs Rear AV Inputs AV Outputs Other CPU GPU	600 x 400 mm Ports HDMI In x 2 USB 2.0 (Android) x 1, USB 3.0 (Public) x	NA 2, VGA In x 1, Audio In x 1, Microphone In x 1 HDMI out x 1, Earphone x 1, SPDIF x 1 x 2, USB 3.0 Touch x 1, RJ45 x 1, RS232 x 1, 0 ating System Hisilicon 811 (A73 x 2 + A53 x 2) MaliG51 x 4	, Type C x 1
Front Interface Inputs Rear AV Inputs AV Outputs Other CPU GPU RAM	600 x 400 mm Ports HDMI In x 2 USB 2.0 (Android) x 1, USB 3.0 (Public) x	NA 2, VGA In x 1, Audio In x 1, Microphone In x 1 HDMI out x 1, Earphone x 1, SPDIF x 1 (2, USB 3.0 Touch x 1, RJ45 x 1, RS232 x 1, 0 ating System Hisilicon 811 (A73 x 2 + A53 x 2) MaliG51 x 4 4GB	, Type C x 1
Front Interface Inputs Rear AV Inputs AV Outputs Other CPU GPU RAM ROM	600 x 400 mm Ports HDMI In x 2 USB 2.0 (Android) x 1, USB 3.0 (Public) x	NA 2, VGA In x 1, Audio In x 1, Microphone In x 1 HDMI out x 1, Earphone x 1, SPDIF x 1 x 2, USB 3.0 Touch x 1, RJ45 x 1, RS232 x 1, C ating System Hisilicon 811 (A73 x 2 + A53 x 2) MaliG51 x 4 4GB 32GB 8.0	, Type C x 1
Front Interface Inputs Rear AV Inputs AV Outputs Other CPU GPU RAM ROM	600 x 400 mm Ports HDMI In x 2 USB 2.0 (Android) x 1, USB 3.0 (Public) x Embedded Opera	NA 2, VGA In x 1, Audio In x 1, Microphone In x 1 HDMI out x 1, Earphone x 1, SPDIF x 1 x 2, USB 3.0 Touch x 1, RJ45 x 1, RS232 x 1, C ating System Hisilicon 811 (A73 x 2 + A53 x 2) MaliG51 x 4 4GB 32GB 8.0	, Type C x 1
Front Interface Inputs Rear AV Inputs AV Outputs Other CPU GPU RAM ROM Android Version	HDMI In x2 USB 2.0 (Android) x 1, USB 3.0 (Public) x Embedded Opera	NA 2, VGA In x 1, Audio In x 1, Microphone In x 1 HDMI out x 1, Earphone x 1, SPDIF x 1 x 2, USB 3.0 Touch x 1, RJ45 x 1, RS232 x 1, (ating System Hisilicon 811 (A73 x 2 + A53 x 2) MaliG51 x 4 4GB 32GB 8.0	, Type C x 1 DPS slot (4K@60Hz/30Hz) x 1, AC In x
Front Interface Inputs Rear AV Inputs AV Outputs Other CPU GPU RAM ROM Android Version OPS PC	HDMI In x2 USB 2.0 (Android) x 1, USB 3.0 (Public) x Embedded Opera Othe	NA 2, VGA In x 1, Audio In x 1, Microphone In x 1 HDMI out x 1, Earphone x 1, SPDIF x 1 x 2, USB 3.0 Touch x 1, RJ45 x 1, RS232 x 1, 0 ating System Hisilicon 811 (A73 x 2 + A53 x 2) MaliG51 x 4 4GB 32GB 8.0 Optional	, Type C x 1 DPS slot (4K@60Hz/30Hz) x 1, AC In x
Front Interface Inputs Rear AV Inputs AV Outputs Other CPU GPU RAM ROM Android Version OPS PC Built-in Wifi Built-in Camera	HDMI In x2 USB 2.0 (Android) x 1, USB 3.0 (Public) x Embedded Opera Othe	NA 2, VGA In x 1, Audio In x 1, Microphone In x 1 HDMI out x 1, Earphone x 1, SPDIF x 1 x 2, USB 3.0 Touch x 1, RJ45 x 1, RS232 x 1, 0 ating System Hisilicon 811 (A73 x 2 + A53 x 2) MaliG51 x 4 4GB 32GB 8.0 T Optional in 2.4g /5G, support wifi, hotspot at the same	, Type C x 1 DPS slot (4K@60Hz/30Hz) x 1, AC In x
Front Interface Inputs Rear AV Inputs AV Outputs Other CPU GPU RAM ROM Android Version OPS PC Built-in Wifi	Othe CMOS Sensor resolution 14	NA 2, VGA In x 1, Audio In x 1, Microphone In x 1 HDMI out x 1, Earphone x 1, SPDIF x 1 x 2, USB 3.0 Touch x 1, RJ45 x 1, RS232 x 1, 0 ating System Hisilicon 811 (A73 x 2 + A53 x 2) MaliG51 x 4 4GB 32GB 8.0 Optional in 2.4g /5G, support wifi, hotspot at the same	, Type C x 1 DPS slot (4K@60Hz/30Hz) x 1, AC In x etime t center, Viewing Angle 90°
Front Interface Inputs Rear AV Inputs AV Outputs Other CPU GPU RAM ROM Android Version OPS PC Built-in Wifi Built-in Camera Built-in Microphone	Othe Support (dual-OS switching) remotes Ports HDMI In x2 USB 2.0 (Android) x 1, USB 3.0 (Public) x Embedded Opera	NA 2, VGA In x 1, Audio In x 1, Microphone In x 1 HDMI out x 1, Earphone x 1, SPDIF x 1 x 2, USB 3.0 Touch x 1, RJ45 x 1, RS232 x 1, 0 ating System Hisilicon 811 (A73 x 2 + A53 x 2) MaliG51 x 4 4GB 32GB 8.0 T Optional in 2.4g /5G, support wifi, hotspot at the same 920x1080, size 1/2.9, position below the from 4-way matrix, 8m pickup distance	, Type C x 1 PPS slot (4K@60Hz/30Hz) x 1, AC In x time t center, Viewing Angle 90° n, noise suppression, beam forming

newline

HEADQUARTERS (TX, USA) 101 East Park Blvd. Suite 807 Plano, TX 75074, USA

TEL: +1 888 233 0868 info@newline-interactive.com

APAC OFFICE (Hsinchu, Taiwan) 6F-3, No. 8, Taiyuan 2nd St.,

Zhubei City, Hsinchu County 302082 , Taiwan TEL: +886 3 550 4768 info_ap@newline-interactive.com EUROPE OFFICE (Madrid, Spain)

Ronda de Poniente, N'2, 1st floor, Oficina 1B, 28760, Tres Cantos, Madrid, Spain TEL: +34 911169178 info_eu@newline-interactive.com INDIA OFFICE (Chennai)

Room No. 203, No. 37, TTK Road, Alwarpet, Chennai, Tamil Nadu, India, 600018 TEL: 1 800 419 0309 info.in@newline-interactive.com KOREA OFFICE (Seoul, South Korea)

A816, 8F, 401 Yangcheon-ro, Gangseo-gu, Seoul, 07528 Korea TEL: +82 2 2638 5140 koreainfo@newline-interactive.com

newline-interactive.com