newline









Wireless Casting



the Cloud



Non-Touch Display



Embedded OS



Remote Management



Control by Remote



with all Devices

STREAMLINE YOUR SUCCESS

The NT+ Series is a non-touch display that brings your lessons to life in vivid Ultra-High Definition (4K) resolution. Focus on just the tools you need to get your students engaged in class without paying more for features you won't use.

Wirelessly cast to the screen from any mobile device, tablet, desktop, or laptop. Whether you use Windows, Mac, or Chrome, the NT+ Series lets you share your screen through a wireless connection or through the multiple I/O ports built into the panel. Access your files on your preferred Cloud storage system right on the display. The built-in file viewer lets you easily navigate through local files, Cloud storage, and files from connected USB thumb drives.

Rediscover the simplicity of real innovation with the new NT+ Series.

Newline NT+ Series includes the following software solutions





DISPLAY MANAGEMENT PLUS

NT+ Series

Model	TT-5522NT-PLUS	TT-6522NT-PLUS	TT-7522NT-PLUS	TT-8622NT-PLUS	TT-9822NT-PLUS	
Display						
Screen Size	55"	65"	75"	86"	98"	
andscape/Portrait Mode	Both	Both	Landscape Only	Landscape Only	Landscape Only	
Backlight	LED	LED	LED	LED	LED	
isplay Ratio	16:9	16:9	16:9	16:9	16:9	
Resolution	3840 x 2160 pixels	3840 x 2160 pixels	3840 x 2160 pixels	3840 x 2160 pixels	3840 x 2160 pixels	
Display Colors	1.07 billion (8 bit + FRC)	1.07 billion (8 bit + FRC)	1.07 billion (8 bit + FRC)	1.07 billion (8 bit + FRC)	1.07 billion (8 bit + FRC)	
Brightness Center Brightness	Without cover glass	Without cover glass	Without cover glass	Without cover glass	Without cover glass	
	>400 cd/m²	>400 cd/m²	>400 cd/m ²	>400 cd/m²	>400 cd/m²	
Contrast	Dynamic 5000:1 Static 1200:1	Dynamic 5000:1 Static 1200:1	Dynamic 5000:1 Static 1200:1	Dynamic 5000:1 Static 1200:1	Dynamic 5000:1 Static 1200:1	
Response Time	8 ms	8 ms	8 ms	8 ms	8 ms	
/iewing Angle	178°	178°	178°	178°	178°	
_ifetime Hours	≥ 50,000 hours	≥ 50,000 hours	≥ 50,000 hours	≥ 50,000 hours	≥ 50,000 hours	
Speakers						
Position	Downward	Downward	Downward	Downward	Downward	
Max Power Output	(2) 15W	(2) 20W	(2) 20W	(2) 20W	(2) 20W	
ransportation/Storage						
outline Dimension	50 x 29 x 3 in	58 x 34 x 4 in	70 x 39 x 4 in	77 x 44 x 4 in	TBD	
acking Dimension	55 x 33 x 8 in	63 x 39 x 8	72 x 43 x 9	82 x 49 x 10	TBD	
let Weight	40 lbs	TBD	73 lbs	TBD	TBD	
Gross Weight	56 lbs	TBD	102 lbs	TBD	TBD	
/ESA Mount nstallation position	400 x 400 mm	600 x 400 mm	800 x 400 mm	800 x 400 mm	800 x 600 mm	
nstallation Method						
Mounting Options	Wall-mounted, Mobile Stand					
Small form factor Computer VESA	No	Yes	Yes	Yes	Yes	
mbedded Operating Systen	1					
RAM	4GB	4GB	4GB	4GB	4GB	
ROM	32GB	32GB	32GB	32GB	32GB	
android Version	11.0	11.0	11.0	11.0	11.0	
speciality						
Vi-Fi Module (Optional)	Pluggable Wi-Fi module, Wi-Fi 6 and BlueTooth 5.2 capable					
irmware update	USB, OTA					
		(1) Power Button				
Back Button	Rocker switch for power Up, Down, Left, Right, OK, Return, Menu					
Continuous Use Time	24/7					
Ports						
Ports Front Port			n/a			

