## newline

All Stars

Vega is the brightest star in the northern constellation of Lyra and relatively close at only 25 light-years from the Sun.







## IMMERSIVE ALL-IN-ONE EXPERIENCE

Vega, Newline's flagshipmodel, is the high end solution for your boardroom offering an immersive AV experience. The sleek unique 3mm bezel with edge-to-edge glass, combined with optically bonded PCAP offers a world class touch and writing experience. Vega features a high-end built-in AV system that includes a 4K camera, an 8 mic array, powerful 20W speakers and subwoofer.

Seamless integration of OPS and SDM into the touchscreen facilitates direct connection to the built-in AV system without the need for any cables. Combined with 100W powered USB-C connection for your laptop, the latest wifi and bluetooth, you have a winning all-in-one solution for your corporate workplace!



No cables needed!

## INTERACTIVE ECOSYSTEM

The completely renewed Interactive Ecosystem is full of software that helps you use your interactive display to the max. Whether it's setting up your video conference super fast, using concept mapping to brainstorm, connecting your device, sharing your screen or broadcasting!





Edae-to-Edae

alass.

Ultra slim design

Wilfi 6



100W Powered

USB Type-C

High Quality Sound incl Subwoofer





Comprehensive Warranty & OTA Update









MODEL	TT-6522Z	CAMERA MODULE	4K
Vega 65"		Camera Resolution	
Vega 75"	TT-7522Z	Field of View	120° FOV Lenses
Vega 86"	TT-8622Z	Camera Tild Range	15°
PANEL		REAR I/O	
Backlight	Direct LED (Wide color gamut +	HDMI IN 2.0	2
Dacklight	Anti blue light)	DisplayPort 1.2	1
Glass Surface	Anti-Glare+Anti-Fingerprint	USB Type-B (Touch)	3
	+ Antimicrobial Tempered Glass	USB 3.0 Type-C	1
Bonding Technology	Certified Optical Bonding	(No Power Delivery)	
D: 1 A	65": 1428 x 804 mm	USB 3.0 Type-A	2
Display Area	75": 1650 x 928 mm 86": 1895 x 1066 mm	USB 3.0 Type-A to Android	1
Display Ratio	16:9	HDMI OUT 2.0 RS232	1
Resolution	3840 x 2160 (4K)		
Colours	1,07 Billion	RJ45 (Gigabit) OPS Slot	In x 1 / Out x 1
Brightness	400 cd/m <sup>2</sup>	SPDIF	1
Contrast Ratio	5000:1	Audio Line Out	1
Response Time	6 ms	WIFI Module Slot	•
Viewing Angle	178°	SDM-S Slot	1
Display Life Time	≥50000 hours		1
Transparency	>88%	Power Out Connect (180 W)	T.
Haze	2 %~5%		
Touch Surface Hardness	7H	SMART SYSTEM	Al A011D0t
	711	SoC Chipset	Amlogic A311D2 octa-core processor 4 x Cortex-A73 at 2,2 Ghz, 4 x Corte x-A53 at 2,0 Ghz
POWER CONSUMPTION	65": 133 W	RAM	8 GB (DDR4)
Standard mode	75": 163 W	Storage	128 GB
	86": 263 W	Operating System	Android 11
Standby mode	<0,5 W	Formats Support For Image	JPEG, BMP, PNG
	-,-	r office Support For image	MPEG1, MPEG2, MPEG4,
TOUCH			SorensonH.263,H.263,H.264,
Touch Solution	Projected Capacitive Touch (PCAP)	Formats Support For Video	HEVC/H.265,MVC,AVS,A VS+,WMV3,VC1,Motion
Touch Points	40 Windows / 20 Android		JPEG,VP8,VP9,RV30/RV40
Number of stylus	2 x PCAP Passive Pen (No battery)	Farmanta Ormanat Far Audia	MPEG1/2 @LAYER1; @LAYER2; @LAYER3, EAC3, ACC-LC,
Touch Screen Writing Tools	Passive pen, Finger, Fist	Formats Support For Audio	HEAAC, VORBIS, LPCM, IMA- ADPCM, MS-ADPCM, G711 A/MU-
Accuracy	±1 mm		LAW,LBR(COOK),FLAC
SPEAKER		Proximity Sensor	1
Speaker Position	Front Facing	Camera	1
Speaker Rated Impedance	6 Ω	Wi-Fi 6 + Bluetooth 5.2 Module	Integrated (Replaceable)
Speaker Freq.Response	250 Hz-20 KHz SPL -10 dB		
Output S.P.L.	80±3 dB	EXTRA FIRMWARE FEATURES	
Speaker Max.Power Output	20 W x 2	Lan control	√
		Wake on Lan	<b>√</b>
SUBWOOFER		CEC	√ 1.1.1.: 5.0
Speaker Position	Rear side	Multiuser profile / User Profiles: 6	
Speaker Rated Impedance	4 Ω	Setting Menu Admin Mode	$\checkmark$
Speaker Freq.Response	20 Hz-20 KHz SPL -10 dB		
Output S.P.L.	77±2 dB	TRANSPORTATION / STORAGE	CEN 14071 0100 000
Speaker Max.Power Output	15 W x 1	Outline Dimensions (Excl. wall mount)	65": 1497,1 x 919,6 x 83,8 mm 75": 1719,3 x 1043,7 x 85 mm 86": 1965,2 x 1184,4 x 85 mm
MICROPHONE			65": 36 Kg
Mic Possition	8 Microphone Array Upper Front	Net Weight	75": 50 Kg
Pick Up Distance	8 m	The trongitt	86": 60 Kg
Mic Performance	Echo cancellation, Beamforming, Noise Reduction	VESA	65": 600 x 400 mm 75": 800 x 400 mm 86": 800 x 400 mm

