



Display						
Active Screen Size	43"	55"	65"	75"	85"	98"
Backlight	LCD	LCD	LCD	LCD	LCD	LCD
Display Area	37.1 x 20.8 in	47.6 x 26.8 in	56.2 x 31.6 in	64.9 x 36.5 in	73.7 x 41.5 in	84.9 x 47.8 in
Display Ratio	16:9	16:9	16:9	16:9	16:9	16:9
Resolution	3840 x 2160 (4K)	3840 x 2160 (4K)	3840 x 2160 (4K)	3840 x 2160 (4K)	3840 x 2160 (4K)	3840 x 2160 (4K)
Pixel Pitch (mm)	0.0817 (H) x 0.2451 (V)	0.105 (H) x 0.3115 (V)	0.124 (H) x 0.372 (V)	0.14325 (H) x 0.42975 (V)	0.1625 (H) x 0.4875 (V)	0.1874 (H) x 0.5622 (V)
Refreshing Frequency	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz
Display Colors	1.07 Billion	1.07 Billion	1.07 Billion	1.07 Billion	1.07 Billion	1.07 Billion
Brightness	260 nits	260 nits	270 nits	300 nits	350 nits	450 nits
Contrast Ratio (Dynamic)	4000:1	4000:1	4000:1	4000:1	5000:1	4000:1
Response Time	6.5 ms	6.5 ms	6.5 ms	6.5 ms	6.5 ms	6.5 ms
Viewing Angle	178°	178°	178°	178°	178°	178°
Operation Time	16/7	16/7	16/7	16/7	16/7	16/7
Display Orientation	Landscape	Landscape	Landscape	Landscape	Landscape	Landscape
Glass Surface	Anti-Glare	Anti-Glare	Anti-Glare	Anti-Glare	Anti-Glare	Anti-Glare
Power						
Working Voltage	110-240 V~ 50/60 Hz	110-240 V~ 50/60 Hz	110-240 V~ 50/60 Hz	110-240 V~ 50/60 Hz	110-240 V~ 50/60 Hz	110-240 V~ 50/60 Hz
Power Consumption (normal)	95W	140W	160W	250W	275W	435W
Power Consumption (full load)	105W	150W	170W	170W	290W	450W
Power Consumption (Standby mode)	≤0.5W	≤0.5W	≤0.5W	≤0.5W	≤0.5W	≤0.5W
Speakers						
Speaker Position	Bottom	Bottom	Bottom	Bottom	Bottom	Bottom
Max Power Output	2 x 10 W	2 x 10 W	2 x 10 W	2 x 10 W	2 x 15 W	2 x 15 W
Transportation/Storage						
Storage Temperature/Humidity	-20~60°C 0~85%RH (non-condensing)	-20~60°C 0~85%RH (non-condensing)	-20~60°C 0~85%RH (non-condensing)	-20~60°C 0~85%RH (non-condensing)	-20~60°C 0~85%RH (non-condensing)	-20~60°C 0~85%RH (non-condensing)
Working Temperature/Humidity	0~40°C 20~80%RH (non-condensing)	0~40°C 20~80%RH (non-condensing)	0~40°C 20~80%RH (non-condensing)	0~40°C 20~80%RH (non-condensing)	0~40°C 20~80%RH (non-condensing)	0~40°C 20~80%RH (non-condensing)
Installation Method (optional)	Wall-mounted / Mobile stand	Wall-mounted / Mobile stand	Wall-mounted / Mobile stand	Wall-mounted / Mobile stand	Wall-mounted / Mobile stand	Wall-mounted / Mobile stand
Bezel Width (Top, Left, Right)	1.2 / 1.2 / 1.2 mm	1.4 / 1.4 / 1.4 mm	1.8 / 1.8 / 1.8 mm	1.8 / 1.8 / 1.8 mm	1.8 / 1.8 / 1.8 mm	3.5 / 3.5 / 3.5 mm
Bottom Bezel Width Including IR Receiver	19.3 mm	20.8 mm	20.3 mm	20.4 mm	17.2 mm	30.2 mm
Bottom Bezel Width	16.3 mm	17.5 mm	17.1 mm	19.3 mm	13.9 mm	19.4 mm
Outline Dimension (without wall mount bracket thickness)	37.67 x 22 x 3.4 in	48.27 x 27.91 x 3.45 in	57.71 x 32.71 x 3.35 in	65.67 x 37.64 x 3.47 in	74.4 x 42.56 x 3.59 in	85.9 x 49.4 x 4.37 in
Packing Dimension	42.32 x 25.66 x 5.59 in	53.14 x 32.95 x 5.66 in	62.99 x 37.79 x 6.45 in	72.44 x 43.42 x 7.48 in	79.92 x 49.21 x 7.55 in	94.09 x 59.05 x 11.02 in
Wall-hanging Screw	M6 x 12 mm	M6 x 20mm	M6 x 20mm	M6 x 20mm	M6 x 20mm	M6 x 20mm
VESA Mount Pattern	300 x 300 mm	400 x 300 mm	400 x 300 mm	400 x 300 mm	500 x 400 mm	800 x 400 mm
Net Weight	13.89 lbs	24.94 lbs	36.60 lbs	50.07 lbs	65.04 lbs	163.14 lbs
Gross Weight	19.84 lbs	34.52 lbs	51.85 lbs	75.51 lbs	93.50 lbs	231.49 lbs
Embedded Operating System						
Android Version	Android 11	Android 11	Android 11	Android 11	Android 11	Android 11
CPU	ARM Cortex-A55 x 4	ARM Cortex-A55 x 4	ARM Cortex-A55 x 4	ARM Cortex-A55 x 4	ARM Cortex-A55 x 4	ARM Cortex-A55 x 4
GPU	ARM Mali-G31 MC2	ARM Mali-G31 MC2	ARM Mali-G31 MC2	ARM Mali-G31 MC2	ARM Mali-G31 MC2	ARM Mali-G31 MC2
RAM	2 GB	2 GB	2 GB	2 GB	2 GB	2 GB
ROM	16 GB	16 GB	16 GB	16 GB	16 GB	16 GB
Wi-Fi / Bluetooth	Wi-Fi 5, Bluetooth	Wi-Fi 5, Bluetooth	Wi-Fi 5, Bluetooth	Wi-Fi 5, Bluetooth	Wi-Fi 5, Bluetooth	Wi-Fi 5, Bluetooth
I/O Ports						
Rear Input Port	(3) HDMI in 2.0; (1) USB-A 2.0; (1) USB-A 3.0; (1) LAN In (RJ45); (1) AV In					
Rear Output Port	(1) S/PDIF Out; (1) Audio Output (Jack 3.5 mm)					
Accessories						
Power Cord By Region	9.8 ft					
Remote Control	1 (with AAA Battery 2 set)					