


Which Newline DV Series Solution is Right for You?


DV One



DV Pro



DV Premier



DV Element



Preconfigured Sizes	120", 150", 180"	-	-	-
Pixel Pitch (mm)	1.38, 1.73, 2.08	1.25, 1.5625, 1.875, 2.5	0.625, 0.9375, 1.25, 1.5625	6.67, 8, 10
LED Type	GOB	GOB	MIP	SMD
Refresh Rate (Hz)	3840 Hz	3840 Hz	3840 Hz	3840 Hz
Brightness	Up to 550nits	Up to 1,000 nits	Up to 1,000 nits	Up to 10,000 nits
Contrast Ratio	3,000:1	6000:1	11,000:1 (average)	5,000:1
Pixel Density (dots/m ²)	519,438; 332,440; 230,861	640,000; 409,600; 284,444; 160,000	2,560,000; 1,137,777; 640,000; 409,600	22,500; 15,625; 10,000
Lifespan (Hours)	100,000	100,000	100,000	100,000
IP Rating	IP30	IP30	IP30	IP65
Maintenance	Front	Front	Front	Front and Rear
Input Voltage	AC100V to AC240V, 50 or 60 Hz	AC100V to AC240V, 50 or 60 Hz	AC100V to AC240V, 50 or 60 Hz	AC100V to AC240V, 50 or 60 Hz