



## **PRO SERIES**

55" 65" 75" 86"

### ALL-IN-ONE SOLUTION FOR COLLABORATION

Experience the ease of seamless collaboration with the EDLA-certified all-in-one Solution from Newline Z Pro Series. Tailored for corporate environments, it delivers reliable, secure, immersive, and impactful meetings. Equipped with an optional 4K AI camera, 8-microphone array, and integrated speakers within an interactive display, it allows you to engage in meetings and interactions effortlessly without any constraints.



Enhanced  
Wi-Fi 6



EDLA  
Ready



Unique 3mm  
Narrow Bezel



High Quality  
Sound Incl.  
Subwoofer



Secure User  
Profiles



SDM-S Ready

newline

# Z PRO SERIES SPECIFICATION

Product Information	Model name	TT-5524ZPRO	TT-6524ZPRO	TT-7524ZPRO	TT-8624ZPRO
Display Specifications	Active Screen Size	55"	65"	75"	86"
	Screen Type	LCD (Direct LED Backlight)			
	Resolution	3840 × 2160 (4K)			
	Display Area	1210 × 680 mm	1428 × 803 mm	1650 × 928 mm	1895 × 1066mm
	Display Ratio	16:9			
	Display Color Depth	1,07 Billion			
	Brightness	400 cd/m <sup>2</sup>			
	Contrast Ratio	Typ. 4000:1			
	Response Time	8ms			
	Viewing Angle	178°			
	LCD Refresh Rate	60Hz			
	Life Time	≥ 50,000 hours			
Touch	Touch Surface Technology	Anti-Glare + Anti-Fingerprint + Antimicrobial			
	Transparency	88% ± 3			
	Surface Hardness	9H (Pencil)			
	Touch Sensor	Projective Capacitive (PCAP)			
	Touch Points	Android 20 Points, Windows 40 Points			
Connectivity	Touch Screen Writing Tools	Passive Pen / Fingers			
	USB Data Ports	1*USB Type-C (PD 100W) + 1*USB Type C (no PD)			
		4*Type-B (Touch)			
	Digital Audio-Video Inputs	3*USB 3.0 Type-A Public + 1*USB 3.0 Type-A Android			
		3*HDMI 2.0 + 1*DP			
	Digital Audio-Video Outputs	1*Microphone In			
		1*Audio Line Out			
		1*HDMI Out			
	Integrated PC Slot	1*S/PDIF Out			
	Integrated SDM Slot	Available			
Control Input	Available				
Control Input	1*RS-232				
Network	1*IN & 1*OUT RJ-45 connector				
Wi-Fi	Dual Channel 2.4G+5G, wifi 6				
Bluetooth	BT5.2				
Embedded Operating System	CPU	Arm Cortex-A73 × 4 + Cortex-A53 × 4			
	GPU	Mali-G52 × 8			
	RAM	8GB			
	ROM	64GB			
	External Memory	N/A or 64GB according to market area			
	Operating System	Android 13			
	Wake-on-LAN	Support			
Proximity Sensor	Yes				
Power	Working Voltage	AC100-240V Max 5.5A	AC100-240V Max. 5.5A	AC100-240V Max. 6.2A	AC100-240V Max. 6.5A
	Max Power Consumption	550W	550W	620W	650W
	Standby Power Consumption	< 0,5W	< 0,5W	< 0,5W	< 0,5W
Speaker	Position	Top Front			
	Rated Impedance	6Ω			
	Frequency Response	250Hz - 20KHz when SPL is -10dB			
	Output S.P.L.	80±3dB			
	Max Power Output	20W × 2			
	Subwoofer	N/A	1 × 15W		
Transportation/ Storage	Storage Temperature/ Humidity	-20~60°C / 0~90%RH (non-condensing)			
	Working Temperature/ Humidity	0°C - 40°C / 20% - 80% RH (Non-Condensing)			
	Mounting (Optional)	Wall-Mounted / Mobile Stand			
	Outline Dimensions	1278 × 799 × 80 mm	1497 × 920 × 94 mm	1719 × 1044 × 95 mm	1965 × 1184 × 95 mm
	Packing Dimensions	1414 × 185 × 915 mm	1640 × 207 × 1036 mm	1859 × 227 × 1160 mm	2119 × 250 × 1290 mm
	Net Weight	28 kg	35.5 kg	47 kg	59 kg
Gross Weight	35 kg	46 kg	60.5 kg	75 kg	
Microphone	Position	8-mic array - upper front			
	Max. Distance	6m			

## HEADQUARTERS (TX,USA)

TEL: +1 888 233 0868  
info@newline-interactive.com

## EUROPE OFFICE

TEL: +34 911169178  
info\_eu@newline-interactive.com

## ASIA PACIFIC OFFICE

TEL: +886 3 550 4768  
info\_ap@newline-interactive.com

## INDIA OFFICE

TEL: 1 800 419 0309  
info.in@newline-interactive.com

## KOREA OFFICE

TEL: +82 2 2638 5140  
koreainfo@newline-interactive.com

**newline**