newline

All Stars

Elara is the eighth largest moon of Jupiter. And with a size of only 2% of Europe, the smallest of the four Galilean moons.

















POWER UP YOUR COLLABORATIVE WORKSPACE

Elara Pro, a Google EDLA certified powerhouse, seamlessly integrated with Google Apps. This flexible solution ensures a superior user experience in any workspace. High-precision writing, immersive sound with a subwoofer, NFC-enabled login and hybrid UC redefine collaboration. Reinvent your workspace, setting a new standard in corporate excellence with Elara Pro.



MODULAR SYSTEM

Elevate your experience with our universe of solutions. Customise your display with Newlines' accessories. Mix and match to create the perfect fit.







100 W Powered USB Type-C



Secure Multi User Profiles



Powerful Performance



High Quality Sound incl. Subwoofer



SDM-S Ready



The Newline Interactive Ecosystem enhances productivity with versatile tools that seamlessly integrate with any software or device, meeting all classroom needs.











LASSROOM TOOLS VISUAL COMMUNICATION SOLUTION







ELARA Pro

MODEL		FRONT I/O	
ELARA Pro 65"	TT-6523QCA+	USB Type-C (Powered 100 W)	1
ELARA Pro 75"	TT-7523QCA+	HDMI IN 2.1 with HDCP 2.2	
ELARA Pro 86"	TT-8623QCA+	(4K @60 Hz)	1
227 (1) (1) 10 00	11 0020 0011	USB 3.2 Type-B (Touch)	1
PANEL		USB 3.2 Type-A	2
PANEL	Direct LED (Wide Color Gamut +	Microphone In	1
Backlight	Anti Blue Light)		ı
Glass Surface	Anti-Glare+Anti-Fingerprint, + Antimicrobial Tempered Glass	REAR I/O HDMI IN 2.1 with HDCP 2.2	
Bonding Technology	Certified Zero Bonding	(4K @60 Hz)	2
	65": 1428 x 803 mm	DisplayPort 1.2	1
Display Area	75": 1650 x 928 mm	USB 3.2 Type-B (Touch)	3
	86": 1895 x 1066 mm	USB 3.0 Type-C	1
Display Ratio	16:09	(Powered 15 W)	1
Resolution	3840 x 2160 (4K)	USB 3.0 Type-C	Out x 1
Colours	1,07 Billion	USB 3.2 Type-A	2
Brightness	450 cd/m ²	USB 3.2 Type-A Android	1
Contrast Ratio	5000:1	HDMI OUT 2.0 (4K @60 Hz)	1
Response Time	5 ms	RS232	1
Viewing Angle	178°	RJ45 (Gigabit)	In x 1 / Out x 1
Display Life Time	≥ 50 000 hours	OPS Slot	1
Transparency	> 88%	SPDIF	1
Haze	2 % - 5 %	Audio Line Out	1
Touch Surface Hardness	2 % - 5 % 7H	WIFI Module Slot	1
rouch surface Hardness	ıΠ	SDM-S Slot	1
			1
POWER CONSUMPTION		Power Out Connect (180 W)	
0, 1, 1, 1,*	65": 133 W	NFC	
Standard mode*	75": 150 W		
01 11 14 1 *	86": 168 W	SMART SYSTEM	
Standby Mode*	<0,5 W		Rockchip RK3588 octa-core
TOUGH		SoC Chipset	processor, 4x Cortex-A76 at
TOUCH	0		2.4GHz, 4x Cortex-A55 cores at
Touch Technology	Stellar Touch Technology		1.8 GHz
Touch Points	50 Windows	GPU	Mali Odin G610 MC4
	20 Android/MAC/Linux	RAM	16 GB (DDR4)
Touch Screen Writing Tools	Passive pen, Finger, Fist	Total Storage	320 GB (Expandable)
Number of stylus	2	Operating System	Android 13 Certified
Accuracy	±1 mm	Google EDLA	\checkmark
Real Palm Rejection	✓	Formats Support For Image	JPG, JPEG, BMP, PNG
			MPEG1, MPEG2, MPEG4,
SPEAKER			SorensonH.263, H.263, H.264,
Speaker Position	Front Facing	Formats Support For Video	MVC, AVS, AVS+, WMV3, VC1,
Speaker Rated Impedance	6 Ω		Motion JPEG, VP8, VP9, RV30/
Speaker Freg.Response	250 Hz-20 KHz SPL -10 dB		RV40
Output S.P.L.	90±3 dB		MPEG1/2 @LAYER1; @LAYER2;
Speaker Max.Power Output	20 W x 2		@LAYER3, EAC3, ACC-LC, HEAAC
opeaner max.r over output	20 11 1/2	Formats Support For Audio	VORBIS, LPCM, IMA-ADPCM, MS
SUBWOOFER			ADPCM, G711 A/ MU-LAW, LBR
Speaker Position	Rear Side	W. E. C. D	(COOK), FLAC
•		Wi-Fi 6 + Bluetooth 5.2 Module	Integrated (Replaceable)
Speaker Rated Impedance	4Ω		
Speaker Freq.Response	20 Hz-20 KHz SPL -10 dB 77±2 dB	EXTRA FIRMWARE FEATURES	
O + + O D!	/ /±:/ dR	Multiuser profile	✓
Output S.P.L.			v .
Output S.P.L. Speaker Max.Power Output	20 W x 1	Embedded Google Apps	√
Speaker Max.Power Output			
Speaker Max.Power Output MICROPHONE	20 W x 1	Embedded Google Apps DIMENSIONS / WEIGHT	✓
Speaker Max.Power Output MICROPHONE Mic Possition	20 W x 1 8 Microphone Array Upper Front		√ 65": 1513 x 927 x 118 mm
Speaker Max.Power Output MICROPHONE Mic Possition Pick Up Distance	20 W x 1 8 Microphone Array Upper Front 8 m	DIMENSIONS / WEIGHT	65": 1513 x 927 x 118 mm 75": 1735 x 1051 x 119 mm
Speaker Max.Power Output MICROPHONE Mic Possition	20 W x 1 8 Microphone Array Upper Front 8 m Echo cancellation, Beamforming,	DIMENSIONS / WEIGHT Outline Dimensions*	65": 1513 x 927 x 118 mm 75": 1735 x 1051 x 119 mm 86": 1982 x 1191 x 119 mm
Speaker Max.Power Output MICROPHONE Mic Possition Pick Up Distance	20 W x 1 8 Microphone Array Upper Front 8 m	DIMENSIONS / WEIGHT Outline Dimensions* (Excl. wall mount)	65": 1513 x 927 x 118 mm 75": 1735 x 1051 x 119 mm 86": 1982 x 1191 x 119 mm 65": 39 Kg
Speaker Max.Power Output MICROPHONE Mic Possition Pick Up Distance Mic Performance	20 W x 1 8 Microphone Array Upper Front 8 m Echo cancellation, Beamforming,	DIMENSIONS / WEIGHT Outline Dimensions*	65": 1513 x 927 x 118 mm 75": 1735 x 1051 x 119 mm 86": 1982 x 1191 x 119 mm 65": 39 Kg 75": 52 Kg
MICROPHONE Mic Possition Pick Up Distance	20 W x 1 8 Microphone Array Upper Front 8 m Echo cancellation, Beamforming,	DIMENSIONS / WEIGHT Outline Dimensions* (Excl. wall mount)	65": 1513 x 927 x 118 mm 75": 1735 x 1051 x 119 mm 86": 1982 x 1191 x 119 mm 65": 39 Kg 75": 52 Kg 86": 65 Kg
MICROPHONE Mic Possition Pick Up Distance Mic Performance AI CAMERA MODULE	20 W x 1 8 Microphone Array Upper Front 8 m Echo cancellation, Beamforming, Noise Reduction Included (ModCam+)	Outline Dimensions* (Excl. wall mount) Net Weight*	65": 1513 x 927 x 118 mm 75": 1735 x 1051 x 119 mm 86": 1982 x 1191 x 119 mm 65": 39 Kg 75": 52 Kg 86": 65 Kg 65": 600 x 400 mm
MICROPHONE Mic Possition Pick Up Distance Mic Performance AI CAMERA MODULE Camera	20 W x 1 8 Microphone Array Upper Front 8 m Echo cancellation, Beamforming, Noise Reduction	DIMENSIONS / WEIGHT Outline Dimensions* (Excl. wall mount)	65": 1513 x 927 x 118 mm 75": 1735 x 1051 x 119 mm 86": 1982 x 1191 x 119 mm 65": 39 Kg 75": 52 Kg 86": 65 Kg 65": 600 x 400 mm 75": 800 x 400 mm
MICROPHONE Mic Possition Pick Up Distance Mic Performance AI CAMERA MODULE Camera Camera Resolution	20 W x 1 8 Microphone Array Upper Front 8 m Echo cancellation, Beamforming, Noise Reduction Included (ModCam+) 3840 × 2160/ 30 fps (4K)	Outline Dimensions* (Excl. wall mount) Net Weight*	65": 1513 x 927 x 118 mm 75": 1735 x 1051 x 119 mm 86": 1982 x 1191 x 119 mm 65": 39 Kg 75": 52 Kg 86": 65 Kg 65": 600 x 400 mm



*The provided measures are indicative and subject to further adjustments. They are not yet considered definitive.