



newline **DV ONE+**

135"

163"

189"


216"

All-in-one Direct View **LED** Display

Experience the next generation of LED display technology with DV ONE+, a cutting-edge solution that blends durability and stunning visuals. Built with innovative glue-on-board (GOB) technology, DV ONE+ ensures unmatched reliability, securing LED chips even in the most demanding environments.

Featuring an impressive 110% NTSC color gamut and a 6000:1 contrast ratio, the DV ONE+ guarantees vivid, lifelike visuals with every use. Whether for immersive indoor advertising, high-stakes conference rooms, or precision-driven control rooms, the DV ONE+ delivers smooth, true-to-life imagery with superior refresh rates and grayscale precision.

Designed for effortless installation and maintenance, its sleek, lightweight build makes it a versatile choice for any space. The DV ONE+ also boasts advanced image calibration and processing, providing consistently vibrant, sharp visuals across every display.



4mm Ultra-Thin
Frame



Ultra High Refresh
Rate



135" - 216" Display
FHD Resolution



Plug & Play Design



Ease Maintenance



Lightweight All-in-one
Design

newline **DV** ONE⁺

Display				
Size	135"	163"	189"	216"
Lights Welding Type	GOB			
Resolution	1920 × 1080			
Aspect Ratio	16:9			
Contrast Ratio	6000:1			
Refresh Rate	3840Hz			
Brightness	Up to 550 nits			
Color Gamut	NTSC 110%			
Pixel Type	RGB			
Pixel Pitch	1.56 mm	1.875 mm	2.08 mm	2.34 mm
Viewing Angle	160°			
Maintenance	Front Access			
Lifespan	100,000 hours			
Operating Environment	Temperature: 0°C - 40°C (14°F - 104°F) / Humidity: 10% - 80% RH No Condensation			

Smart System				
CPU	ARM A73*4 + A53*4			
GPU	ARM G52*8			
RAM	4GB			
ROM	32GB			
Wake-on-LAN	YES			
Wake-on-WiFi	YES			
OS Version	Android 13			
Speaker	Avg. 3W × 1, Max. 5W × 1			
Input Voltage	AC100V to AC 240V, 50 or 60 Hz			
Power Required	2	2	3	3
Power Consumption (Standby)	<0.5W <2W when WOL&WOW			

I / O Port				
Side I/O	1 × USB 3.0 Type A, 1 × USB 2.0 Type B 1 × HDMI In, 1 × Type C(PD 65W)			
Rear I/O Ports	1 × HDMI In, 1 × HDMI Out, 1 × USB 3.0 Type A 1 × Line Out, 1 × S/PDIF Out, 1 × LAN In, 1 × RS232			

newline

HEADQUARTERS (TX,USA)
TEL: +1 888 233 0868
info@newline-interactive.com

EUROPE OFFICE
TEL: +34 911169178
info_eu@newline-interactive.com

ASIA PACIFIC OFFICE
TEL: +886 3 550 4768
info_ap@newline-interactive.com

INDIA OFFICE
TEL: 1 800 419 0309
info.in@newline-interactive.com