

# newline



CAST

BROADCAST

DISPLAY MANAGEMENT PLUS

## NT<sup>+</sup> Series

### BRING YOU **BETTER NON-TOUCH** EXPERIENCE

The NT<sup>+</sup> Series is a non-touch display that brings your lessons to life in vivid Ultra-High Definition (4K) resolution. Focus on just the tools you need to get your students engaged in class without paying more for features you won't use.

Wireless cast to the screen from any mobile device, table, desktop, or laptop. Whether you use Windows, Mac, or Chrome, the NT<sup>+</sup> Series lets you share your screen through a wireless connection or through the multiple I/O ports built into the panel. Access your files on your preferred Cloud storage system right on the display. The built-in file from connected USB thumb drives.



Superior  
Image Quality



Access to  
the Cloud



Non-Touch  
Display



android 13  
Impressive  
Embedded OS



Control by  
Remote



Compatible  
with all Devices



Product Information	Model	TT-5523NT	TT-6523NT	TT-7523NT	TT-8623NT	TT-9823NT
Display	Active Screen Size	55"	65"	75"	86"	98"
	Display Area (Decimal point is rounded off)	1210 × 681mm	1429 × 804 mm	1651 × 929mm	1896 × 1066mm	2159 × 1214mm
	Backlight	DLED				
	Display Ratio	16:9				
	Resolution	3840 × 2160				
	Display Colors	1.07G (8 bit + FRC)				
	Brightness Center brightness	400 cd/m²				
	Contrast	Typ. 4000:1				
	Response Time	8 ms (typ.)				
	Viewing Angle	178°				
Life Time	≥50000 hours					
Electrical	Working Voltage	AC100-240V Max. 2.5A	AC100-240V Max. 3.0A	AC100-240V Max. 3.0A	AC100-240V Max. 3.5A	AC100-240V Max. 5.5A
	Power Consumption (Standard Mode)	250W	300W	300W	350W	550W
	Power Consumption (Standby mode)	<0.5W				
Speaker	Speaker position	Downward				
	Rated Impedance	6Ω				
	Freq. Response	200Hz-20KHz SPL -10dB	250Hz-20KHz SPL -10dB			
	Output S.P.L.	80±3dB				
	Avg. Power Output	10W × 2	15W × 2			
	Max. Power Output	15W × 2	20W × 2			
Transportation/Storage	Storage Temperature/Humidity	15 °C ~45 °C / 20~90% RH (Non coagulation)				
	Working Temperature/Humidity	0 °C~40 °C / 20~80% RH (Non coagulation)				
	Installation Method (optional)	wall-mounted, mobile cart				
	Outline Dimension (without wall mount bracket thickness) (Decimal point is rounded off)	1260 × 731 × 71 mm	1479 × 854 × 92 mm	1701 × 979 × 94 mm	1946 × 1116 × 94 mm	2213 × 1293 × 88 mm
	Packing Dimension (Decimal point is rounded off)	1378 × 185 × 840 mm	1604 × 207 × 977 mm	1819 × 227 × 1095 mm	2075 × 250 × 1230 mm	2370 × 1484 × 356 mm
	Net Weight	18±2kg	24±2kg	33±2kg	42±2kg	73±2kg
	Gross Weight	25±2kg	34±2kg	46±2kg	59±2kg	93±2kg
VESA Mount installation position	400 x 400 mm	600 x 400 mm	800 x 400 mm	800 x 400 mm	800 x 600 mm	

Smart System	CPU	Quad core ARM Cortex-A55 1.5GHz,Max.1.9GHz
	GPU	ARM Mali-G52 MP2 (2EE)
	RAM	4G
	ROM	32G
	Android Version	13
	Multimedia File Formats Support	Image: .jpg, .bmp, .png Video: .mkv/.wmv/.avi/.mp4/.mpeg/.mov/.dat/.iso Audio: .mp3/.wma/.m4a/.mp4/.aac
Specialty	Wifi module	Optional: Pluggable WiFi module wifi 5 + wifi 6 +BT 5.2
	Multi-language	Support
	Firmware update	USB/OTA
	Internal camera	N/A
	Standby mode	Support

Ports	Back button	Power, Up, Down, Left, Right, OK, Return, Menu
	Rear input port	Type A USB 2.0 x 3, HDMI IN x 2, HDMI IN(ARC) x 1, LAN INx1 RS232x1, Type C x 1, DP x 1
	Rear output port	HDMI OUT x 1 LAN OUT x1 S/PDIF OUTx1 LINE OUT(3.5mm) x 1
	OPS Slot	N/A

HEADQUARTERS (TX,USA)

TEL: +1 888 233 0868  
info@newline-interactive.com

EUROPE OFFICE

TEL: +34 911169178  
info\_eu@newline-interactive.com

ASIA PACIFIC OFFICE

TEL: +886 3 550 4768  
info\_ap@newline-interactive.com

INDIA OFFICE

TEL: 1 800 419 0309  
info.in@newline-interactive.com

KOREA OFFICE

TEL: +82 2 2638 5140  
koreainfo@newline-interactive.