



Model	DSX-4326	DSX-5526	DSX-6526	DSX-7526	DSX-8626
Picture					
<b>Display</b>					
Active Screen Size	43"	55"	65"	75"	86"
Screen Type	LCD (Direct LED Backlight)	LCD (Direct LED Backlight)	LCD (Direct LED Backlight)	LCD (Direct LED Backlight)	LCD (Direct LED Backlight)
LED Zone	1	1	1	1	1
Display Area (H x V) (Inches)	37.1 x 20.4 in	47.6 x 26.8 in	56.2 x 31.63 in	64.9 x 36.5 in	74.6 x 41.9 in
Display Area (H x V) (mm)	941.184 x 529.416 mm	1209.60 x 680.40 mm	1428.48 x 803.52 mm	1650.24 x 928.26 mm	1895.04 x 1065.96 mm
Display Ratio	16:9	16:9	16:9	16:9	16:9
Resolution	3840 x 2160 (4K)	3840 x 2160 (4K)	3840 x 2160 (4K)	3840 x 2160 (4K)	3840 x 2160 (4K)
Pixel Pitch (Sub Pixel)	0.0817 (H) x 0.2451 (V)	0.105 (H) x 0.315 (V)	0.124 (H) x 0.372 (V)	0.1432 5(H) x 0.4297 5(V)	0.1645 (H) x 0.4935 (V)
Refresh Rate	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz
Colors	1.07Billion	1.07Billion	1.07Billion	1.07Billion	1.07Billion
Color Depth	8bit+FRC	8bit+FRC	8bit+FRC	8bit+FRC	8bit+FRC
After Glass Center Brightness (100% White Field)	700 nits (Typ)	700 nits (Typ)	700 nits (Typ)	700 nits (Typ)	700 nits (Typ)
Typ. Static Contrast Ratio	4000:1	5000:1	5000:1	5500:1	5000:1
Color Gamut	DCIP-3 93% / NTSC 85%	DCIP-3 93% / NTSC 85%	DCIP-3 93% / NTSC 85%	DCIP-3 93% / NTSC 85%	DCIP-3 93% / NTSC 85%
Typ. Response Time	6.5 ms	6.5 ms	6.5 ms	6.5 ms	6.5 ms
Viewing Angle	178°/178°	178°/178°	178°/178°	178°/178°	178°/178°
Display Life Time (MTBF)	50000 hours	50000 hours	50000 hours	50000 hours	50000 hours
OC Haze	25%	25%	25%	25%	25%
Display Orientation	Landscape and Portrait	Landscape and Portrait	Landscape and Portrait	Landscape and Portrait	Landscape and Portrait
Backlight Type	OD22	OD22	OD22	OD22	OD22
Operation Time	24/7	24/7	24/7	24/7	24/7
<b>Smart System</b>					
Chipset	RK3576	RK3576	RK3576	RK3576	RK3576
CPU	Octa Core A72*4+A53*4	Octa Core A72*4+A53*4	Octa Core A72*4+A53*4	Octa Core A72*4+A53*4	Octa Core A72*4+A53*4
GPU	Mali G52 MC3	Mali G52 MC3	Mali G52 MC3	Mali G52 MC3	Mali G52 MC3
RAM	4 GB	4 GB	4 GB	4 GB	4 GB
ROM	32 GB	32 GB	32 GB	32 GB	32 GB
SD Card	No Slot	No Slot	No Slot	No Slot	No Slot
Android Version	Android 14	Android 14	Android 14	Android 14	Android 14
OS Version	AOSP	AOSP	AOSP	AOSP	AOSP
Other in OS	/	/	/	/	/
WiFi Module Model	MT7921AU	MT7921AU	MT7921AU	MT7921AU	MT7921AU
WiFi Version	Wi-Fi 6	Wi-Fi 6	Wi-Fi 6	Wi-Fi 6	Wi-Fi 6
Bluetooth	BTS.2	BTS.2	BTS.2	BTS.2	BTS.2
Wake-on-LAN at power off mode	N/A	N/A	N/A	N/A	N/A
Wake-on-LAN at STR mode	Yes	Yes	Yes	Yes	Yes
Wake-on-LAN at sleep mode	N/A	N/A	N/A	N/A	N/A
Wake-on-LAN after unplug-power off mode	N/A	N/A	N/A	N/A	N/A
Wake-on-LAN after unplug-STR mode	Yes	Yes	Yes	Yes	Yes
Wake-on-WiFi at power off mode	N/A	N/A	N/A	N/A	N/A
Wake-on-WiFi at STR mode	Yes	Yes	Yes	Yes	Yes
Wake-on-WiFi at sleep mode	N/A	N/A	N/A	N/A	N/A
Wake-on-WiFi after unplug-pow	N/A	N/A	N/A	N/A	N/A
Wake-on-WiFi after unplug-STR	Yes	Yes	Yes	Yes	Yes
RTC	Support (Capacitors)	Support (Capacitors)	Support (Capacitors)	Support (Capacitors)	Support (Capacitors)
Top Camera Port	No Top Camera Port	No Top Camera Port	No Top Camera Port	No Top Camera Port	No Top Camera Port
OPS Slot	No OPS Slot	No OPS Slot	No OPS Slot	No OPS Slot	No OPS Slot
SDM-S Slot	No SDM-S Slot	No SDM-S Slot	No SDM-S Slot	No SDM-S Slot	No SDM-S Slot
Built-in Microphone	N/A	N/A	N/A	N/A	N/A
Proximity Sensor	N/A	N/A	N/A	N/A	N/A
<b>I/O Ports</b>					
Rear Input Port	2 x HDMI In	2 x HDMI In	2 x HDMI In	2 x HDMI In	2 x HDMI In
Rear Input Port	0 x DP	0 x DP	0 x DP	0 x DP	0 x DP
Rear Input Port	1 x Type-C (15W Full-function Alt) USB 3.0 downstream/USB 2.0 upstream	1 x Type-C (15W Full-function Alt) USB 3.0 downstream/USB 2.0 upstream	1 x Type-C (15W Full-function Alt) USB 3.0 downstream/USB 2.0 upstream	1 x Type-C (15W Full-function Alt) USB 3.0 downstream/USB 2.0 upstream	1 x Type-C (15W Full-function Alt) USB 3.0 downstream/USB 2.0 upstream
Rear Input Port	1 x USB 3.0 Android	1 x USB 3.0 Android	1 x USB 3.0 Android	1 x USB 3.0 Android	1 x USB 3.0 Android
Rear Input Port	0 x USB 2.0 Android	0 x USB 2.0 Android	0 x USB 2.0 Android	0 x USB 2.0 Android	0 x USB 2.0 Android
Rear Input Port	1 x HDMI Out	1 x HDMI Out	1 x HDMI Out	1 x HDMI Out	1 x HDMI Out
Rear Input Port	1 x S/PDIF Out	1 x S/PDIF Out	1 x S/PDIF Out	1 x S/PDIF Out	1 x S/PDIF Out
Rear Input Port	1 x Line Out	1 x Line Out	1 x Line Out	1 x Line Out	1 x Line Out
Rear Input Port	2 x RS232 (1 x RS232 in; 1 x RS232 out)	2 x RS232 (1 x RS232 in; 1 x RS232 out)	2 x RS232 (1 x RS232 in; 1 x RS232 out)	2 x RS232 (1 x RS232 in; 1 x RS232 out)	2 x RS232 (1 x RS232 in; 1 x RS232 out)
Rear Input Port	1 x LAN In (1000M)	1 x LAN In (1000M)	1 x LAN In (1000M)	1 x LAN In (1000M)	1 x LAN In (1000M)
Rear Input Port	0 x LAN Out	0 x LAN Out	0 x LAN Out	0 x LAN Out	0 x LAN Out
Rear Input Port	0 x AV In	0 x AV In	0 x AV In	0 x AV In	0 x AV In
<b>Sound</b>					
Speaker Position	Back Bottom	Back Bottom	Back Bottom	Back Bottom	Back Bottom
Speaker Power (Max.)	N/A	N/A	N/A	N/A	N/A
Speaker Power (Typ.)	L + R 2x10W	L + R 2x10W	L + R 2x10W	L + R 2x10W	L + R 2x10W
Speaker Rated Impedance	6Ω	6Ω	6Ω	6Ω	6Ω
Speaker Freq. Response	300~15K Hz	300~15K Hz	300~15K Hz	300~15K Hz	300~15K Hz
Output S.P.L.	-10dB	-10dB	-10dB	-10dB	-10dB
Subwoofer (Max.)	N/A	N/A	N/A	N/A	N/A
<b>Electronic Capacity</b>					
Working Voltage	AC100-240V	AC100-240V	AC100-240V	AC100-240V	AC100-240V
Working Power Consumption (Normal)	≤168W	≤212W	≤264W	≤280W	≤360W
Working Power Consumption (Full Load)	≤210W	≤265W	≤330W	≤350W	≤450W
Power Consumption (Standby Mode)	<0.5W	<0.5W	<0.5W	<0.5W	<0.5W

Power Consumption (Wake-on-LAN or Wake-on-WiFi)	<2W	<2W	<2W	<2W	<2W
<b>Structure</b>					
Outline Dimension (without wall mount/stand) (inches)	38.2 x 21.9 x 2.8 in	48.7 x 27.9 x 2.8 in	57.4 x 32.8 x 2.7 in	66.1 x 37.7 x 2.7 in	75.9 x 43.3 x 2.7 in
Outline Dimension (without wall mount/stand) (mm)	969.9 x 558.0 x 70 mm	1237.0 x 707.8 x 70 mm	1457.7 x 832.4 x 68.8 mm	1678.8 x 956.8 x 68.8 mm	1928.6 x 1099.2 x 69 mm
Bezel Width (T/L/R)	12.8 mm (0.5 in)	12.8 mm (0.5 in)	12.8 mm (0.5 in)	12.8 mm (0.5 in)	13.9 mm (0.55 in)
Bottom Bezel Width	12.8 mm (0.5 in)	12.8 mm (0.5 in)	12.8 mm (0.5 in)	12.8 mm (0.5 in)	13.9 mm (0.55 in)
Bottom Bezel Width including IR Receiver	12.8 mm (0.5 in)	12.8 mm (0.5 in)	12.8 mm (0.5 in)	12.8 mm (0.5 in)	13.9 mm (0.55 in)
<b>Transportation &amp; Storage</b>					
Storage	-4~140°F (-20~60°C)	-4~140°F (-20~60°C)	-4~140°F (-20~60°C)	-4~140°F (-20~60°C)	-4~140°F (-20~60°C)
Temperature&Humidity	0~90%RH (non-condensing)	0~90%RH (non-condensing)	0~90%RH (non-condensing)	0~90%RH (non-condensing)	0~90%RH (non-condensing)
Working	32~104°F (0~40°C)	32~104°F (0~40°C)	32~104°F (0~40°C)	32~104°F (0~40°C)	32~104°F (0~40°C)
Temperature/Humidity	20~80%RH (non-condensing)	20~80%RH (non-condensing)	20~80%RH (non-condensing)	20~80%RH (non-condensing)	20~80%RH (non-condensing)
Installation Method (optional)	Wall-mounted	Wall-mounted	Wall-mounted	Wall-mounted	Wall-mounted
Packing Dimension (inches)	42.3 x 25.7 x 5.7 in	54.7 x 32.7 x 5.7 in	64.6 x 38.9 x 6.5 in	72.4 x 43.4 x 6.9 in	82.7 x 49.2 x 9.1 in
Packing Dimension (mm)	1075 x 652 x 144 mm	1390 x 830 x 144 mm	1640 x 990 x 164 mm	1840 x 1103 x 177 mm	2100 x 1250 x 230 mm
VESA Mount Pattern	300 x 300 mm	400 x 400 mm	500 x 500 mm	500 x 500 mm	700 x 500 mm
Wall-hanging Screw	M6 x 18 mm	M6 x 18 mm	M8 x 16 mm	M8 x 16 mm	M8 x 16 mm
Net Weight	17.6 lbs (8 kg)	28.6 lbs (13 kg)	39 lbs (17.7 kg)	61 lbs (27.7 kg)	90. lbs (41 kg)
Gross Weight	25.3 lbs (11.5 kg)	40.8 lbs (18.5 kg)	60.6 lbs (27.5 kg)	86.2 lbs (39.1 kg)	135.8 lbs (61.6 kg)
<b>Accessories</b>					
<p style="text-align: center;">Power Cable: 1 x UK; 1 x EU; 1 x UL  1 x Remote Control (RC870 RCA), AAA Battery for Remote Control  1 x RS232 (3.5mm) to DB9 (3m/9.8 ft)  1 x RS232 (3.5mm) to RS232 (3.5mm) (3m/9.8 ft)</p>					