



newline **DV** GO POSTER



Portable for
Flexible Use



Multiple
Splicing



Multidevice
Compatible



Networked
Centralized Control



Offline
Playback



High
Protection

DIGITAL SIGNAGE THAT MOVES WITH YOU

The Newline DV Go Poster brings ultra-high-definition visuals wherever you need them. Designed for mobility and versatility, this transportable LED display is perfect for digital signage, wayfinding, and dynamic spaces that demand flexibility without sacrificing quality.

Built with durable COB technology, the DV Go Poster ensures reliable performance on the go. Use it as a standalone display or connect multiple units to create an instant video wall—setup is fast, management is simple, and playback runs automatically, even offline. From trade shows to storefronts, the DV Go Poster makes it easy to move, set up, and showcase your message anywhere.

newline

950 W Bethany Drive, Suite 330
Allen, TX 75013

Toll-Free: 888-233-0868
Local: 972-468-9728

sales@newline-interactive.com
www.newline-interactive.com

DV GO POSTER

Newline DV Go Poster Direct View Mobile LED Display Specifications

Model	DV-GoPoster
Pixel Configuration	COB
Pixel Pitch	1.5625 mm
Module Size (mm) (WxHxD)	300 x 168.75
Module Size (inches) (WxHxD)	11.81 x 6.64
External Dimension (mm) (WxHxD)	610 x 1806 x 500
External Dimension (inches) (WxHxD)	24 x 71.1 x 19.7
Resolution (WxH)	384 x 1080
Interface	(1) HDMI, (1) USB, (1) RJ45
WIFI	2.4GHz, AP/STA
Remote Control	WiFi, RJ45, 5G
Audio	5W x 2
Overall Weight (Without Base)	92.6 lbs (42 kg)
Brightness (nits)	600
Viewing Angle (H/V)	170°/170°
Max. Power Consumption (W)	400
Avg. Power Consumption (W)	133
Working Voltage (V)	AC100~240 (50~60Hz)
Frame Rate (Hz)	50/60
Refresh Rate (Hz)	3840
Gray Scale (bit)	14~16
Operation Temp	14~104°F (-10~+40°C)
Operation Humidity (RH)	10%~80%, no condensation
Lifetime (H)	100,000
Maintenance Mode	Front
IP Level	IP41
Bracket Type	Mobile