

newline



Secure Access with
NFC Card Reader




USB-C with
100W Power



New Chipset
with Android 15



Built-in
8-Mic Array



Improved 16GB
RAM & 256GB ROM



Up to 50 Points
of Touch



25W Speaker &
20W Subwoofer



Google
EDLA Certified

UNMATCHED POWER. **UNSTOPPABLE COLLABORATION.**

Newline Interactive proudly introduces the Q Pro Elite Series, the newest member of its flagship Q Pro line, designed to deliver unmatched performance and engagement in classrooms and educational spaces. Packed with upgraded hardware, the Q Pro Elite raises the bar with 16GB of RAM and 256GB of storage, offering faster processing and ample space for applications, lessons, and collaboration tools. Running on Android 15, it provides a future-ready, secure, and highly customizable platform for educators and campus staff.

The Q Pro Elite also enhances communication and collaboration with a built-in 8-mic array, ensuring crystal-clear audio pickup for hybrid learning and video conferencing. A built-in NFC card reader streamlines user access and personalization, allowing multiple profiles and quick sign-ins with a simple tap. Combined with its USB-C port with 100W power delivery, the Q Pro Elite supports faster charging and expanded connectivity, making it easier than ever to plug in, power up, and get started.

For an even more immersive experience, the Q Pro Elite features an enhanced sound system with dual 25W speakers and a powerful 20W subwoofer, delivering rich, room-filling audio that makes every lesson or presentation more impactful. From its performance-driven upgrades to its intuitive design, the Q Pro Elite Series empowers educators and students to connect, collaborate, and create like never before.

newline

950 W Bethany Drive, Suite 330
Allen, TX 75013

Toll-Free: 888-233-0868
Local: 972-468-9728

sales@newline-interactive.com
www.newline-interactive.com



Q Pro Elite Series

Model	TT-6525QELT	TT-7525QELT	TT-8625QELT
Display			
Active Screen Size	65"	75"	86"
Screen Type	LCD (Direct LED Backlight)	LCD (Direct LED Backlight)	LCD (Direct LED Backlight)
Display Area	56.22 x 31.61 in	64.96 x 36.53 in	74.6 x 41.96 in
Display Ratio	16:9	16:9	16:9
Resolution	3840 x 2160 (4K)	3840 x 2160 (4K)	3840 x 2160 (4K)
Refresh Rate	60 Hz	60 Hz	60 Hz
Colors	1.07billion (8bit+2bit FRC)	1.07billion (8bit+2bit FRC)	1.07billion (8bit+2bit FRC)
After Glass Center Brightness (100% White Field)	400 nits	400 nits	400 nits
Typ. Static Contrast Ratio	4000:1	4000:1	4000:1
Typ. Response Time	8ms	8ms	8ms
Viewing Angle	178°	178°	178°
Display Life Time (MTBF)	50000 hours	50000 hours	50000 hours
Continuous Run Time	24/7	24/7	24/7
Smart System			
CPU	ARM A76*4 + A55*4	ARM A76*4 + A55*4	ARM A76*4 + A55*4
RAM	16GB	16GB	16GB
ROM	256GB	256GB	256GB
Android Version	Android 15	Android 15	Android 15
OS Version	EDLA	EDLA	EDLA
Top Camera Port	Yes	Yes	Yes
OPS Slot	Yes	Yes	Yes
WiFi Version	WiFi 5: 2.4G+5G / WiFi 6: 2.4G+5G	WiFi 5: 2.4G+5G / WiFi 6: 2.4G+5G	WiFi 5: 2.4G+5G / WiFi 6: 2.4G+5G
Bluetooth	BT5.2	BT5.2	BT5.2
Built-in Microphone	8-Mic Array, Upper Front	8-Mic Array, Upper Front	8-Mic Array, Upper Front
NFC	Yes	Yes	Yes
Ports			
Front/Side I/O	1 (PD 100W); 1 x HDMI In (2.0, 4K@60Hz); 1 x USB Touch; 2 x USB 3.2; 1 x Mic In		
Rear I/O	2 x HDMI In (2.0, 4K@60Hz); 1 x DP1.2 (4K@60Hz); 1 x Type C (no PD); 1 x Type C Out (no PD, 4K@60Hz); 2 x USB 3.2 Public; 1 x USB 3.2 Android; 3 x USB Touch 3.0; 1 x S/PDIF Out; 1 x Line Out; 1 x RS232; 1 x LAN In; 1 x LAN Out		
Speakers			
Speaker Position	Bottom Front	Bottom Front	Bottom Front
Speaker Power (Max.)	25Wx2 Max / 15Wx2 Avg.	25Wx2 Max / 15Wx2 Avg.	25Wx2 Max / 15Wx2 Avg.
Output S.P.L.	80±3dB	80±3dB	80±3dB
Subwoofer			
Speaker Position	Back Center	Back Center	Back Center
Speaker Power (Max.)	20Wx1 Max / 15Wx1 Avg.	20Wx1 Max / 15Wx1 Avg.	20Wx1 Max / 15Wx1 Avg.
Output S.P.L.	77±3dB	77±3dB	77±3dB
Touch Panel			
Glass Surface Treatment	Anti-Glare + Anti-Fingerprint + Antimicrobial Tempered Glass	Anti-Glare + Anti-Fingerprint + Antimicrobial Tempered Glass	Anti-Glare + Anti-Fingerprint + Antimicrobial Tempered Glass
Touch Solution	IR	IR	IR
Touch Points	Android 50 / Windows 50	Android 50 / Windows 50	Android 50 / Windows 50
Electronic Capacity			
Working Voltage	AC100-240V	AC100-240V	AC100-240V
Working Power Consumption	<=550W (Standby ≤0.5W)	<=550W (Standby ≤0.5W)	<=550W (Standby ≤0.5W)
Transportation & Storage			
Storage Temperature & Humidity	-4~140°F / 0~90%RH (non-condensing)	-4~140°F / 0~90%RH (non-condensing)	-4~140°F / 0~90%RH (non-condensing)
Working Temperature/Humidity	32~104°F / 20~80%RH (non-condensing)	32~104°F / 20~80%RH (non-condensing)	32~104°F / 20~80%RH (non-condensing)
Installation Method (optional)	Wall-mounted / Mobile Stand	Wall-mounted / Mobile Stand	Wall-mounted / Mobile Stand
Outline Dimension (without wall mount bracket)	59.56 x 36.49 x 4.68 in	68.3 x 41.37 x 4.8 in	78.03 x 46.88 x 4.68 in
Packing Dimension	4.56 x 40.78 x 8.14 in	73.18 x 45.66 x 8.14 in	83.42 x 50.78 x 8.93 in
VESA Mount Pattern	600x400 mm	800x400 mm	800x400 mm
Net Weight / Gross Weight	85.98 lbs / 110.23 lbs	113.53 lbs / 143.3 lbs	142.19 lbs / 181.88 lbs