



# newline



IP56-rated  
Weatherproof  
Construction



Portrait or  
Landscape  
Orientation



Ultra High  
Brightness for  
Outdoor Visibility



Fast, reliable  
connectivity with  
Wi-Fi 6



Built-in Newline  
Signage Pro  
Integration



Enhanced  
Android 14 OS



Available in sizes  
43"-86"



Designed for  
All-Season  
Outdoor Use

## OUTDOOR DISPLAYS FOR SMARTER CAMPUSES

The Newline XRT Series is a purpose-built outdoor display designed to support the dynamic communication needs of higher education environments. With ultra-high brightness and screen sizes ranging from 43" to 86", the XRT Series delivers clear, readable content—even in direct sunlight—making it ideal for campuses with open quads, walkways, athletic facilities, and outdoor gathering spaces.

Engineered for year-round campus use, the XRT Series features an IP56-rated, fully weatherproof construction that protects against rain, dust, and changing environmental conditions. This durable design ensures reliable operation across seasons without the need for additional enclosures, helping institutions reduce maintenance while maintaining consistent visibility. Whether used for campus announcements, event promotions, or emergency messaging, the XRT Series is built to perform in demanding outdoor settings.

Support for both portrait and landscape orientation provides flexibility to match a wide range of campus applications. From wayfinding and class schedules to digital signage, donor recognition, and branded messaging, content can be displayed in the format that best fits each location. With its combination of brightness, durability, and versatility, the Newline XRT Series enables colleges and universities to communicate effectively, enhance campus experiences, and keep students, faculty, and visitors informed—wherever campus life happens.

newline

950 W Bethany Drive, Suite 330  
Allen, TX 75013

Toll-Free: 888-233-0868  
Local: 972-468-9728

sales@newline-interactive.com  
www.newline-interactive.com

Model	XRT-4326	XRT-5526	XRT-6526	XRT-7526	XRT-8626
<b>Display</b>					
Active Screen Size	43"	55"	65"	75"	86"
Screen Type	LCD	LCD	LCD	LCD	LCD
Display Ratio	16:9	16:9	16:9	16:9	16:9
Resolution	3840 x 2160 (4K)	3840 x 2160 (4K)	3840 x 2160 (4K)	3840 x 2160 (4K)	3840 x 2160 (4K)
Refresh Rate	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz
Colors	1.07 Billion	1.07 Billion	1.07 Billion	1.07 Billion	1.07 Billion
Color Depth	10 bit (8 bit+FRC)	10 bit (8 bit+FRC)	10 bit (8 bit+FRC)	10 bit (8 bit+FRC)	10 bit (8 bit+FRC)
Color Gamut(TYP.)	≥72% NTSC	≥72% NTSC	≥72% NTSC	≥72% NTSC	≥72% NTSC
After Glass Center Brightness (Min.) (100% White Field)	2000 nits	2000 nits	2000 nits	2000 nits	2000 nits
After Glass Center Brightness (TYP.) (100% White Field)	2500 nits	2500 nits	2500 nits	2500 nits	2500 nits
Viewing Angle	178/178	178/178	178/178	178/178	178/178
Working time	24/7	24/7	24/7	24/7	24/7
Display Life Time (MTBF)	50000 hours	50000 hours	50000 hours	50000 hours	50000 hours
Backlight Type	DLED-OD28	DLED-OD28	DLED-OD28	DLED-OD28	DLED-OD28
<b>Panel</b>					
Glass Surface Treatment	AG	AG	AG	AG	AG
Glass Surface Haze	≥25%	≥25%	≥25%	≥25%	≥25%
Glass Hardness	IK10	IK10	IK10	IK10	IK10
Glass Thickness	5 mm (0.19685 in)	5 mm (0.19685 in)	5 mm (0.19685 in)	5 mm (0.19685 in)	5 mm (0.19685 in)
Black border width	Four equilateral sides: 35.9 mm (1.413386 in)	Four equilateral sides: 35.9 mm (1.413386 in)	Four equilateral sides: 35.9 mm (1.413386 in)	Four equilateral sides: 35.9 mm (1.413386 in)	Four equilateral sides: 35.9 mm (1.413386 in)
Bonding Type	Optical bonding	Optical bonding	Optical bonding	Optical bonding	Optical bonding
<b>Sound</b>					
Speaker Position	Back	Back	Back	Back	Back
Speaker Power (Max.)	10W x 2	10W x 2	10W x 2	10W x 2	10W x 2
<b>Electronic Capacity</b>					
Working Voltage	AC100-240V 50-60hz	AC100-240V 50-60hz	AC100-240V 50-60hz	AC100-240V 50-60hz	AC100-240V 50-60hz
<b>Smart System</b>					
RAM	4	4	4	4	4
ROM	32	32	32	32	32
Android Version	Android 14	Android 14	Android 14	Android 14	Android 14
OPS Slot	N/A	N/A	N/A	N/A	N/A
Brightness sensor	Yes	Yes	Yes	Yes	Yes
WiFi Version	WiFi 6	WiFi 6	WiFi 6	WiFi 6	WiFi 6
Bluetooth	BT 5.2	BT 5.2	BT 5.2	BT 5.2	BT 5.2
<b>Transportation &amp; Storage</b>					
Storage Temperature & Humidity	-22~140°F (-30~60°C) 10~85%RH (non-condensing)	-22~140°F (-30~60°C) 10~85%RH (non-condensing)	-22~140°F (-30~60°C) 10~85%RH (non-condensing)	-22~140°F (-30~60°C) 10~85%RH (non-condensing)	-22~140°F (-30~60°C) 10~85%RH (non-condensing)
Working Temperature/Humidity	-22~140°F (-30~60°C) 10~85%RH (non-condensing)	-22~140°F (-30~60°C) 10~85%RH (non-condensing)	-22~140°F (-30~60°C) 10~85%RH (non-condensing)	-22~140°F (-30~60°C) 10~85%RH (non-condensing)	-22~140°F (-30~60°C) 10~85%RH (non-condensing)
Installation Method	On wall; Support structural design for hanging/embedding	On wall; Support structural design for hanging/embedding	On wall; Support structural design for hanging/embedding	On wall; Support structural design for hanging/embedding	On wall; Support structural design for hanging/embedding
Mounting Method	Landscape/Portrait	Landscape/Portrait	Landscape/Portrait	Landscape/Portrait	Landscape/Portrait
Mounting Vesa	300 x 400 mm	400 x 400 mm	400 x 400 mm	400 x 400 mm	400 x 400 mm
IP Rating	IP56	IP56	IP56	IP56	IP56
Display Weight	74.53 lbs (33.8 kg)	112.46 lbs (51 kg)	145.53 lbs (66 kg)	187.43 lbs (85 kg)	249.39 lbs (113.1 kg)
<b>Rear I/O Ports</b>					
2 x HDMI In (2.1, 4K@60Hz,HDCP2.3), 1 x ARC; 1 x Type C (PD 15W, full functions); 1 x USB 3.2 Gen 1 Public; 1 x Line Out; 1 x LAN In; 1 x RS232C (In); 1 x RS232C (Out)					
<b>Certification</b>					
FCC (EMC: Class A); UL (Safety); Energy star ES8.0					