

newline



Secure Access with
NFC Card Reader




USB-C with
100W Power



New Chipset
with Android 16



Built-in
8-Mic Array



16GB RAM &
256GB ROM



Up to 50 Points
of Touch



25W Speaker &
25W Subwoofer



Google
EDLA Certified

ELITE LEARNING STARTS HERE

Newline Interactive proudly introduces the newly upgraded Q Ultra Elite Series, designed to deliver unmatched performance and engagement in classrooms and educational spaces. Packed with upgraded hardware, the Q Ultra Elite raises the bar with 16GB of RAM and 256GB of storage, offering faster processing and ample space for applications, lessons, and collaboration tools. Running on next-gen Android 16, it provides a future-ready, secure, and highly customizable platform for educators and campus staff.

The Q Ultra Elite also enhances communication and collaboration with a built-in 8-mic array, ensuring crystal-clear audio pickup for hybrid learning and video conferencing. A built-in NFC card reader streamlines user access and personalization, allowing multiple profiles and quick sign-ins with a simple tap. Combined with its USB-C port with 100W power delivery, the Q Ultra Elite supports faster charging and expanded connectivity, making it easier than ever to plug in, power up, and get started.

For an even more immersive experience, the Q Ultra Elite features an enhanced sound system with dual 25W speakers and a powerful 25W subwoofer, delivering rich, room-filling audio that makes every lesson or presentation more impactful. From its performance-driven upgrades to its intuitive design, the Q Ultra Elite Series empowers educators and students to connect, collaborate, and create like never before.

newline

950 W Bethany Drive, Suite 330
Allen, TX 75013

Toll-Free: 888-233-0868
Local: 972-468-9728

sales@newline-interactive.com
www.newline-interactive.com

Q Ultra Elite Series

Model	TT-5526QELT	TT-6526QELT	TT-7526QELT	TT-8626QELT	TT-9826QELT
Display					
Screen Size	55"	65"	75"	86"	98"
Display Area (W x H)	47.62 x 26.79 in	56.24 x 31.63 in	64.97 x 36.5 in	74.6 x 41.97 in	84.99 x 47.81 in
Screen Type	LCD (Direct LED Backlight)	LCD (Direct LED Backlight)	LCD (Direct LED Backlight)	LCD (Direct LED Backlight)	LCD (Direct LED Backlight)
Resolution	3840 x 2160 pixels	3840 x 2160 pixels	3840 x 2160 pixels	3840 x 2160 pixels	3840 x 2160 pixels
Display Ratio	16:9	16:9	16:9	16:9	16:9
Brightness	550nit	550nit	550nit	550nit	550nit
Display Colors	1.07 billion (8 bit)	1.07 billion (8 bit)	1.07 billion (8 bit)	1.07 billion (8 bit)	1.07 billion (8 bit)
Contrast Ratio	5000:1	5000:1	5000:1	5000:1	5000:1
Response Time	6.5 ms	6.5 ms	6.5 ms	8 ms	6.5 ms
Viewing Angle	178°	178°	178°	178°	178°
Lifetime Hours	50,000 hours	50,000 hours	50,000 hours	50,000 hours	50,000 hours
Continuous Run Time	24/7	24/7	24/7	24/7	24/7
Built-in Microphone	8-Mic Array, Upper Front	8-Mic Array, Upper Front	8-Mic Array, Upper Front	8-Mic Array, Upper Front	8-Mic Array, Upper Front
NFC	Yes	Yes	Yes	Yes	Yes
Speakers					
Speaker Position	Bottom Front	Bottom Front	Bottom Front	Bottom Front	Bottom Front
Speaker Max Power Output	(2) 25 W	(2) 25 W	(2) 25 W	(2) 25 W	(2) 25 W
Subwoofer Position	Back Center	Back Center	Back Center	Back Center	Back Center
Subwoofer Max Power Output	25W	25W	25W	25W	25W
Power					
Working Power Consumption	≤ 600 W	≤ 650 W	≤ 650 W	≤ 800 W	≤ 900 W
Working Voltage	AC 100-240V, 50/60Hz	AC 100-240V, 50/60Hz	AC 100-240V, 50/60Hz	AC 100-240V, 50/60Hz	AC 100-240V, 50/60Hz
Touch					
Glass Surface Technology	Anti-Glare + Anti-Fingerprint + Anti-microbial Tempered Glass				
Touch Points	Up to 50 Points	Up to 50 Points	Up to 50 Points	Up to 50 Points	Up to 50 Points
Touch Sensor	Infrared Touch	Infrared Touch	Infrared Touch	Infrared Touch	Infrared Touch
Writing Tools	Stylus or Finger	Stylus or Finger	Stylus or Finger	Stylus or Finger	Stylus or Finger
Transportation/Storage					
Storage Temp/Humidity	-20~60°C (-4~140°F) / 0~90%RH (non-condensing)				
Working Temp/Humidity	0~40°C (32~104°F) / 20~80%RH (non-condensing)				
Mounting Options	Wall-mount or Mobile Stand	Wall-mount or Mobile Stand	Wall-mount or Mobile Stand	Wall-mount or Mobile Stand	Wall-mount or Mobile Stand
VESA Mount Pattern	400x400mm	600x400mm	800x400mm	800x400mm	800x600mm
Bezel Widths	Top: 1.05 in (26.8 mm) Left & Right: 0.68 in (17.4 mm) Bottom: 2.39 in (60.9 mm)	Top: 1.07 in (27.2 mm) Left & Right: 0.70 in (17.8 mm) Bottom: 2.39 in (60.9 mm)	Top: 1.07 in (27.2 mm) Left & Right: 0.70 in (17.8 mm) Bottom: 2.39 in (60.9 mm)	Top: 1.07 in (27.2 mm) Left & Right: 0.70 in (17.8 mm) Bottom: 2.39 in (60.9 mm)	Top: 1.15 in (29.3 mm) Left & Right: 0.82 in (20.8 mm) Bottom: 2.79 in (71 mm)
Outline Dimension (without wall mount bracket)	50.39 x 31.85 x 4.29 in (1280 x 809 x 109 mm)	58.54 x 36.14 x 4.76 in (1487 x 918 x 121 mm)	67.28 x 41.02 x 4.76 in (1709 x 1042 x 121 mm)	76.97 x 46.49 x 4.8 in (1955 x 1181 x 122 mm)	88.07 x 53.31 x 4.72 in (2237 x 1354 x 120 mm)
Packing Dimension	55.66 x 36.02 x 7.28 in (1414 x 915 x 185 mm)	64.33 x 39.96 x 7.28 in (1634 x 1015 x 185 mm)	72.59 x 45.07 x 8.15 in (1844 x 1145 x 207 mm)	82.44 x 50.39 x 8.93 in (2094 x 1280 x 227 mm)	93.89 x 62.72 x 11.22 in (2385 x 1593 x 285 mm [include single pallet])
Net Weight	61.73 lbs (28.0 KG)	73.85 lbs (33.5 KG)	98.11 lbs (44.5 KG)	131.17 lbs (59.5 KG)	231.45 lbs (105.0 KG)
Gross Weight	78.26 lbs (35.5 KG)	92.59 lbs (42 KG)	124.56 lbs (56.5 KG)	157.63 lbs (71.5 KG)	276.68 lbs (125.5 KG)
Embedded Operating System					
RAM	16 GB	16 GB	16 GB	16 GB	16 GB
ROM	256 GB	256 GB	256 GB	256 GB	256 GB
Android Version	16	16	16	16	16
WiFi Version	WiFi 7 (IEEE 802.11be): 2.4G+5G+6G / WiFi 5: 2.4G+5G				
Bluetooth	BT 6.0	BT 6.0	BT 6.0	BT 6.0	BT 6.0
Ports					
Front Interface Inputs	1 x Type C (PD 100W, full functions); 1 x HDMI In (2.1, 4K@60Hz,HDCP2.3); 1 x USB Touch 3.0; 2 x USB 3.2 Gen 1; 1 x Mic In				
Rear Inputs/Outputs	1 x OPS slot; 2 x HDMI In (2.1, 4K@60Hz,HDCP2.3), 1*ARC; 1 x DP1.2 (4K@60Hz); 1 x Type C (PD 15W, full functions); 1 x Type C Out (no PD, 4K@60Hz); 2 x USB 3.2 Gen 1 Public; 1 x USB 3.2 Gen 1 Android; 3 x USB Touch 3.0; 1 x HDMI Out; 1 x S/PDIF Out; 1 x Line Out; 1 x RS232; 1 x Mic In; 1 x LAN In; 1 x LAN Out				
Camera Module Port Location	Top-center of panel, USB-C 3.0 connection				