

# newline



Secure Access with  
NFC Card Reader




USB-C with  
100W Power



New Chipset  
with Android 16



Built-in  
8-Mic Array



16GB RAM &  
256GB ROM



Up to 50 Points  
of Touch



25W Speaker &  
25W Subwoofer



Google  
EDLA Certified

## ELITE INNOVATION FOR MODERN CAMPUSES

Newline Interactive proudly introduces the newly upgraded Q Ultra Elite Series, designed to elevate teaching, learning, and collaboration across higher education. Built with upgraded performance in mind, the Q Ultra Elite is equipped with 16GB of RAM and 256GB of storage, ensuring faster processing power and plenty of space for advanced applications, research tools, and collaborative platforms. Running on next-gen Android 16, it provides a secure, customizable, and future-ready foundation that supports the diverse needs of colleges and universities.

The Q Ultra Elite enhances communication in lecture halls and hybrid learning environments with its built-in 8-mic array, capturing every voice with clarity during discussions and remote sessions. With a built-in NFC card reader, faculty and students can access personalized profiles and settings with a simple tap, streamlining transitions between users. Its USB-C port with 100W power delivery not only simplifies device connectivity but also keeps laptops and mobile devices charged, making it effortless to plug in and start class or presentations.

Delivering an immersive audio experience, the Q Ultra Elite boasts dual 25W speakers and a 25W subwoofer, filling large lecture spaces with powerful, crystal-clear sound that enhances both presentations and multimedia content. With its performance-driven upgrades and user-friendly design, the Q Ultra Elite Series empowers higher education institutions to foster collaboration, inspire engagement, and support innovation in every academic setting.

newline

950 W Bethany Drive, Suite 330  
Allen, TX 75013

Toll-Free: 888-233-0868  
Local: 972-468-9728

sales@newline-interactive.com  
www.newline-interactive.com

# Q Ultra Elite Series

Model	TT-5526QELT	TT-6526QELT	TT-7526QELT	TT-8626QELT	TT-9826QELT
<b>Display</b>					
Screen Size	55"	65"	75"	86"	98"
Display Area (W x H)	47.62 x 26.79 in	56.24 x 31.63 in	64.97 x 36.5 in	74.6 x 41.97 in	84.99 x 47.81 in
Screen Type	LCD (Direct LED Backlight)	LCD (Direct LED Backlight)	LCD (Direct LED Backlight)	LCD (Direct LED Backlight)	LCD (Direct LED Backlight)
Resolution	3840 x 2160 pixels	3840 x 2160 pixels	3840 x 2160 pixels	3840 x 2160 pixels	3840 x 2160 pixels
Display Ratio	16:9	16:9	16:9	16:9	16:9
Brightness	550nit	550nit	550nit	550nit	550nit
Display Colors	1.07 billion (8 bit)	1.07 billion (8 bit)	1.07 billion (8 bit)	1.07 billion (8 bit)	1.07 billion (8 bit)
Contrast Ratio	5000:1	5000:1	5000:1	5000:1	5000:1
Response Time	6.5 ms	6.5 ms	6.5 ms	8 ms	6.5 ms
Viewing Angle	178°	178°	178°	178°	178°
Lifetime Hours	50,000 hours	50,000 hours	50,000 hours	50,000 hours	50,000 hours
Continuous Run Time	24/7	24/7	24/7	24/7	24/7
Built-in Microphone	8-Mic Array, Upper Front	8-Mic Array, Upper Front	8-Mic Array, Upper Front	8-Mic Array, Upper Front	8-Mic Array, Upper Front
NFC	Yes	Yes	Yes	Yes	Yes
<b>Speakers</b>					
Speaker Position	Bottom Front	Bottom Front	Bottom Front	Bottom Front	Bottom Front
Speaker Max Power Output	(2) 25 W	(2) 25 W	(2) 25 W	(2) 25 W	(2) 25 W
Subwoofer Position	Back Center	Back Center	Back Center	Back Center	Back Center
Subwoofer Max Power Output	25W	25W	25W	25W	25W
<b>Power</b>					
Working Power Consumption	≤ 600 W	≤ 650 W	≤ 650 W	≤ 800 W	≤ 900 W
Working Voltage	AC 100-240V, 50/60Hz	AC 100-240V, 50/60Hz	AC 100-240V, 50/60Hz	AC 100-240V, 50/60Hz	AC 100-240V, 50/60Hz
<b>Touch</b>					
Glass Surface Technology	Anti-Glare + Anti-Fingerprint + Anti-microbial Tempered Glass				
Touch Points	Up to 50 Points	Up to 50 Points	Up to 50 Points	Up to 50 Points	Up to 50 Points
Touch Sensor	Infrared Touch	Infrared Touch	Infrared Touch	Infrared Touch	Infrared Touch
Writing Tools	Stylus or Finger	Stylus or Finger	Stylus or Finger	Stylus or Finger	Stylus or Finger
<b>Transportation/Storage</b>					
Storage Temp/Humidity	-20~60°C (-4~140°F) / 0~90%RH (non-condensing)				
Working Temp/Humidity	0~40°C (32~104°F) / 20~80%RH (non-condensing)				
Mounting Options	Wall-mount or Mobile Stand	Wall-mount or Mobile Stand	Wall-mount or Mobile Stand	Wall-mount or Mobile Stand	Wall-mount or Mobile Stand
VESA Mount Pattern	400x400mm	600x400mm	800x400mm	800x400mm	800x600mm
Bezel Widths	Top: 1.05 in (26.8 mm) Left & Right: 0.68 in (17.4 mm) Bottom: 2.39 in (60.9 mm)	Top: 1.07 in (27.2 mm) Left & Right: 0.70 in (17.8 mm) Bottom: 2.39 in (60.9 mm)	Top: 1.07 in (27.2 mm) Left & Right: 0.70 in (17.8 mm) Bottom: 2.39 in (60.9 mm)	Top: 1.07 in (27.2 mm) Left & Right: 0.70 in (17.8 mm) Bottom: 2.39 in (60.9 mm)	Top: 1.15 in (29.3 mm) Left & Right: 0.82 in (20.8 mm) Bottom: 2.79 in (71 mm)
Outline Dimension (without wall mount bracket)	50.39 x 31.85 x 4.29 in (1280 x 809 x 109 mm)	58.54 x 36.14 x 4.76 in (1487 x 918 x 121 mm)	67.28 x 41.02 x 4.76 in (1709 x 1042 x 121 mm)	76.97 x 46.49 x 4.8 in (1955 x 1181 x 122 mm)	88.07 x 53.31 x 4.72 in (2237 x 1354 x 120 mm)
Packing Dimension	55.66 x 36.02 x 7.28 in (1414 x 915 x 185 mm)	64.33 x 39.96 x 7.28 in (1634 x 1015 x 185 mm)	72.59 x 45.07 x 8.15 in (1844 x 1145 x 207 mm)	82.44 x 50.39 x 8.93 in (2094 x 1280 x 227 mm)	93.89 x 62.72 x 11.22 in (2385 x 1593 x 285 mm [include single pallet])
Net Weight	61.73 lbs (28.0 KG)	73.85 lbs (33.5 KG)	98.11 lbs (44.5 KG)	131.17 lbs (59.5 KG)	231.45 lbs (105.0 KG)
Gross Weight	78.26 lbs (35.5 KG)	92.59 lbs (42 KG)	124.56 lbs (56.5 KG)	157.63 lbs (71.5 KG)	276.68 lbs (125.5 KG)
<b>Embedded Operating System</b>					
RAM	16 GB	16 GB	16 GB	16 GB	16 GB
ROM	256 GB	256 GB	256 GB	256 GB	256 GB
Android Version	16	16	16	16	16
WiFi Version	WiFi 7 (IEEE 802.11be): 2.4G+5G+6G / WiFi 5: 2.4G+5G				
Bluetooth	BT 6.0	BT 6.0	BT 6.0	BT 6.0	BT 6.0
<b>Ports</b>					
Front Interface Inputs	1 x Type C (PD 100W, full functions); 1 x HDMI In (2.1, 4K@60Hz,HDCP2.3); 1 x USB Touch 3.0; 2 x USB 3.2 Gen 1; 1 x Mic In				
Rear Inputs/Outputs	1 x OPS slot; 2 x HDMI In (2.1, 4K@60Hz,HDCP2.3), 1*ARC; 1 x DP1.2 (4K@60Hz); 1 x Type C (PD 15W, full functions); 1 x Type C Out (no PD, 4K@60Hz); 2 x USB 3.2 Gen 1 Public; 1 x USB 3.2 Gen 1 Android; 3 x USB Touch 3.0; 1 x HDMI Out; 1 x S/PDIF Out; 1 x Line Out; 1 x RS232; 1 x Mic In; 1 x LAN In; 1 x LAN Out				
Camera Module Port Location	Top-center of panel, USB-C 3.0 connection				