

newline



Google EDLA
Certified




USB Type-C
with 65W Power



Android 16 with
User Profiles



Camera Module
Capable



16GB RAM &
128GB ROM



Up to 50 Points
of Touch



Embedded 20W
Speakers



Compatible
with all Devices

ULTRA PERFORMANCE FOR HIGHER LEARNING

Bring your campus to life with the Newline Q Ultra Series, a high-performance interactive display solution with native Google EDLA Certification. Seamless integration with Google Apps enhances instruction by providing easy access to Google Docs, Sheets, Slides, Drive, and other applications.

The Q Ultra Series revolutionizes the educational experience, offering an immersive audio-visual journey. Whether you're seated in the front row or the back, the 4K display ensures crystal-clear images with a wide 178° viewing angle. Its integrated 20W speakers ensure every student can hear clearly.

Starting a lecture is effortless with the Q Ultra's plug-and-play design. Simply connect your laptop through the convenient USB Type-C cable, and class can begin. Plus, the Q Ultra Series will keep your laptop charged with 65 Watts of power.

Powered by the latest and most advanced Android 14 operating system, the Q Ultra Series is highly customizable, allowing for tailored user profiles. Packed with upgraded hardware, the Q Ultra raises the bar with 16GB of RAM and 128GB of storage, offering faster processing and ample space for applications, lessons, and collaboration tools.

Integrate the Q Ultra Series on your campus to cultivate a dynamic and immersive learning environment, offering students opportunities to engage and acquire knowledge through innovative and exciting methods.

newline

950 W Bethany Drive, Suite 330
Allen, TX 75013

Toll-Free: 888-233-0868
Local: 972-468-9728

sales@newline-interactive.com
www.newline-interactive.com

Q Ultra Series

Model	TT-5526QULT	TT-6526QULT	TT-7526QULT	TT-8626QULT	TT-9826QULT
Display					
Screen Size	55"	65"	75"	86"	98"
Display Area (W x H)	47.62 x 26.79 in	56.24 x 31.63 in	64.97 x 36.5 in	74.6 x 41.97 in	84.99 x 47.81 in
Screen Type	LCD (Direct LED Backlight)	LCD (Direct LED Backlight)	LCD (Direct LED Backlight)	LCD (Direct LED Backlight)	LCD (Direct LED Backlight)
Resolution	3840 x 2160 pixels	3840 x 2160 pixels	3840 x 2160 pixels	3840 x 2160 pixels	3840 x 2160 pixels
Display Ratio	16:9	16:9	16:9	16:9	16:9
Brightness	550nit	550nit	550nit	550nit	550nit
Display Colors	1.07 billion (8 bit)	1.07 billion (8 bit)	1.07 billion (8 bit)	1.07 billion (8 bit)	1.07 billion (8 bit)
Contrast Ratio	5000:1	5000:1	5000:1	5000:1	5000:1
Response Time	6.5 ms	6.5 ms	6.5 ms	8 ms	6.5 ms
Viewing Angle	178°	178°	178°	178°	178°
Lifetime Hours	50,000 hours	50,000 hours	50,000 hours	50,000 hours	50,000 hours
Continuous Run Time	24/7	24/7	24/7	24/7	24/7
Speakers					
Position	Bottom Front	Bottom Front	Bottom Front	Bottom Front	Bottom Front
Max Power Output	(2) 20W	(2) 20W	(2) 20W	(2) 20W	(2) 20W
Power					
Max Power Consumption	≤ 550 W	≤ 600 W	≤ 600 W	≤ 750 W	≤ 850 W
Working Voltage	AC 100-240V, 50/60Hz	AC 100-240V, 50/60Hz	AC 100-240V, 50/60Hz	AC 100-240V, 50/60Hz	AC 100-240V, 50/60Hz
Touch					
Glass Surface Technology	Anti-Glare + Anti-Fingerprint + Anti-microbial Tempered Glass				
Touch Points	Up to 50 Points	Up to 50 Points	Up to 50 Points	Up to 50 Points	Up to 50 Points
Touch Sensor	Infrared Touch	Infrared Touch	Infrared Touch	Infrared Touch	Infrared Touch
Writing Tools	Stylus or Finger	Stylus or Finger	Stylus or Finger	Stylus or Finger	Stylus or Finger
Transportation/Storage					
Storage Temp/Humidity	-20~60°C (-4~140°F) / 0~90%RH (non-condensing)				
Working Temp/Humidity	0~40°C (32~104°F) / 20~80%RH (non-condensing)				
Mounting Options	Wall-mount or Mobile Stand	Wall-mount or Mobile Stand	Wall-mount or Mobile Stand	Wall-mount or Mobile Stand	Wall-mount or Mobile Stand
VESA Mount Pattern	400x400mm	600x400mm	800x400mm	800x400mm	800x600mm
Bezel Widths	Top & Left & Right: 0.68 in (17.4mm) Bottom: 2.39 in (60.9mm)	Top & Left & Right: 0.7 in (17.8mm) Bottom: 2.39 in (60.9mm)	Top & Left & Right: 0.7 in (17.8mm) Bottom: 2.39 in (60.9mm)	Top & Left & Right: 0.7 in (17.8mm) Bottom: 2.39 in (60.9mm)	Top & Left & Right: 0.82 in (20.8mm) Bottom: 2.79 in (71mm)
Outline Dimension (without wall mount bracket)	50.39 x 31.46 x 4.29 in (1280 x 799 x 109 mm)	58.54 x 35.78 x 4.76 in (1487 x 909 x 121 mm)	67.28 x 40.67 x 4.8 in (1709 x 1033 x 122 mm)	76.97 x 46.1 x 4.8 in (1955 x 1171 x 122 mm)	88.07 x 52.95 x 4.72 in (2237 x 1345 x 122 mm)
Packing Dimension	55.66 x 36.02 x 7.28 in (1414 x 915 x 185 mm)	64.33 x 39.96 x 7.28 in (1634 x 1015 x 185 mm)	72.59 x 45.07 x 8.15 in (1844 x 1145 x 207 mm)	82.44 x 50.39 x 8.93 in (2094 x 1280 x 227 mm)	93.89 x 62.72 x 11.22 in (2385 x 1593 x 285 mm [include single pallet])
Net Weight	61.73 lbs (28.0 KG)	73.85 lbs (33.5 KG)	98.11 lbs (44.5 KG)	131.17 lbs (59.5 KG)	231.45 lbs (105.0 KG)
Gross Weight	78.26 lbs (35.5 KG)	92.59 lbs (42 KG)	124.56 lbs (56.5 KG)	157.63 lbs (71.5 KG)	276.68 lbs (125.5 KG)
Embedded Operating System					
RAM	16 GB	16 GB	16 GB	16 GB	16 GB
ROM	128 GB	128 GB	128 GB	128 GB	128 GB
Android Version	16	16	16	16	16
WiFi Version	WiFi 6 (IEEE 802.11ax) : 2.4G+5G / WiFi 5: 2.4G+5G				
Bluetooth	BT5.2	BT5.2	BT5.2	BT5.2	BT5.2
Ports					
Front Interface Inputs	1 x Type C (PD 65W, full functions); 1 x HDMI In (2.1, 4K@60Hz, HDCP2.3); 1 x USB Touch 3.0; 2 x USB 3.2 Gen 1; 1 x Mic In				
Rear Inputs/Outputs	1 x OPS slot; 2 x HDMI In (2.1, 4K@60Hz, HDCP2.3), 1*ARC; 1 x DP1.2 (4K@60Hz); 1 x Type C (PD 15W, full functions); 1 x Type C Out (no PD, 4K@60Hz); 2 x USB 3.2 Gen 1 Public; 1 x USB 3.2 Gen 1 Android; 3 x USB Touch 3.0; 1 x HDMI Out; 1 x S/PDIF Out; 1 x Line Out; 1 x RS232; 1 x Mic In; 1 x LAN In; 1 x LAN Out				
Camera Module Port Location	Top-center of panel, USB-C 3.0 connection				