

NEXT-GENERATION **COMMERCIAL DISPLAY**

Captivate customers and drive sales with our advanced commercial display. Its 700nits high brightness and 85% NTSC color gamut ensure stunning visibility in any retail lighting. Engineered for 24/7 reliability, the sleek design supports both landscape and portrait modes for versatile placement. Powered by a superior CPU/GPU and Android 14, it seamlessly runs our Newline Signage Pro platform for centralized, effortless content management of promotions and pricing. Comprehensive ports like USB-C and RS232 allow for easy integration.



GO BEYOND WITH CLICK2CAST!


Compatible with the Newline Click2Cast dongle, a hassle-free hardware solution for one click casting. Just a single button to initiate wireless screen casting effortlessly.




NEWLINE INTERACTIVE ECOSYSTEM

The Newline Interactive Ecosystem streamlines operations with seamless tools for content sharing, signage management, and display control, optimizing workflows


- CAST+
- CAST
- BROADCAST
- DISPLAY MANAGEMENT PLUS
- APP STORE
- SIGNAGE PRO




Edge-to-Edge
Ultra Slim Design




Crystal Clear
Image



4K HD
Resolution



Day Long
Run



Wide Range
of Sizes

- 43"
- 55"
- 65"
- 75"
- 86"

MODEL	DSX 43"	DSX55"	DSX 65"	DSX 75"	DSX 86"
	DSX-4326	DSX-5526	DSX-6526	DSX-7526	DSX-8626

PANEL

Display Type	Direct LED	Direct LED	Direct LED	Direct LED	Direct LED
Display Area	941 x 529 mm	1210 x 680 mm	1428 x 804 mm	1650 x 928 mm	1895 x 1066 mm
Display Ratio	16:9	16:9	16:9	16:9	16:9
Resolution	3840 x 2160 4K UHD	3840 x 2160 4K UHD	3840 x 2160 4K UHD	3840 x 2160 4K UHD	3840 x 2160 4K UHD
Colours	1,07 Billion	1,07 Billion	1,07 Billion	1,07 Billion	1,07 Billion
Brightness	700 nits	700 nits	700 nits	700 nits	700 nits
Contrast Ratio	5000:1	5000:1	5000:1	5000:1	5000:1
Response Time	6,5 ms	6,5 ms	6,5 ms	6,5 ms	6,5 ms
Viewing Angle	178°	178°	178°	178°	178°
Operating Time	24 hrs / 7 days	24 hrs / 7 days	24 hrs / 7 days	24 hrs / 7 days	24 hrs / 7 days
Refresh Rate	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz
Display Lifetime	50 000 hours	50 000 hours	50 000 hours	50 000 hours	50 000 hours
Haze	2%	2%	2%	2%	2%

POWER CONSUMPTION

Standard Mode	80 W	105 W	155 W	200 W	230 W
Standby Mode	0,5 W	0,5 W	0,5 W	0,5 W	0,5 W

SPEAKERS

Speakers Position	Back	Back	Back	Back	Back
Speakers Max. Power	2 x 15 W	2 x 15 W	2 x 15 W	2 x 15 W	2 x 15 W
Impedance	6Ω	6Ω	6Ω	6Ω	6Ω
Output S.P.L	-10dB	-10dB	-10dB	-10dB	-10dB

SMART SYSTEM

CPU	Octa Core A72*4+A53*4
GPU	Mali G52 MC3
RAM	4 GB
Storage	32 GB
Operating System	Android 14
Wi-Fi	Wi-Fi 6
Bluetooth	5.2

PORTS I/O

Rear	2x HDMI In; 1 x Type-C (15W Full-function Alt); 1 x USB 3.0 Android; 1 x HDMI Out; 1 x S/PDIF Out; 1 x line Out; 2 x RS232C (RS232C in *1, RS232C out *1); 1 x LAN In (1000M)
------	---

DIMENSIONS / WEIGHT / STORAGE

Net Weight (Kg)	8	13	17,7	27,7	41
Gross Weight (Kg)	11,5	18,5	27,5	39,1	60
Outline Dim. (mm)	970 x 558 x 70	1237 x 708 x 70	1458 x 832 x 89	1679 x 957 x 69	1929 x 1099 x 69
Packaging Dim. (mm)	1075 x 142 x 652	1350 x 144 x 830	1640 x 164 x 990	1840 x 177x 1103	2100 x 230 x 1250
Operating/ Storage Temperature	0°C - 40°C / -20°C - 60°C	0°C - 40°C / -20°C - 60°C	0°C - 40°C / -20°C - 60°C	0°C - 40°C / -20°C - 60°C	0°C - 40°C / -20°C - 60°C
Operating/ Storage Humidity	0% - 90% / 20% - 80% (non-condensing)	0% - 90% / 20% - 80% (non-condensing)	0% - 90% / 20% - 80% (non-condensing)	0% - 90% / 20% - 80% (non-condensing)	0% - 90% / 20% - 80% (non-condensing)
VESA (mm)	300 x 300	400 x 400	500 x 500	500 x 500	700 x 500

ACCESSORIES

Power Cabels(UK)*1 + (EU)*1, Remete Control(RC870 RCA)*1, AAA Battery fer Remete Control, RS232(3.5mm) to D89*1 (3M), RS232(3.5mm)*1 (3M)

NEWLINE COMPATIBILITY

Software Ecosystem	Cast, Broadcast, App Store, Display Management Plus, Signage Pro, Cast+ (Available in App Store)
Accessories	Click2Cast