newline

DV GO POSTER

DIRECT VIEW MOBILE LED DISPLAY







DIGITAL SIGNAGE THAT MOVES WITH YOU

The Newline DV Go Poster brings ultra-high-definition visuals wherever you need them. Designed for mobility and versatility, this transportable LED display is perfect for digital signage, wayfinding and dynamic spaces that demand flexibility without sacrificing quality.

- Folding Design / Space-saving
- Seamless Splicing up to FHD
- Plug-and-Play Setup
- Synchronous & Asynchronous
- Dual-Face via Folding
- Packaging Including Flight Case
- COB LED Module
- Smart Wireless Control

DIGITAL SIGNAGE THAT MOVES WITH YOU

Standalone operation or instant multi-unit video wall, with simple setup and reliable offline playback.

DV GO POSTER

Product **Specifications**

Not-Foldable

1. PHYSICAL PARAMETERS

Pixel Pitch	1,25 / 1,56 / 1,875 / 2,5 mm
Lights Welding Type	COB: 1,25 / 1,56 / 1,875 GOB: 2,5
Resolution	480 x 1350 384 x 1080 320 x 900 240 x 675
Display Size	600 x 1687,5 mm
Outline Dimension	610 x 1806 x 500 mm
Cabinet Material	Die-cast aluminum

2. OPTICAL PARAMETERS

Brightness	800 nits
Refresh Rate	3840 Hz
Grayscale	14~16 bit
Contrast Ratio	10.000:1
Color Temperature	2.000 - 10.000 K
Viewing Angle (H/V)	170° / 170°
Frame Rate	50/60 Hz

3. SPEAKERS

Audio	5 W x 2

4. SMART SYSTEM

Controller	TB50
OS	Android 11
CPU	Quad-core ARM A55@1,8 GHz
RAM	1 GB
ROM	32 GB
Communication Mode	170WiFi, RJ45, 5G° / 170°
Display Mode	Synchronous/Asynchronous

5. I/O PORTS

HDMI	1 x In, 1 x Out
RJ45	x 1
USB	x 1

6. ELECTRICAL PARAMETERS

Power Consumption (Max.)	1,25 / 1,56 / 1,87: 400 W 2,5: 380 W
Power Consumption (Avg.)	1,25 / 1,56 / 1,87: 133 W 2,5: 126 W

7. APPLICATION PARAMETERS

Maintenance	Front
Operation Temperature	-10 ~ +40 °C
Operation Humidity	10% ~ 80% RH
IP Rating	IP41
Exterior/Interior	Indoor
Lifespan	100,000
Packing Dimension	1900 x 610 x 860 mm
Net Weight	42 Kg
Gross Weight	80 Kg

8. OTHERS

Packing	Wooden Box

Foldable

1. PHYSICAL PARAMETERS

Pixel Pitch	1,25 / 1,56 / 1,875 / 2,5 mm
Lights Welding Type	COB: 1,25 / 1,56 / 1,875 GOB: 2,5
Resolution	480 x 1620 384 x 1296 320 x 1080 240 x 810
Display Size	600 x 2025 mm
Outline Dimension	610 x 2143,4 x 500 mm
Cabinet Material	Die-cast aluminum

2. OPTICAL PARAMETERS

Brightness	800 nits
Refresh Rate	3840 Hz
Grayscale	14~16 bit
Contrast Ratio	10.000:1
Color Temperature	2.000 - 10.000 K
Viewing Angle (H/V)	170° / 170°
Frame Rate	50/60 Hz

3. SPEAKERS

Audio	5 W x 2

4. SMART SYSTEM

Controller	TB50
OS	Android 11
CPU	Quad-core ARM A55@1,8 GHz
RAM	1 GB
ROM	32 GB
Communication Mode	170WiFi, RJ45, 5G° / 170°
Display Mode	Synchronous/Asynchronous

5. I/O PORTS

HDMI	1 x In, 1 x Out
RJ45	x 1
USB	x 1

6. ELECTRICAL PARAMETERS

Power Consumption (Max.)	450 W
Power Consumption (Avg.)	150 W

7. APPLICATION PARAMETERS

Maintenance	Front
Operation Temperature	-10 ~ +40 °C
Operation Humidity	10% ~ 80% RH
IP Rating	IP41
Exterior/Interior	Indoor
Lifespan	100,000
Packing Dimension	627 x 696 x 1215 mm
Net Weight	45 Kg
Gross Weight	60 Kg

8. OTHERS

Packing	Flight Case Included

The provided measures are indicative and subject to further adjustments. They are not yet considered definitive.

newline

newline-interactive.com/eu
Contact us at: info_eu@newline-interactive.com / Support_eu@newline-interactive.com / Technical Support Hotline: +34 91 804 31 79

2026 Newline Interactive Europe S.L. All Rights Reserved. Newline logo is a registered trademark in the United States and other countries around the world. Product specifications may vary by region, please contact our local offices for details. All weights and dimensions are approximate. Actual product features and specifications are subject to change without notice. This material may include corporate names and trademarks of third parties which are the properties of the third parties respectively.