

newline S ELITE SERIES

65" 75" 86"

SMART PERFORMANCE
READY FOR EVERY WORKSPACE

The Newline S Elite is designed for modern meeting rooms and shared workspaces, delivering the perfect balance of performance, collaboration, and value. Powered by Android 16 with Google EDLA certification, it provides secure access to Google services and familiar productivity tools, helping teams collaborate more efficiently.

Featuring a 4K UHD Zero Bonding display, responsive 50-point touch, Wi-Fi 6, 65W USB-C connectivity, and powerful 20W ×2 speakers, S Elite supports seamless presentations, productive meetings, and everyday collaboration. Available in 65”, 75”, and 86”, it offers a dependable interactive display solution for organizations of every size.

- Android 16
- Google EDLA Certified
- Wi-Fi 6
- 50-Point Multi-Touch
- 65W USB-C Connectivity
- 20W ×2 Speakers

This document will be kept updated. For promotional use only and please do not publish in the public.
Copyright © 2026 NEWLINE. All rights reserved.

S ELITE SPECIFICATION

Model		S ELITE		
Display	Active Screen Size	65"	75"	86"
	Screen Type	LCD (Direct LED Backlight)		
	Display Area	1428.48mm (H) × 803.52mm (V)	1650.24 mm (H) × 928.26 mm (V)	1895.04mm (H) ×1065.96mm (V)
	Display Ratio	16:9		
	Refresh Rate	60 Hz		
	Resolution	3840 x 2160 (4K)		
	Colors	1.07 Billion		
	Color Depth	10bit (8bit+FRC)		
	After Glass Center Brightness (Typ.)	≥ 400 cd/m²		
	Static Contrast Ratio (Typ.)	5500:1	1200:1	4000:1
	Pannel Measured Static Contrast Ratio (Typ.)	5000:1	1500:1	5000:1
	Response Time (Typ.)	6.5 ms	8 ms	8 ms
	Viewing Angle	178°		
	Display Life Time (MTBF)	50000 hours		
Smart System	CPU	2 × A78 + 6 × A55		
	GPU	G57 MC2		
	NPU	9 TOPS		
	RAM	8 GB		
	ROM	64 GB		
	Android Version	Android 16		
	OS Version	EDLA		
	OPS Slot	Yes		
	Wi-Fi Module	Wi-Fi 6: 2.4G + 5G		
	Wi-Fi Standard	IEEE 802.11a/b/g/n/ac/ax		
	Bluetooth	BT5.2		
I/O Ports	Front/Side I/O	1 × USB-C In (PD 65W, full functions)		
		1 × HDMI In (2.1, 4K@60Hz) HDCP 2.3		
		1 × USB Touch		
		2 x USB 3.2 Gen 1		
		1 × Mic In (3.5mm Mini Jack)		
	Rear I/O	2 x HDMI In (2.1, 4K@60Hz) HDCP2.3		
		1 × DP In (1.2,4K@60Hz)		
		1 × USB-C In (15W, full functions)		
		2 × USB 3.2 Gen 1 Public		
		2 × USB Touch		
		1 × HDMI Out (2.1, 4K@60 Hz) HDCP 2.3		
		1 × S/PDIF Out		
		1 x Line Out		
		1 x RS-232		
		1 × VGA In		
		1 × VGA Audio In		
		1 × LAN In 10/100/1000		
		1 × LAN Out 10/100/1000		
Speakers	Speaker Position	Bottom Front		
	Speaker Power (Max.)	20W x 2		
	Speaker Power (Avg.)	15W x 2		
Touch Panel	Glass Surface Treatment	Anti-Glare		
	Glass Hardness	Mohs 7 / 9H Pencil Hardness		
	Glass Thickness	3.2 mm		
	Glass Transparency	88% ± 3%		
	Bonding Type	Zero bonding		
	Touch Solution	32,768 × 32,768 px		
	Touch Accuracy	±0.5 mm (90% of center part)		
	Touch Scan Rate	600Hz		
	Touch Points	Windows / Android: 50 Touch Points Mac / Linux / ChromeOS: 20 Touch Points		
Electronic Capacity	Working Voltage	AC200-240V		
	Working Power Consumption	380W	420W	480W
	Power Consumption (Standby Mode)	<0.5W		
Transportation & Storage	Storage Temperature&Humidity	-20~60°C		
	Working Temperature/Humidity	0~40°C		
	Installation Method (optional)	Wall-mounted / Mobile stand		
	Outline Dimension (without wall mount bracket)	1485 x 109 x 897mm	1707 x 104 x 1021mm	1953 x 109 x 1159mm
	Packing Dimension	1634 x 185 x 1015mm	1844 x 207 x 1145mm	2094 x 227 x 1280mm
	Net Weight	33.5 KG	44.5 KG	55.5 KG
	Gross Weight	42.5 KG	55.0 KG	68.0 KG

HEADQUARTERS(TX,USA)
TEL: +1 888 233 0868
info@newline-interactive.com

EUROPE OFFICE
TEL: +34 911169178
info_eu@newline-interactive.com

ASIA PACIFIC OFFICE
TEL: +886 3 550 4768
info_ap@newline-interactive.com

INDIA OFFICE
TEL: 1 800 419 0309
info.in@newline-interactive.com

newline